Hardware Guide

Drawer Slides | Shelving | Closet and Specialty Hardware







Contents

Drawer Slides	ł
Shelving	6 int
Closet and Specialty Hardware	92

Knape & Vogt's names and logos and all related trademarks, including series numbers (e.g., 85 and 185 Series), trademarks and other intellectual property are the property of Knape & Vogt Manufacturing Company and cannot be used without its express prior written permission.

Customer Service: 1.800.253.1561

1



Drawer Slides

How to Choose a Drawer Slide
Light-Duty Drawer Slides91175 3/4 Extension Center Under Drawer Slide101300 3/4 Extension Drawer Slides111805 Epoxy-Coated Drawer Slide128350 3/4 Extension Drawer Slides134400 Low Profile Full Extension Drawer Slide144450 Low Profile Full Extension Soft-Close Drawer Slide15
Medium-Duty Drawer Slides
8400 Full Extension Box or File Drawer Slide
8405 Over Travel Box or File Drawer Slide
8407 Full Extension Box or File Drawer Slide with Shelf Tabs 20
8414 Full Extension Hold-Out Drawer Slide
8417, 8419, 8400RV Self-Closing Drawer Slides
8420, 8425 Metal Cabinet and Drawer Slide
8450FM, 8455FM Soft-Close Drawer Slides
KV GSlide GS4200, GS4205 Drawer Slide
KV GSlide GS4260 Push-Open Drawer Slide
KV GSlide GS4270 Soft-Close Drawer Slide
KV Tru-Trac TT100 Full Extension Ball-Bearing Drawer Slide 28
KV DuriSlide 4500 Ball-Bearing Drawer Slide
Undermount Drawer Slides
KV GSlide GS2070 Full Extension Undermount Drawer Slide
MuV+ Full Extension Undermount Drawer Slide
MuV+34 Full Extension Undermount Drawer Slide
MuV+HD Heavy-Duty Full Extension Undermount Drawer Slide 34
MuV+34HD Heavy-Duty Full Extension Undermount Drawer Slide 35 $$

Heavy-Duty Drawer Slides	. 36
6500, 6505 Box or File Drawer Slide	
8500, 8505 Heavy-Duty File or Lateral Drawer Slides	38
8520, 8525 Extra Heavy-Duty File or Lateral Drawer Slides	39
8600, 8605 Heavy-Duty Drawer Slide	40
8620, 8625 Metal Cabinet and Drawer Slide	41
8650FM, 8655FM Heavy-Duty Soft-Close Drawer Slide	42
8810, 8815 Heavy-Duty Drawer Slide	
8820, 8825 Heavy-Duty Metal Cabinet and Drawer Slide	
8900 Extra Heavy-Duty Full Extension Drawer Slide	
8908 Extra Heavy-Duty Full Extension Locking Drawer Slides	46
Specialty Drawer Slides	. 47
6300 Corrosion Resistant Finish Drawer Slide	
6400 Stainless Steel Drawer Slide	49
8000 Over Travel Undermount Pantry Drawer Slide	
8500T Lateral File Drawer Systems	
Overhead Door and Desk Slides	. 52
4461D 5/8 Extension Variable Height Keyboard Slide	
8150, 8157 3/4 Extension Variable Height Keyboard Slides	
8250 3/4 Extension Variable Height Pencil or Center Drawer Slide	
8050 Hinged Door Slide	56
Door Slides and Hinge Kits	. 57
8070, 8071, 8072 Pivot Door Slides	
8080, 8081, 8082 Pivot Door Slides	
8091, 8092 Pivot Door Slides	
4x4 Pocket Door Full Overlay Kit	
KV Hinge Kits	62

How to Choose a Drawer Slide

Design Factors

Each drawer slide model has unique performance characteristics that are determined by the intended application for which it is designed. There are many different slides available for a variety of applications; choose the slide that best fits your application.

Length. Slide length is a key factor. Typically, the longer the slide, the less load it will carry and vice versa.

Travel. Travel is the maximum extension compared to the closed length. Most slides are either 3/4 or full travel. Special extension lengths are available with modified travel. In general, the longer the travel, the less load a slide can carry and vice versa.

- A 3/4 travel slide has extension to approximately 75% of its length.
- A full travel slide has extension approximately equal to its length.
- An over travel slide extends beyond its length.

Width. Drawer width affects the rigidity of the installation. In wide drawers, the slides will rack from side to side. Excessive racking can degrade performance and shorten slide life.

Action. The type of mechanism used to carry the load affects slide performance, motion, noise, and the "fit and feel." KV slides use rollers, ball-bearings, friction fits, or any combination in achieving movement. In general, superior action requires more rollers or ball-bearings to support and distribute large loads. Size. In addition to a slide's load rating, the physical size of the application is a consideration. Drawers having unusual width, depth, or height especially require careful consideration to determine which slide best suits the application.

Operating Clearance. Drawer slides operate within a specified clearance (the space between the drawer and the case). The clearance must be strictly held within the specified tolerances. When the clearance is too wide or too narrow, the slide will experience additional forces and stresses that will reduce its expected performance and life.

Case Goods Construction and Materials. Slides perform better when mounted in rigidly constructed furniture. Construction with soft or thin materials often results in flexing. This causes the drawer to rack from

side to side, placing considerable stress on the slides. Do not use drawer slides as support members carrying structural loads.

Application Factors

Location of Pull. The location of the drawer handle affects slide performance. Center pull positions "are recommended because they permit a balanced pull force evenly carried by both slides. Side or edge pulls put more force directly on one slide than the other, causing the two slides to progress at different speeds. The additional force required to open and close the drawer hinders performance and shortens slide life. Installation. Most slide designs require installation in a single position. Carefully study the application before installing the slides in different or abnormal positions.

- Orientation. Slides should not be installed in an orientation other than for their intended usage. For example, a slide designed for Side-mounting may lose 75 percent or more of its loadcarrying capacity if mounted flat underneath a drawer.
- 2. Location. Drawer construction, pull position, and type of load are all key considerations to determine the best location to fasten the slides.
- 3. Balance. Most slides are designed for use in pairs. For example, suspending a load from just one side (cantilevered load) causes excessive stress and may result in premature slide failure.

Fastening. For best performance, slides require proper fastening. Use the recommended fasteners in sufficient quantity to properly secure the slide. Too few fasteners can cause the slide to pull loose and cause damage. Abnormal fastening methods should be carefully evaluated, because methods such as gluing, riveting, or welding may have unanticipated effects.

Load Factors

Alignment. Slides run in a straight motion. The more precisely the slides are aligned, the less chance they will work against each other.

Load Ratings. KV designates drawer slides in "Pound Class" categories, and uses dynamic (rather than static) loading to determine load ratings. The "Pound Class" categories are used within the slide industry as general guidelines for drawer slide selection. These categories are not the same as actual load ratings. Load ratings vary based on slide length, application, and case goods construction.

The categories provide a reference point in selecting which slide may fit a particular application. The Pound Class designations are not intended as a substitute for actual product testing. Proper slide selection may be significantly different from the Pound Class designation, depending on the application or other use factors. Representative testing of the selected drawer slide in the fully configured application is the only way to assure proper performance, durability, and safety.

Static Loads. A static load is a resting load without any motion.
Static load capacity is significantly higher than dynamic load capacity.

Dynamic Loads. A dynamic load is a load in motion. When a dynamic load gains momentum, it induces more stress and fatigue. Slides must withstand more forces when in motion than when still.

Dynamic loads affect the life and performance of any slide. Other load

performance of any slide. Other load factors affecting performance are:

- An evenly or unevenly distributed load
- 2. A centered or off-centered load
- 3. The load's center-of-gravity relative to the slide's centerline-of-travel
- 4. The number of cycles
- 5. The speed or frequency of cycles
- 6. The length of the cycle stroke
- 7. The percent of travel
- 8. The stopping force and distance **Abnormal Loads/Vibration.**

Shipping, abusive loads, and impact loads—even in short duration—put large stresses on the slide and can cause immediate or premature failure. Excessive or continuous vibrations can also reduce slide performance and life.

Corrosion. Excessive humidity, salts, or other chemical agents can corrode the finish and attack metal or plastic components. The effects may be immediate, or they may develop over time.

Lubrication. Knape & Vogt lubricates slides at the factory. However, contaminants such as dirt, filings, sawdust, paints, etc. can rapidly break down the effectiveness of the factory-applied lubricant.

Temperature. Extreme high or low temperatures can cause lubricants to thin or gel. Extreme temperatures caused by equipment such as finishing ovens can deteriorate a slide's plastic and rubber components.

Finishing. Over-spray from stains, paints, varnishes, or other finishing agents may degrade the quality of a slide's "fit and feel." These types of chemical agents can also attack plastic, rubber, and metal slide components. It's important to properly mask or otherwise protect installed slides before finishing furniture and cabinetry.

Proper slide specification and installation are keys to long and problem-free operation. To help you select the drawer slides best-suited to your specific applications, Knape & Vogt offers a free consultation service. KV also offers a "no charge" testing service.

KV strongly recommends that manufacturers test representative samples of the complete application. Appropriate industry standards should be followed to assure proper performance, durability, and safety. NOTE: Knape & Vogt's testing service does not include product cost nor freight cost to or from the KV test laboratory. Product is properly disposed of shortly after testing, unless otherwise requested.

Drawer Slides Quick Reference Guide

			Slid	е Туре			Extension			Die	connect 1	Γ _ν ης			0	nen/Clo	se Feati	Irae				
	Mounting Style	Load Class	Roller Bearing	Ball-Bearing	Undermount	3/4 Extension	Full Extension	1" Over Travel	No Disconnect	Friction Release	Lever Release	Lift Out	Quick Disconnect (QD RAIL)	Hold In Anti-Re- bound	Hold-Out / Open	Lock-In	Lock Open	Self-Close	Push-to- Open	Soft-Close	Shelf Tabs	V-Notch (Special Order)
Light-Duty Sli		×	© #	<u></u>	74	4 =	5 =	교 역	ㅁㅁ	ő S	89 44	<u> </u>	[다 라 뜻	E 약 표	5 ~	5	3	ő	5	ő	%	3 E F
1175	Under	50	•			•						•										
1300	Side	75				•					•				•							
1805	Side	75	•			•						•		•	•		•	•				
8350	Side	75		•		•					•			•								
8355	Side	75		•		•					•			•	•							
8357	Side	75		•		•					•			•	•						•	
4400	Side	65		•			•				•			•								
4450	Side	65		•			•				•									•		
Medium-Duty	Slides																					
8400	Side	100		•			•				•			•								
8405	Side	90		•				•			•			•								
8407	Side	100		•			•				•			•							•	
8414	Side	100		•			•				•			•	•							
8417	Side	100		•			•				•			•				•				
8419	Side	90		•				•			•			•				•				
8420	Side	100		•			•				•			•								
8425	Side	90		•				•			•			•								
8400RV	Side	100		•			•				•			•								
8450FM	Side	100		•			•				•			•						•		
8455FM	Side	90		•				•			•			•						•		
MuV+	Under	75			•		•				•			•						•		
MuV+34	Under	75			•		•				•			•						•		
MuV ⁺ HD	Under	120			•		•				•			•						•		
MuV+34HD	Under	120			•		•				•			•						•		
GS2070	Under	75			•		•				•			•						•		
GS4200	Side	100		•			•				•			•								
GS4205	Side	90		•				•			•			•								
GS4260	Side	100		•			•				•								•			
GS4270	Side	100		•			•				•									•		
TT100	Side	100		•			•				•			•					İ			
DUR4500	Side	100		•			•				•			•								

Drawer Slides Quick Reference Guide (continued)

													,									
			Slid	е Турє			Extension			Disc	connect 1	Гуре			0	pen/Clc	se Feat	ures				
	Mounting Style	Load Class	Roller Bearing	Ball-Bearing	Undermount	3/4 Extension	Full Extension	1" Over Travel	No Disconnect	Friction Release	Lever Release	Lift Out	Quick Disconnect (QD RAIL)	Hold In Anti-Re- bound	Hold-Out / Open	Lock-In	Lock Open	Self-Close	Push-to- Open	Soft-Close	Shelf Tabs	V-Notch (Special Order)
Heavy-Duty																						
6500	Side	125		•			•				•			•								
6505	Side	125		•				•			•			•								
8500	Side	150		•			•						•	•								
8505	Side	150		•				•					•	•								
8520	Side	175		•			•						•	•								
8525	Side	175		•				•					•	•								
8600	Side	150		•			•				•			•								
8605	Side	140		•				•			•			•								
8620	Side	150		•			•				•			•								
8625	Side	140		•				•			•			•								
8650FM	Side	150		•			•				•			•						•		
8655FM	Side	140		•				•			•			•						•		
8810	Side	200		•			•				•			•								
8815	Side	190		•				•			•			•								
8820	Side	200		•			•				•			•								
8825	Side	190		•				•			•			•								
8900	Side	150-500		•			•		•					•								
8908	Side	150-500		•			•		•							•	•					
Specialty Sli	des																					
6300	Side	100		•			•				•			•								
6400	Side	100		•			•				•			•								
8000	Under	130		•				•				•		•								
8500T	Side	150		•			•						•	•								
8505T	Side	150		•				•					•	•								
8520T	Side	175		•			•						•	•								
8525T	Side	175		•				•					•	•								
4461D	Under	75		•																		
8150	Under	75		•		•					•			•	•							
8157	Under	75		•		•					•			•	•							
8250	Under	75		•		•					•			•								

Ball-Bearing Slides: Suggested Product Application Matrix

						J									J														.70	1																
									Re	com	men	ded	Appl	icat	ions																		Avai	ilable	Sto	ck S	izes									
Part Number	Kitchen Cabinets	Bathroom Vanities	Desk & Credenza Box Drawers	Cabinetry	Mill Work	Lateral Files	Keyboard & Tray Units	Store Fixtures	Institutional Furniture	Fine Cabinetry	Wet/Corrosive Environments	Kitchen Pantries	Up & Over Hinge Doors	Entertainment Centers	Storage Cabinetry	Heavy-Duty Storage	Desk Trays	Pull-out Work Surfaces	Work Stations, Tool Storage	RV Vehicles, Mobile Carts	Automotive	Undermount Applications	Metal Cabinets and Drawers	6"	8"	10"	12"	13"	14"	15"	16"	18.	20"	24	26:	28"	30"	22: 22:	32	34"	36"	40"	42"	48"	60"	Special Order Only
4400	•	•	•	•																						•	•		•		•	•	•	• •	•	•		I		\Box						
4450	•	•	•	•																						•	•		•		•	•	•	•	•			I								
6300											•															•	•		•		•	•	•	• •	•	•		Ţ								
6400											•															•	•		•		•	•	•	•	•	•										
6500			•					•	•																		•		•		•	•	•	•	•	•										
6505			•					•	•																		•		•		•	•	•	• •	•	•										
8000												•															•		•		•	•	•	•	•	•										
8040EZ													•														•		•		•	•	•	• •				\perp								
8050EZ													•														•		•		•	•	•	•	•											
8070EZ														•	•												•		•		•	•	•	•	•			I								
8071EZ														•													•		•		•	•	•	•	•											
8072EZ														•													•		•		•	•	•	•	•											
8080EZ														•	•												•		•		•	•	•	• •	•											
8081EZ														•	•												•		•		•	•	•	• •	•											
8082EZ														•	•												•		•		•	•	•	• •	•			\perp								ш
8091									•					•		•											•	•	•	•	•	•	•	• •	•	•	•	\perp								
8092									•					•		•											•	•	•	•	•	•	•	•	•	•	•									
8150							•																				•		•		•	•	•	•												
8157							•																						•		•	•	•					Ţ								
8250																	•									•	•		•		•	•	•	•												
8350			•	•	•																						•		•		•	•	•	• •	•	•	•	L								
8355			•	•	•																						•		•		•	•	•													
8357			•	•	•																								•		•	•	•													
8400			•	•	•																			•	•	•	•		•		•	•	•	• •	•	•		\perp	\perp							
8405			•	•	•																					•	•		•		•	•	•	• •	•	•										
8407			•	•	•																					•	•		•		•	•	•	• •	•	•		L								
8414																		•								•	•		•		•	•	•	• •				Ţ								
8417	•			•					•																		•		•		•	•	•	• •	•											
8419	•			•					•																				•		•	•	•	• •	•											
8420																							•								•	•	•	•												
8425																							•								•	•	•	•												

Ball-Bearing Slides: Suggested Product Application Matrix (continued)

									Re			nded																						ailat	ole S	Stoc	k Si										
Part Number	Kitchen Cabinets	Bathroom Vanities	Desk & Credenza Box Drawers	Cabinetry	Mill Work	Lateral Files	Keyboard & Tray Units	Store Fixtures	Institutional Furniture	Fine Cabinetry	Wet/Corrosive Environments	Kitchen Pantries	Up & Over Hinge Doors	Entertainment Centers	Storage Cabinetry	Heavy-Duty Storage	Desk Trays	Pull-out Work Surfaces	Work Stations, Tool Storage	RV Vehicles, Mobile Carts	Automotive	Undermount Applications	Metal Cabinets and Drawers	6"	8"	10"	12"	13"	14"	15"	16"	18"	20"	22"	24"	26"	28"	30"	32"	34"	36"	40	42	45	40	09	Special Order Only
8400RV																				•						•	•		•		_	•	•	•	•	•	•									П	
8450FM			•	•	•					\top	\top	\top		T				Т	\top		\top						•		•		•	•	•	•	•	•	•		\top	\top	T	\top	\top	\top	\top	\exists	
8455FM			•	•	•						т																				•	•	•	•	•	•	•		Т	Т	\top	\top	\top	Т	\top	\neg	_
8500			•	•	•						\top																•		•		•	•	•	•	•	•	•	•		\top	T		\top	T	\top	\exists	
8500TQ						•					\top	\top		T							\top										•	•	•						\top	Т	\top	\top	\top	\top	\top	\exists	_
8505			•	•	•				\top		т																•		•		•	•	•	•	•	•	•	•	Т	Т	Т	\top		Т	\top	\exists	_
8520			•			•					\top	\top									\top										•	•	•						\top	\top	T	\top	\top	\top	\top	\exists	
8525			•			•					\top										Т										•	•	•							Т	\top	\top	\top	\top	\top	\exists	
8600			•	•	•			•	•						•	•			•								•		•		•	•	•	•	•	•	•								\top	\exists	_
8605								•	•		\top	\top		T	•	•		Т	•		\top						•		•		•	•	•	•	•	•	•		\top	\top	\top	\top	\top	\top	\top	\exists	_
8620											\top												•								\exists	•		•					Т	Т		\top			\top	\exists	_
8625																							•																							\exists	•
8650FM				•				•	•		\top	\top			•	•			•		Т								•		•	•	•	•	•	•	•			Т	\top	\top	\top	\top	\top	\exists	
8655FM				•				•	•						•	•			•													•	•	•	•	•	•			Т					\top	\exists	_
8810																			•		•					•	•		•		•	•	•	•	•	•	•								\top	\exists	
8815																			•		•						•		•		•	•	•	•	•	•	•									\exists	
8820																							•								•			•		•								T		\exists	
8825										Т	Т								Т				•																	Т		Т	Т	Т		П	•
8900																•			•		•					•	•		•		•	•	•	•	•	•	•	•	•	•	•	•	•	•	,	•	
8908																•			•	•	•						•		•		•	•	•	•	•	•	•	•	•	•	•	•				•	
GS4200			•	•	•						İ								Ì			İ				•	•		•		•	•	•	•	•	•	•			Ī		Ť				\neg	
GS4205			•	•	•																					•	•		•		•	•	•	•	•	•	•	Г				Ť			T	\exists	
GS4260	١.			•					•		Т	\top														•	•		•		•	•	•	•	•	•	•			Т		T	\top		T	\top	
GS4270			•	•	•						\top	\top																	•		•	•	•	•	•	•	•			\top		†			†	\forall	
TT100	\top		•	•	•						+	+														•	•		•		•	•	•	•	•	•	•				\perp	$^{+}$	+	†	†	+	_
DUR4500	+		•								+																		•		-	•	•	•	•	•	•						+	+	+	+	_

Roller Bearing Slides: Suggested Product Application Matrix

			Reco	mmer	ided A														e Stoc	k Size								
Part Number	Kitchen Cabinets	Bathroom Vanities	Architectural Woodwork	Residential Furniture	Institutional Furniture	Office Furniture	Store Fixtures	Work Benches	Fine Cabinetry	Special Order Only	12"	14"	16"	18"	20"	22"	22-5/8"	24"	26"	28"	300mm	350mm	400mm	450mm	500mm	550mm	600mm	650mm
1175	•	•												•	•	•	•	•										
1300	•	•	•				•				•	•	•	•	•	•		•	•	•								
1805	•	•	•	•																	•	•	•	•	•	•	•	

Undermount Drawer Slide Size Guide

								k Size:					
Part Number	9"	10"	12"	14"	15"	16"	18"	20"	21"	22"	24"	27"	30"
MuV+	•	•	•	•	•	•	•	•	•	•			
MuV+34	•	•	•	•	•	•	•	•	•	•			
MuV+HD							•	•	•	•	•	•	•
MuV ⁺ 34HD							•	•	•	•	•	•	•
GS2070	•		•		•		•		•				



Light-Duty Drawer Slides

1175 3/4 Extension Center Under Drawer Slide
1300 3/4 Extension Drawer Slides
1805 Epoxy-Coated Drawer Slide
8350 3/4 Extension Drawer Slides
4400 Low Profile Full Extension Drawer Slide
4450 Low Profile Full Extension Soft-Close Drawer Slide

			Ту	ре	Ex	tens	ion	D	isco	nnec	t Typ	ре	0	pen/	'Clos	e Fe	ature	es		
	Mounting Style	Load Class	Roller Bearing	Ball-Bearing	3/4 Extension	Full Extension	1" Over Travel	No Disconnect	Friction Release	Lever Release	Lift Out	Quick Disconnect	Hold In Anti-Rebound	Hold-Out / Open	Lock Open	Self-Close	Push-to-Open	Soft-Close	Shelf Tabs	V-Notch Special Order
1175	Under	50	•		•						•									
1300	Side	75	•		•					•				•						
1805	Side	75	•		•						•		•	•		•				
8350	Side	75		•	•					•			•							
4400	Side	65		•		•				•			•							
4450	Side	65		•		•				•			•					•		

1175 3/4 Extension Center Under Drawer Slide





Features

- Mounts with staples or screws
- Drawers lift out for easy removal
- Recommended maximum drawer width 18"

Mounting:Under-drawerAction:RollersLoad Rating:50 lb. classHeight:1" [25.4mm]Finish:Zinc (ZC)

Configurations

Poly (P)	1 slide per bag with screws; 10 slides per carton
1175 Zinc (ZC) Finish	
Size	Poly (P)
22-5/8"	1175P ZC 22-5/8

Recommended Fasteners	KV Part	Finish	Qty
#6 x 1/2" Phillips Pan Head Screws	200106-5	Zinc (ZC)	1000

Mounting Brackets



Product	Pack
1123 PLAS	500 per carton

1300 3/4 Extension Drawer Slides



Features

- · Positive stop lever
- Stay close design
- Recommended maximum drawer width 18"
- 3/4 extension slide


Mounting: Side

Action: Ball-bearing rollers Load Rating: 75 lb. class Height: 3" [76.2mm]

Clearance: .50" + .03" - 0" on each side

Finish: Zinc (ZC)

Profile:



Mounting Brackets







1123 PLAS Plastic Rear Mounting Bracket

Product	Pack
1303	100 per carton
1123 PLAS	500 per carton

Configurations

Bulk (B)	10 pairs per carton with	10 pairs per carton without screws	
Poly (P)	1 pair per bag with scre	1 pair per bag with screws; 10 pairs per carton	
1300 Zinc (ZC) Finish			
12"	_	1300P ZC 12	
14"	1300B ZC 14	1300P ZC 14	
16"	1300B ZC 16	1300P ZC 16	
18"	1300B ZC 18	1300P ZC 18	
20"	1300B ZC 20	1300P ZC 20	
22"	1300B ZC 22	1300P ZC 22	
24"	1300B ZC 24	1300P ZC 24	
26"	1300B ZC 26	1300P ZC 26	
28"	_	1300P ZC 28	

Recommended Fasteners	KV Part	Finish	Qty
#7 x 1/2" Phillips Pan Head Screws	8500-93	Zinc (ZC)	1000
	8500-93 EB	Ebony Black (EB)	1000

Non-stock item – minimum order quantities and additional lead time may apply.

1805 Epoxy-Coated Drawer Slide




Features

- 32mm mounting hole pattern
- Lift out disconnect
- Self-close design
- Recommended maximum drawer width 18"

Mounting:SideAction:RollersLoad Rating:75 lb. classHeight:1.39" [35.5mm]

Clearance: .50" + .03" - 0" on each side

Finish: White (WH)



Configurations


Hefty (H)	1 pair per bag with so	crews; 20 pairs per carto	on	
Quantity (Q)	100 pairs per carton	100 pairs per carton without screws; multiple cartons		
Taped Pair (T)	1 pair taped together	1 pair taped together without screws; 20 pairs per carton		
1805 White (WH) F	1805 White (WH) Finish			
300mm	1805H WH 300	1805Q WH 300	1805T WH 300	
350mm	1805H WH 350	1805Q WH 350	1805T WH 350	
400mm	1805H WH 400	1805Q WH 400	1805T WH 400	
450mm	1805H WH 450	1805Q WH 450	1805T WH 450	
500mm	1805H WH 500	1805Q WH 500	1805T WH 500	
550mm	1805H WH 550	1805Q WH 550	1805T WH 550	
600mm	1805H WH 600	1805Q WH 600	1805T WH 600	

Recommended Fasteners	KV Part	Finish	Qty
#6 x 7/16" Phillips Flathead Screws	1284-80	Zinc (ZC)	1000

Mounting Brackets







1805-401 Left and right handed sockets (4" socket)

Product	Pack	Handed
1805-101L BP	50 per carton	Left
1805-101R BP	50 per carton	Right
1805-401L BP	50 per carton	Left
1805-401R BP	50 per carton	Right

8350 3/4 Extension Drawer Slides



Features

- 32mm mounting hole pattern
- Lever disconnect permits easy drawer removal
- Non-handed design
- Recommended maximum drawer width 24"
- 3/4 extension drawer slide

Mounting: Side


Action: Ball-bearing movement

Load Rating: 75 lb. class Height: 1.37" [35mm]

Clearance: .50" + .03" - 0" on each side

Finish: Anochrome (ANO)

Profile:



Configurations



Bulk (B)	10 pairs per carton without screws		
8350 Anochrome (ANO) Finish			
Size	Bulk (B)		
12"	8350B 12		
14"	8350B 14		
16"	8350B 16		
18"	8350B 18		
20"	8350B 20		
22"	8350B 22		
8355 Anochrome	(ANO) Finish		
Size	Bulk (B)		
12"	8355B 12		
14"	8355B 14		
16"	8355B 16		
18"	8355B 18		

Recommended Fasteners	KV Part	Finish	Qty
#7 x 1/2" Phillips Pan Head Screws	8500-93	Zinc (ZC)	1000

Non-stock item – minimum order quantities and additional lead time may apply.

4400 Low Profile Full Extension Drawer Slide



Features

- · Lever release
- Hold-in detent
- Recommended maximum drawer width 24"

Mounting: Side


Action: Telescopic movement on ball-bearings

Load Rating: 65 lb. class Height: 1.42" [36mm]

Clearance: .50" + .03" - 0" on each side

Finish: Zinc (ZC)





Configurations



Bulk (B)	10 pairs per carton without screws
4400 Zinc (ZC) Finish	
Size	Bulk (B)
10" (250mm)	4400B 10
12" (300mm)	4400B 12
14" (350mm)	4400B 14
16" (400mm)	4400B 16
18" (450mm)	4400B 18
20" (500mm)	4400B 20
22" (550mm)	4400B 22
24" (600mm)	4400B 24
26" (650mm)	4400B 26
28" (700mm)	4400B 28

Recommended Fasteners
#6 x 1/2" Truss Head Screws

Mounting Brackets



4101B Rear Mounting Bracket



Front Face Frame Bracket

Non-handed snap-on design

Product	Pack
4101B	20 per carton
4104B	20 per carton

4450 Low Profile Full Extension Soft-Close Drawer Slide




Features

- · Lever release
- Soft-close module
- Recommended maximum drawer width 24"

Mounting:SideAction:Soft-closeLoad Rating:65 lb. classHeight:1.42" [36mm]

Clearance: .50" + .03" - 0" on each side

Finish: Zinc (ZC)



Mounting Brackets







Front Face Frame Bracket

Non-handed snap-on design

Product	Pack			
4101B	20 per carton			
4104B	20 per carton			

Configurations



Bulk (B)	10 pairs per carton without screws
4450 Zinc (ZC) Finish	
Size	Bulk (B)
10" (250mm)	4450B 10
12" (300mm)	4450B 12
14" (350mm)	4450B 14
16" (400mm)	4450B 16
18" (450mm)	4450B 18
20" (500mm)	4450B 20
22" (550mm)	4450B 22
24" (600mm)	4450B 24

Recommended Fasteners	
#6 x 1/2" Truss Head Screws	

Less than Full Extension: 10" = 7.8" Extension




Medium-Duty Drawer Slides

8400 Series Overview
8400 Full Extension Box or File Drawer Slide
8405 Over Travel Box or File Drawer Slide
8407 Full Extension Box or File Drawer Slide with Shelf Tabs 20
8414 Full Extension Hold-Out Drawer Slide
8417, 8419, 8400RV Self-Closing Drawer Slides
8420, 8425 Metal Cabinet and Drawer Slide
8450FM, 8455FM Soft-Close Drawer Slides
KV GSlide GS4200, GS4205 Drawer Slide
KV GSlide GS4260 Push-Open Drawer Slide
KV GSlide GS4270 Soft-Close Drawer Slide
KV Tru-Trac TT100 Full Extension Ball-Bearing Drawer Slide 28
KV DuriSlide 4500 Ball-Bearing Drawer Slide

			Ту	ре	Ex	tens	ion	D	isco	nnec	t Typ	ое	0	pen/	'Clos	e Fe	ature	es	
	Mounting Style	Load Class	Roller Bearing	Ball-Bearing	3/4 Extension	Full Extension	1" Over Travel	No Disconnect	Friction Release	Lever Release	Lift Out	Quick Disconnect	Hold In Anti-Rebound	Hold-Out / Open	Lock Open	Self-Close	Push-to-Open	Soft-Close	Shelf Tabs
8400	Side	100		•		•				•			•						
8405	Side	100		•			•			•			•						
8407	Side	100		•		•				•			•						•
8414	Side	100		•		•				•			•	•					
8417	Side	100		•		•				•			•			•			
8419	Side	90		•			•			•			•			•			
8420	Side	100		•		•				•			•						
8425	Side	90		•			•			•			•						
8400RV	Side	100		•		•				•			•			•			
8450FM	Side	100		•		•				•			•			•		•	
8455FM	Side	90		•			•			•			•			•		•	
GS4200	Side	100		•		•				•			•						
GS4205	Side	90		•		•				•			•						
GS4260	Side	100		•		•				•							•		
GS4270	Side	100		•		•				•								•	
TT100	Side	100		•		•				•			•						
DUR4500	Side	100		•		•				•			•						

8400 Series Drawer Slides



- 1. Push-in button for drawer disconnect is ergonomically designed for easy drawer removal.
- 2. Traditional and 32mm hole pattern supports industry standards for safely fastening slide in place.
- 3. Reversed flex tabs allow improved slide performance with side clearance tolerance adjustments.
- 4. Rolled ball-bearing raceway allows lateral loads to be carried by ball-bearings and not transferred to bushings sliding on metal.
- 5. Mounting hole is provided for face frame applications to eliminate the need for a separate bracket.
- 6. Access holes allow for drawer adjustments at full extension without removing drawer.
- 7. Lacquer finish provides superior corrosion resistance.

Self-Close Series Drawer Slides



Self-close slides use spring technology to close a drawer.

Models and Descriptions:

8417: Self-closing full extension

8419: Self-closing over travel drawer slide

8400RV: Heavy-duty self-closing full extension drawer slide

Features and Benefits:

- Self-close feature assist with the closing of a drawer and is fully integrated into the slide
- RV version has stronger springs to ensure closure in mobile applications

8450FM Soft-Close Drawer Slide

The new KV8450FM Series is a step forward in side-mounted ball-bearing drawer slides. The KV8450FM series incorporates state-of-the-art soft-close technology. The fully integrated soft-close module brings drawer box to a smooth, quiet and secure closure.

Collector increases

closure performance

Optional rear mounting hole increases mounting options

8450FM Series Features and Benefits

- Patented KV design incorporates dampening cylinder with balanced spring technology
- Soft-close module is fully integrated into an KV8400 style slide with same side clearance allowing cabinet makers to migrate directly to KV8450FM series products with no set up changes
- Exceeds KCMA, BHMA and BIFMA standards of performance: over 50,000 cycles including the soft-close module

8400 Full Extension Box or File Drawer Slide



Features


- 32mm hole pattern with direct access mounting
- Lever disconnect for easy drawer removal
- Non-handed design
- Recommended maximum drawer width 24"

Mounting: Side

Action: Telescopic movement on ball-bearings

Load Rating: 100 lb. class **Height**: 1.79" [45.5mm]

Clearance: .50" + .03" - 0" on each side
Finish: Anochrome (ANO), Ebony Black (EB)



Mounting Brackets







Product	Front or Rear	Finish	Pack
8401	Rear	Zinc (ZC)	20 brackets/carton
8402	Rear	Zinc (ZC)	20 brackets/carton
8402BBL	Rear	Zinc (ZC)	400 brackets/carton
8402WP	Rear	Zinc (ZC)	20 brackets/warehouse pack
8404	Front	Zinc (ZC)	20 brackets/carton
8404B	Front	Zinc (ZC)	400 brackets/carton
8404 EB	Front	Ebony Black (EB)	20 brackets/carton
8404BBL	Front	Zinc (ZC)	400 brackets/carton
8404B KIT	Both	Zinc (ZC)	2 [8403] + 2 [8404] + screws

Configurations



Bulk (B)		10 pairs per carton	10 pairs per carton without screws			
Poly (P)		1 pair per bag with	1 pair per bag with screws; 10 pairs per carton			
Quantity	(Q)	50 pairs without so	50 pairs without screws; multiple cartons			
8400 An	ochrome (ANO) Finish					
Size	Bulk (B)	Poly (P)	Quantity (Q)			
8"	8400B 8	8400P 8	8400Q 8			
10"	8400B 10	8400P 10	8400Q 10			
12"	8400B 12	8400P 12	8400Q 12			
14"	8400B 14	8400P 14	8400Q 14			
16"	8400B 16	8400P 16	8400Q 16			
18"	8400B 18	8400P 18	8400Q 18			
20"	8400B 20	8400P 20	8400Q 20			
22"	8400B 22	8400P 22	8400Q 22			
24"	8400B 24	8400P 24	8400Q 24			
26"	8400B 26	8400P 26	8400Q 26			
28"	8400B 28	8400P 28	8400Q 28			
8400 Eb	ony Black (EB) Finish					
8"	8400B EB 8	8400P EB 8	8400Q EB 8			
10"	8400B EB 10	8400P EB 10	8400Q EB 10			
12"	8400B EB 12	8400P EB 12	8400Q EB 12			
14"	8400B EB 14	8400P EB 14	8400Q EB 14			
16"	8400B EB 16	8400P EB 16	8400Q EB 16			
18"	8400B EB 18	8400P EB 18	8400Q EB 18			
20"	8400B EB 20	8400P EB 20	8400Q EB 20			
22"	8400B EB 22	8400P EB 22	8400Q EB 22			
24"	8400B EB 24	8400P EB 24	8400Q EB 24			
26"	8400B EB 26	8400P EB 26	8400Q EB 26			
28"	8400B EB 28	8400P EB 28	8400Q EB 28			

Recommended Fasteners	KV Part	Finish	Qty
#7 x 1/2" Phillips Pan Head Screws	8500-93	Zinc (ZC)	1000
	8500-93 EB	Ebony Black (EB)	1000

Non-stock item – minimum order quantities and additional lead time may apply.

8405 Over Travel Box or File Drawer Slide



Features


- 1" over travel for full access to drawer contents
- Lever disconnect for easy drawer removal
- Non-handed design
- Recommended maximum drawer width 24"

Mounting: Side

Action: Telescopic action on ball-bearings

Load Rating: 100 lb. class **Height**: 1.79" [45.5mm]

Clearance: .50" + .03" - 0" on each side
Finish: Anochrome (ANO), Ebony Black (EB)



Mounting Brackets









Product	Front or Rear	Finish	Pack
8401	Rear	Zinc (ZC)	20 brackets/carton
8402	Rear	Zinc (ZC)	20 brackets/carton
8402BBL	Rear	Zinc (ZC)	400 brackets/carton
8402WP	Rear	Zinc (ZC)	20 brackets/warehouse pack
8404	Front	Zinc (ZC)	20 brackets/carton
8404B	Front	Zinc (ZC)	400 brackets/carton
8404 EB	Front	Ebony Black (EB)	20 brackets/carton
8404BBL	Front	Zinc (ZC)	400 brackets/carton
8404B KIT	Both	Zinc (ZC)	2 [8403] + 2 [8404] + screws

Configurations




Bulk (B)	10 pairs per carton v	without screws					
Poly (P)	1 pair per bag with screws; 10 pairs per carton						
Quantity (Q)	50 pairs without scre	ews; multiple cartons					
8405 Anochrome (A	ANO) Finish						
Size	Bulk (B)	Poly (P)	Quantity (Q)				
10"	8405B 10	8405P 10	8405Q 10				
12"	8405B 12	8405P 12	8405Q 12				
14"	8405B 14	8405P 14	8405Q 14				
16"	8405B 16	8405P 16	8405Q 16				
18"	8405B 18	8405P 18	8405Q 18				
20"	8405B 20	8405P 20	8405Q 20				
22"	8405B 22	8405P 22	8405Q 22				
24"	8405B 24	8405P 24	8405Q 24				
26"	8405B 26	8405P 26	8405Q 26				
28"	8405B 28	8405P 28	8405Q 28				
8405 Ebony Black	(EB) Finish						
10"	8405B EB 10	8405P EB 10	8405Q EB 10				
12"	8405B EB 12	8405P EB 12	8405Q EB 12				
14"	8405B EB 14	8405P EB 14	8405Q EB 14				
16"	8405B EB 16	8405P EB 16	8405Q EB 16				
18"	8405B EB 18	8405P EB 18	8405Q EB 18				
20"	8405B EB 20	8405P EB 20	8405Q EB 20				
22"	8405B EB 22	8405P EB 22	8405Q EB 22				
24"	8405B EB 24	8405P EB 24	8405Q EB 24				
26"	8405B EB 26	8405P EB 26	8405Q EB 26				

Recommended Fasteners	KV Part	Finish	Qty
	8500-93	Zinc (ZC)	1000
#7 x 1/2" Phillips Pan Head Screws	8500-93 EB	Ebony Black (EB)	1000

Non-stock item – minimum order quantities and additional lead time may apply.

8407 Full Extension Box or File Drawer Slide with Shelf Tabs





Features

- 32mm hole pattern with direct access mounting
- Lever disconnect for easy drawer removal
- · Integrated shelf tabs
- Recommended maximum drawer width 24"


Mounting: Side

Action: Telescopic movement on ball-bearings

Load Rating: 100 lb. class Height: 1.79" [45.5mm]

Clearance: .50" + .03" - 0" on each side

Finish: Anochrome (ANO)



Mounting Brackets











Finish Product Front or Rear Pack 8401 Rear Zinc (ZC) 20 brackets/carton 8402 Rear Zinc (ZC) 20 brackets/carton 8402BBL Rear Zinc (ZC) 400 brackets/carton 8402WP Rear Zinc (ZC) 20 brackets/warehouse pack 8404 Front Zinc (ZC) 20 brackets/carton 8404B Front Zinc (ZC) 400 brackets/carton 8404 EB Front Ebony Black (EB) 20 brackets/carton 8404BBL Front Zinc (ZC) 400 brackets/carton 8404B KIT Both Zinc (ZC) 2 [8403] + 2 [8404] + screws

Configurations

Bulk (B)	10 pairs per carto	10 pairs per carton without screws	
Poly (P)	1 pair per bag wit	1 pair per bag with screws; 10 pairs per carton	
8407 Anochro	me (ANO) Finish		
Size	Bulk (B)	Poly (P)	
10"	8407B 10	_	
12"	8407B 12	_	
14"	8407B 14	8407P 14	
16"	8407B 16	8407P 16	
18"	8407B 18	8407P 18	
20"	8407B 20	8407P 20	
22"	8407B 22	8407P 22	
24"	8407B 24	8407P 24	
26"	8407B 26	_	
28"	8407B 28	-	

Recommended Fasteners	KV Part	Finish	Qty
#7 x 1/2" Phillips Pan Head Screws	8500-93	Zinc (ZC)	1000

Non-stock item – minimum order quantities and additional lead time may apply.

8414 Full Extension Hold-Out Precision Drawer Slide



Features

- 32mm hole pattern with direct access mounting
- Lever disconnect for easy drawer removal
- Hold-out feature holds slide in place when drawer is open
- Recommended maximum drawer width 24"


Mounting: Side

Action: Telescopic movement on ball-bearings

Load Rating: 100 lb. class Height: 1.79" [45.5mm]

Clearance: .50" + .03" - 0" on each side

Finish: Anochrome (ANO)



Mounting Brackets









Product Front or Rear Finish Pack Zinc (ZC) 20 brackets/carton 8401 Rear 8402 Rear Zinc (ZC) 20 brackets/carton 8402BBL Rear Zinc (ZC) 400 brackets/carton 8402WP Rear Zinc (ZC) 20 brackets/warehouse pack 8404 Front Zinc (ZC) 20 brackets/carton 8404B Zinc (ZC) 400 brackets/carton Front 8404 EB Front Ebony Black (EB) 20 brackets/carton 8404BBL Front Zinc (ZC) 400 brackets/carton 8404B KIT Both 2 [8403] + 2 [8404] + screws Zinc (ZC)

Configurations



Bulk (B)	10 pairs per cartor	10 pairs per carton without screws	
Poly (P)	1 pair per bag with	1 pair per bag with screws; 10 pairs per carton	
8414 Anochro	me (ANO) Finish		
Size	Bulk (B)	Poly (P)	
10"	8414B 10	_	
12"	8414B 12	8414P 12	
14"	8414B 14	8414P 14	
16"	8414B 16	8414P 16	
18"	8414B 18	8414P 18	
20"	8414B 20	8414P 20	
22"	8414B 22	8414P 22	
24"	8414B 24	8414P 24	

Recommended Fasteners	KV Part	Finish	Qty
#7 x 1/2" Phillips Pan Head Screws	8500-93	Zinc (ZC)	1000

Non-stock item – minimum order quantities and additional lead time may apply.

8417, 8419, 8400RV Self-Closing Drawer Slides



Features

- 32mm hole pattern with direct access mounting
- · Self-closing feature
- 8400RV features a stronger spring for mobile applications
- Recommended maximum drawer width 24"

Extension: 8417: Self-closing full extension drawer slide

8419: Self-closing 1" over travel drawer slide

8400RV: Heavy-Duty self-closing full extension drawer slide

Mounting: Side

Action: Telescopic movement on ball-bearings


Load Rating: 100 lb. class (8417/8400RV); 90 lb. class (8419)

Height: 1.79" [45.5mm]

Clearance: .50" + .03" - 0" on each side

Finish: Anochrome (ANO)

Profile:



Configurations



Bulk (B)	10 pairs per carton wit	10 pairs per carton without screws	
Poly (P)	1 pair per bag with scr	ews; 10 pairs per carton	
8417 Anochrome (ANO) Finish		
Size	Bulk (B)	Poly (P)	
12"	8417B 12	8417P 12	
14"	8417B 14	8417P 14	
16"	8417B 16	8417P 16	
18"	8417B 18	8417P 18	
20"	8417B 20	8417P 20	
22"	8417B 22	8417P 22	
24"	8417B 24	8417P 24	
26"	8417B 26	8417P 26	
8419 Anochrome (ANO) Finish		
14"	8419B 14	8419P 14	
16"	8419B 16	8419P 16	
18"	8419B 18	8419P 18	
20"	8419B 20	8419P 20	
22"	8419B 22	8419P 22	
24"	8419B 24	8419P 24	
26"	8419B 26	8419P 26	
8400RV Anochrom	e (ANO) Finish		
10"	8400BRV 10	_	
12"	8400BRV 12	-	
14"	8400BRV 14	-	
16"	8400BRV 16	_	
18"	8400BRV 18	_	
20"	8400BRV 20	_	
22"	8400BRV 22	_	
24"	8400BRV 24	_	
26"	8400BRV 26		
28"	8400BRV 28	_	

Mounting Brackets







Product	Front or Rear	Finish	Pack
8403	Rear	Zinc (ZC)	20 brackets/carton
8403BBL	Rear	Zinc (ZC)	400 brackets/carton
8404	Front	Zinc (ZC)	20 brackets/carton
8404B	Front	Zinc (ZC)	400 brackets/carton
8404 EB	Front	Ebony Black (EB)	20 brackets/carton
8404BBL	Front	Zinc (ZC)	400 brackets/carton
8404B KIT	Both	Zinc (ZC)	2 [8403] + 2 [8404] + screws

Non-stock item – minimum order quantities and additional lead time may apply

8420, 8425 Metal Cabinet and Drawer Slide





Features

- Bayonet and Belt Loop Mount
- Lever disconnect for easy drawer removal
- Recommended maximum drawer width 24"

Extension: 8420: Full Extension

8425: 1" Over Travel

Mounting: Side (Bayonet and Belt Loop)
Action: Telescopic action on ball-bearings


Load Rating: 8420: 100 lb. class

8425: 90 lb. class

Height: 1.79" [45.5mm]

Clearance: .50" + .03" - 0" on each side
Finish: Anochrome (ANO), Ebony Black (EB)

Profile:



Configurations

Quantity (Q)	20 pairs without screws; multiple cartons
8420 Anochromo	e (ANO) Finish
Size	Quantity (Q)
14"	8420Q 14
16"	8420Q 16
18"	8420Q 18
20"	8420Q 20
22"	8420Q 22
24"	8420Q 24
26"	8420Q 26
28"	8420Q 28
8420 Ebony Blac	ck (EB) Finish
14"	8420Q EB 14
16"	8420Q EB 16
18"	8420Q EB 18
20"	8420Q EB 20
22"	8420Q EB 22
24"	8420Q EB 24
26"	8420Q EB 26
28"	8420Q EB 28
8425 Anochromo	e (ANO) Finish
Size	Quantity (Q)
14"	8425Q 14
16"	8425Q 16
18"	8425Q 18
20"	8425Q 20
22"	8425Q 22
24"	8425Q 24
26"	8425Q 26
28"	8425Q 28
8425 Ebony Blac	k (EB) Finish
14"	8425Q EB 14
16"	8425Q EB 16
18"	8425Q EB 18
20"	8425Q EB 20
22"	8425Q EB 22
24"	8425Q EB 24
26"	8425Q EB 26
28"	8425Q EB 28

Non-stock item - minimum order quantities and additional lead time may apply.

8450FM, 8455FM Soft-Close Drawer Slide





Features

- Patented Force Management[™] (FM) soft-close technology
- 32mm hole pattern with direct access mounting
- Lever disconnect for easy drawer removal
- · Non-handed design
- Recommended maximum drawer width 24"

Extension: 8450FM: Full extension

8455FM: 1" Over travel

Action: Telescopic movement on ball-bearings


Load Rating: 8450FM: 100 lb. class

8455FM: 90 lb. class

Height: 1.79" [45.5mm]

Clearance: .50" + .03" - 0" on each side
Finish: Anochrome (ANO), Ebony Black (EB)

Profile:



Mounting Brackets





Product	Front or Rear	Finish	Pack
8403	Rear	Zinc (ZC)	20 brackets/carton
8403BBL	Rear	Zinc (ZC)	400 brackets/carton
8404	Front	Zinc (ZC)	20 brackets/carton
8404B	Front	Zinc (ZC)	400 brackets/carton
8404 EB	Front	Ebony Black (EB)	20 brackets/carton
8404BBL	Front	Zinc (ZC)	400 brackets/carton
8404B KIT	Both	Zinc (ZC)	2 [8403] + 2 [8404] + screws

Configurations



Bulk (B)	10 pairs per carton with	out screws
Poly (P)	1 pair per bag with scre	ws; 10 pairs per carton
8450FM Anochron	ne (ANO) Finish	
Size	Bulk (B)	Poly (P)
12"	8450FMB 12	8450FMP 12
14"	8450FMB 14	8450FMP 14
16"	8450FMB 16	8450FMP 16
18"	8450FMB 18	8450FMP 18
20"	8450FMB 20	8450FMP 20
22"	8450FMB 22	8450FMP 22
24"	8450FMB 24	8450FMP 24
26"	8450FMB 26	8450FMP 26
28"	8450FMB 28	8450FMP 28
8450FM Ebony Bla	ck (EB) Finish	
12"	8450FMB EB 12	_
14"	8450FMB EB 14	-
16"	8450FMB EB 16	-
18"	8450FMB EB 18	_
20"	8450FMB EB 20	_
22"	8450FMB EB 22	_
24"	8450FMB EB 24	_
26"	8450FMB EB 26	_
28"	8450FMB EB 28	_
8455FM Anochron	ne (ANO) Finish	
16"	8455FMB 16	8455FMP 16
18"	8455FMB 18	8455FMP 18
20"	8455FMB 20	8455FMP 20
22"	8455FMB 22	8455FMP 22
24"	8455FMB 24	8455FMP 24
26"	8455FMB 26	8455FMP 26
28"	8455FMB 28	8455FMP 28
8455FM Ebony Bla	ck (EB) Finish	
16"	8455FMB EB 16	_
18"	8455FMB EB 18	-
20"	8455FMB EB 20	-
22"	8455FMB EB 22	_
24"	8455FMB EB 24	-
26"	8455FMB EB 26	-
28"	8455FMB EB 28	-

Recommended Fasteners	KV Part	Finish	Qty
WZ 4/01/21/11/12 20 11 10	8500-93	Zinc (ZC)	1000
#7 x 1/2" Phillips Pan Head Screws	8500-93 EB	Ebony Black (EB)	1000

Less than Full Extension: 12" = 10.2" Extension

Non-stock item – minimum order quantities and additional lead time may apply.

KV GSlide® GS4200, GS4205 Drawer Slide



Features

- 32mm hole pattern
- Lever disconnect for easy drawer removal
- Hold-in detent
- Non-handed design
- Recommended maximum drawer width 24"

Mounting: Side

Action: Telescopic movement on ball-bearings

Load Rating: GS4200: 100 lb. class


GS4205: 90 lb. class

Height: 1.79" [45.5mm]

Clearance: .50" + .03" - 0" on each side

Finish: Zinc (ZC)

Profile:



Mounting Brackets



Product	Front or Rear	Finish	Pack
GS4340 RB	Rear	Zinc (ZC)	200

Configurations

Bulk (B)	10 Pair and 1 set of instructions per box without screws
GS4200 Zinc (ZC) F	rinish
Size	Bulk (B)
250mm	GS4200 10
300mm	GS4200 12
350mm	GS4200 14
400mm	GS4200 16
450mm	GS4200 18
500mm	GS4200 20
550mm	GS4200 22
600mm	GS4200 24
650mm	GS4200 26
700mm	GS4200 28
GS4205 Zinc (ZC) F	^E inish
Size	Bulk (B)
250mm	GS4205 10
300mm	GS4205 12
350mm	GS4205 14
400mm	GS4205 16
450mm	GS4205 18
500mm	GS4205 20
550mm	GS4205 22
600mm	GS4205 24
650mm	GS4205 26
700mm	GS4205 28

Recommended Fasteners	KV Part	Finish	Qty
#7 x 1/2" Phillips Pan Head Screws	8500-93	Zinc (ZC)	1000

KV GSlide® GS4260 Push-Open Drawer Slide



Features

- Push-open feature holds a drawer or tray in the closed position until activated by a slight push
- 32mm hole pattern
- Lever disconnect for easy drawer removal
- · Non-handed design
- Recommended maximum drawer width 24"

Mounting: Side


Action: Telescopic movement on ball-bearings

Load Rating: 100 lb. class Height: 1.79" [45.5mm]

Clearance: .50" + .03" - 0" on each side

Finish: Zinc (ZC)

Profile:



Mounting Brackets



Product	Front or Rear	Finish	Pack
GS4340 RB	Rear	Zinc (ZC)	200

Configurations

Bulk (B)	10 Pair and 1 set of instructions per box without screws		
GS4260 Zinc (ZC) Finish			
Size	Bulk (B)		
250mm	GS4260 10		
300mm	GS4260 12		
350mm	GS4260 14		
400mm	GS4260 16		
450mm	GS4260 18		
500mm	GS4260 20		
550mm	GS4260 22		
600mm	GS4260 24		
650mm	GS4260 26		
700mm	GS4260 28		

Recommended Fasteners	KV Part	Finish	Qty
#7 x 1/2" Phillips Pan Head Screws	8500-93	Zinc (ZC)	1000

KV GSlide® GS4270 Soft-Close Drawer Slide





Features

- · Soft-close module
- 32mm hole pattern
- Lever disconnect for easy drawer removal
- Non-handed design
- Recommended maximum drawer width 24"

Mounting: Side


Action: Telescopic movement on ball-bearings

Load Rating: 100 lb. class Height: 1.79" [45.5mm]

Clearance: .50" + .03" - 0" on each side

Finish: Zinc (ZC)

Profile:



Mounting Brackets



Product	Front or Rear	Finish	Pack
GS4340 RB	Rear	Zinc (ZC)	200

Configurations

Bulk (B)	10 Pair and 1 set of instructions per box without screws	
GS4270 Zinc (ZC) Finish		
Size	Bulk (B)	
300mm	GS4270 12	
350mm	GS4270 14	
400mm	GS4270 16	
450mm	GS4270 18	
500mm	GS4270 20	
550mm	GS4270 22	
600mm	GS4270 24	
650mm	GS4270 26	
700mm	GS4270 28	

Recommended Fasteners	KV Part	Finish	Qty
#7 x 1/2" Phillips Pan Head Screws	8500-93	Zinc (ZC)	1000

Less than Full Extension: 12" = 8.4" Extension; 14" = 11.9" Extension

KV Tru-Trac® TT100 Full Extension Ball-Bearing Drawer Slide



Features

- For face framed and frameless construction
- 32mm and traditional hole pattern
- Lever disconnect for easy drawer removal
- · Non-handed design
- Recommended maximum drawer width 24"

Mounting: Side


Action: Telescopic movement on ball-bearings

Load Rating: 100 lb. class Height: 1.79" [45.5mm]

Clearance: .50" + .03" - 0" on each side

Finish: Zinc (ZC)

Profile:



Mounting Brackets



Product	Front or Rear	Finish	Pack
TT401	Rear	Zinc (ZC)	200 (10 Inner Boxes of 20 Brackets) Pallet Qty: 9,600 each
TT401B	Rear	Zinc (ZC)	200 (200 Loose Brackets) Pallet Qty: 9,600 each

Configurations

Bulk (B)	10 pairs per carton without screws		
TT100 Zinc (ZC) Finish			
Size	Bulk (B)		
250mm	TT100B 250		
300mm	TT100B 300		
350mm	TT100B 350		
400mm	TT100B 400		
450mm	TT100B 450		
500mm	TT100B 500		
550mm	TT100B 550		
600mm	TT100B 600		
650mm	TT100B 650		
700mm	TT100B 700		

Recommended Fasteners	KV Part	Finish	Qty
#7 x 1/2" Phillips Pan Head Screws	8500-93	Zinc (ZC)	1000

KV DuriSlide™ 4500 Ball-Bearing Drawer Slide



Features

- 32mm and traditional hole pattern
- Lever disconnect for easy drawer removal
- Non-handed design
- Recommended maximum drawer width 24"

Mounting: Side


Action: Telescopic movement on ball-bearings

Load Rating: 100 lb. class **Height**: 1.79" [45.5mm]

Clearance: .50" + .03" - 0" on each side

Finish: Zinc (ZC)

Profile:



Mounting Brackets



Product	Front or Rear	Finish	Pack
TT401	Rear	Zinc (ZC)	200 (10 Inner Boxes of 20 Brackets) Pallet Qty: 9,600 each
TT401B	Rear	Zinc (ZC)	200 (200 Loose Brackets) Pallet Qty: 9,600 each

Configurations

Bulk (B)	10 pairs per carton wit	10 pairs per carton without screws		
Quantity (Q)		20 cabinet members per carton, 100 drawer members per carton		
DUR4500 Zinc (ZC) Finish				
Size	Bulk (B)	Quantity (Q)*		
250mm	DUR45B 250	DUR45Q 250		
300mm	DUR45B 300	DUR45Q 300		
350mm	DUR45B 350	DUR45Q 350		
400mm	DUR45B 400	DUR45Q 400		
450mm	DUR45B 450	DUR45Q 450		
500mm	DUR45B 500	DUR45Q 500		
550mm	DUR45B 550	DUR45Q 550		
600mm	DUR45B 600	DUR45Q 600		
650mm	DUR45B 650	DUR45Q 650		
700mm	DUR45B 700	DUR45Q 700		

Recommended Fasteners	KV Part	Finish	Qty
#7 x 1/2" Phillips Pan Head Screws	8500-93	Zinc (ZC)	1000

^{*} Drop Ship Full Container - full pallet quantities vary by size.



Undermount Drawer Slides

KV GSlide GS2070 Full Extension Undermount Drawer Slide31MuV+ Full Extension Undermount Drawer Slide32MuV+34 Full Extension Undermount Drawer Slide33MuV+HD Heavy-Duty Full Extension Undermount Drawer Slide34MuV+34HD Heavy-Duty Full Extension Undermount Drawer Slide35

			Type	Extension		Disconnect Type		е	Open/Close Features						
	Mounting Style	Load Class	Undermount	3/4 Extension	Full Extension	1" Over Travel	No Disconnect	Friction Release	Lever Release	Lift Out	Quick Disconnect	Hold In Anti-Rebound	Hold-Out / Open	Self-Close	Soft-Close
S2070	Under	75	•		•				•			•		•	•
1uV+	Under	75	•		•				•			•		•	•
1uV+34	Under	75	•		•				•			•		•	•
1uV+HD	Under	120	•		•				•			•		•	•
1uV ⁺ 34HD	Under	120	•		•				•			•		•	•

KV GSlide® GS2070 Full Extension Undermount Drawer Slide






Features

- For use with drawer material thickness from 1/2" to 5/8"
- 32mm hole pattern matches existing industry standards
- Full extension travel

Mounting:UndermountAction:Telescopic actionLoad Rating:75 lb. classHeight:1.80" [45.7mm]Finish:Zinc (ZC)

Profile:



Configurations



Bulk (B)	6 pairs per carton without screws
2070 Zinc (ZC) F	Finish
Size	Bulk (B)
9"	KVGS-2070B 9
12"	KVGS-2070B 12
15"	KVGS-2070B 15
18"	KVGS-2070B 18
21"	KVGS-2070B 21

Recommended Fasteners	
#7 x 5/8" Flat Head Slide Mounting Screws	
#7 x 3/4" Flat Head Front Mounting Clip Screws	

Mounting Brackets







2070-RBM Metal Rear Mounting Bracket All Lengths

Product	Description	Carton Quantity
2070-RBP	Plastic rear mounting brackets	60
2070-RBM	Metal rear mounting brackets	60

Release Levers



2070-2D-RL

Release Lever Adjustment

Part Numbe	r Height	Side-to-Side	Carton Quantity
2070-2D-RL	+ 1/8" [3mm]	± 1/16" [1.5mm]	30

MuV+ Full Extension Undermount Drawer Slide




Features

- For use with drawer material thickness from 1/2" to 5/8"
- 32mm hole pattern matches existing industry standards
- Full extension travel 14"-22"; Partial 9"-12"
- Redesigned pivoting latch increases sound dampening for a quieter close
- Updated soft-close module allows pull-force adjustment to maintain smooth operation
- Five release levers allow adjustments in installed drawers
- · Bottom mounting holes for flat surface mounting

Mounting:UndermountAction:Telescopic actionLoad Rating:75 lb. classHeight:1.87" [47.6mm]Finish:Zinc (ZC)

Profile:



Release Levers Height adjustment Side-to-side adjustment MUV1D-RL MUV2D-RL MUV3D-RL MUV3D-RL MUV2DF-RL MUV2DF-RL

Release Lever Adjustment

Part Number	Height	Side-to-Side	In/Out
MUV1D-RL	+ 1/8" [3mm]	_	-
MUV2D-RL	+ 1/8" [3mm]	± 1/16" [1.5mm]	-
MUV3D-RL	+ 1/8" [3mm]	± 1/16" [1.5mm]	+ 3/32" [2.5mm]
MUV1DF-RL	+ 1/8" [3mm]	-	-
MUV2DF-RL	+ 1/8" [3mm]	± 1/16" [1.5mm]	-

Configurations



Dulle (D)	9"-12": 4 pairs per carton without screws					
Bulk (B)	14"-22": 6 pairs per carton without screws					
MuV ⁺ Zinc (ZC) Finish						
Size	Bulk (B)					
9"	MUVAB 9					
10"	MUVAB 10					
12"	MUVAB 12					
14"	MUVAB 14					
15"	MUVAB 15					
16"	MUVAB 16					
18"	MUVAB 18					
20"	MUVAB 20					
21"	MUVAB 21					
22"	MUVAB 22					

Recommended Fasteners	KV Part	Finish	Qty
#7 x 5/8" Slide Mounting Screws	MUV-122	Zinc (ZC)	100
#6 x 1/2" Front Mounting Clip Screws	MUV-123	Zinc (ZC)	100

Optimal Operation Guidelines for Drawer Width Based on Drawer Height						
Drawer Height	Maximum Width					
Up to 6"	Slide length + 10"					
Greater than 6"	Slide length + 10" or 28", whichever is less					
Greater than 8"	Slide length + 10" or 24", whichever is less					
Greater than 10"	Slide length + 10" or 21", whichever is less					

Mounting Brackets & Installation Jig



MUV-RBP Plastic Rear Mounting Bracket Sizes 9–12"



MUV-RBM Metal Rear Mounting Bracket Sizes 14"+



MUV-124 Installation Jig

Product	Description	Carton Quantity	
MUV-RBP	Plastic rear mounting brackets (sizes 9–12")	8 (4L, 4R)	
MUV-RBM	MUV-RBM Metal rear mounting brackets (sizes 14"+)		
MUV-124	Installation jig	1	

MuV+34 Full Extension Undermount Drawer Slide





Features

- For use with drawer material thickness from 5/8" to 3/4"
- 32mm hole pattern matches existing industry standards
- Full extension travel
- Redesigned pivoting latch increases sound dampening for a quieter close
- Updated soft-close module allows pull-force adjustment to maintain smooth operation
- Five release levers allow adjustments in installed drawers
- · Bottom mounting holes for flat surface mounting

Mounting:UndermountAction:Telescopic actionLoad Rating:75 lb. classHeight:1.87" [47.6mm]Finish:Zinc (ZC)







Release Lever Adjustment

Part Number	Height	Side-to-Side	In/Out					
MUV1D-RL	+ 1/8" [3mm]	_	_					
MUV2D-RL	+ 1/8" [3mm]	± 1/16" [1.5mm]	_					
MUV3D-RL	+ 1/8" [3mm]	± 1/16" [1.5mm]	+ 3/32" [2.5mm]					
MUV1DF-RL	+ 1/8" [3mm]	_	_					
MUV2DF-RL	+ 1/8" [3mm]	± 1/16" [1.5mm]	_					

Configurations



D. II. (D)	9"-12": 4 pairs per carton without screws		
Bulk (B)	14"-22": 6 pairs per carton without screws		
MuV ⁺ 34 Zinc (ZC) Finish			
Size	Bulk (B)		
9"	MUV34AB 9		
10"	MUV34AB 10		
12"	MUV34AB 12		
14"	MUV34AB 14		
15"	MUV34AB 15		
16"	MUV34AB 16		
18"	MUV34AB 18		
20"	MUV34AB 20		
21"	MUV34AB 21		
22"	MUV34AB 22		

Recommended Fasteners	KV Part	Finish	Qty
#7 x 5/8" Slide Mounting Screws	MUV-122	Zinc (ZC)	100
#6 x 1/2" Front Mounting Clip Screws	MUV-123	Zinc (ZC)	100

Optimal Operation Guidelines for Drawer Width Based on Drawer Height			
Drawer Height Maximum Width			
Up to 6"	Slide length + 10"		
Greater than 6"	Slide length + 10" or 28", whichever is less		
Greater than 8"	Slide length + 10" or 24", whichever is less		
Greater than 10"	Slide length + 10" or 21", whichever is less		

Mounting Brackets & Installation Jig



MUV-RBP Plastic Rear Mounting Bracket Sizes 9–12"



MUV-RBM Metal Rear Mounting Bracket Sizes 14"+



MUV-124 Installation Jig

Product	Description	Carton Quantity
MUV-RBP	Plastic rear mounting brackets (sizes 9-12")	8 (4L, 4R)
MUV-RBM	Metal rear mounting brackets (sizes 14"+)	12 (non-handed)
MUV-124	Installation jig	1

MuV+HD Heavy-Duty Full Extension Undermount Drawer Slide






Features

- For use with drawer material thickness from 1/2" to 5/8"
- Industry standard 32mm mounting hole pattern
- Recommended maximum drawer width 42"
- Redesigned pivoting latch increases sound dampening for a quieter close
- Updated soft-close module allows pull-force adjustment to maintain smooth operation
- Five release levers allow adjustments in installed drawers
- · Bottom mounting holes for flat surface mounting

Mounting: Undermount
Load Rating: 120 lb. class
Height: 1.87" [47.6mm]
Finish: Zinc (ZC)

Profile:




Configurations

Bulk (B)	4 pairs per carton without screws		
MuV+HD Zinc (ZC)	MuV+HD Zinc (ZC) Finish		
Size	Bulk (B)		
18"	MUVHDAB 18		
20"	MUVHDAB 20		
21"	MUVHDAB 21		
22"	MUVHDAB 22		
24"	MUVHDAB 24		
27"	MUVHDAB 27		
30"	MUVHDAB 30		

Recommended Fasteners	KV Part	Finish	Qty
#7 x 5/8" Flathead Wood Screws	MUV-122	Zinc (ZC)	100
#6 x 1/2" Truss Head Wood Screws	MUV-123	Zinc (ZC)	100

Note: MuV+HD and MuV+34HD Face-Frame applications must be blocked out.



Release Lever Adjustment

Part Number	Height	Side-to-Side	In/Out
MUV1D-RL	+ 1/8" [3mm]	_	_
MUV2D-RL	+ 1/8" [3mm]	± 1/16" [1.5mm]	_
MUV3D-RL	+ 1/8" [3mm]	± 1/16" [1.5mm]	+ 3/32" [2.5mm]
MUV1DF-RL	+ 1/8" [3mm]	_	_
MUV2DF-RL	+ 1/8" [3mm]	± 1/16" [1.5mm]	-

Installation Jig



MUV-124 Installation Jig

Product	Description	Carton Quantity
MUV-124	Installation jig	1

MuV+34HD Heavy-Duty Full Extension Undermount Drawer Slide






Features

- For use with drawer material thickness from 5/8" to 3/4"
- Industry standard 32mm mounting hole pattern
- Recommended maximum drawer width 42"
- Redesigned pivoting latch increases sound dampening for a quieter close
- Updated soft-close module allows pull-force adjustment to maintain smooth operation
- Five release levers allow adjustments in installed drawers
- · Bottom mounting holes for flat surface mounting

Mounting: Undermount Load Rating: 120 lb. class Height: 1.87" [47.6mm] Finish: Zinc (ZC)

Profile:



Release Levers Height adjustment Side-to-side adjustment Inset adjustment MUV1D-RL MUV2D-RL MUV3D-RL MUV2D-RL MUV2DF-RL

Release Lever Adjustment

Troitage Level Adjustment				
Part Number	Height	Side-to-Side	In/Out	
MUV1D-RL	+ 1/8" [3mm]	_	_	
MUV2D-RL	+ 1/8" [3mm]	± 1/16" [1.5mm]	_	
MUV3D-RL	+ 1/8" [3mm]	± 1/16" [1.5mm]	+ 3/32" [2.5mm]	
MUV1DF-RL	+ 1/8" [3mm]	_	-	
MUV2DF-RL	+ 1/8" [3mm]	± 1/16" [1.5mm]	_	

Configurations

Bulk (B)	4 pairs per carton without screws		
MuV+34HD Zin	MuV+34HD Zinc (ZC) Finish		
Size	Bulk (B)		
18"	MUV34HDAB 18		
20"	MUV34HDAB 20		
21"	MUV34HDAB 21		
22"	MUV34HDAB 22		
24"	MUV34HDAB 24		
27"	MUV34HDAB 27		
30"	MUV34HDAB 30		

Recommended Fasteners	KV Part	Finish	Qty
#7 x 5/8" Flathead Wood Screws	MUV-122	Zinc (ZC)	100
#6 x 1/2" Truss Head Wood Screws	MUV-123	Zinc (ZC)	100

Note: MuV+HD and MuV+34HD Face-Frame applications must be blocked out.

Installation Jig



MUV-124 Installation Jig

Product	Description	Carton Quantity
MUV-124	Installation jig	1



Heavy-Duty Drawer Slides

6500, 6505 Box or File Drawer Slide
8500, 8505 Heavy-Duty File or Lateral Drawer Slides
8520, 8525 Extra Heavy-Duty File or Lateral Drawer Slides
8600, 8605 Heavy-Duty Drawer Slide
8620, 8625 Metal Cabinet and Drawer Slide 41
8650FM, 8655FM Heavy-Duty Soft-Close Drawer Slide
8810, 8815 Heavy-Duty Drawer Slide
8820, 8825 Heavy-Duty Metal Cabinet and Drawer Slide $\ldots\ldots$ 44
8900 Extra Heavy-Duty Full Extension Drawer Slide
8908 Extra Heavy-Duty Full Extension Locking Drawer Slides 46 $$

			_	_													
	Туре		Type Extension		Disconnect Type			Open/Close Features									
	Mounting Style	Load Class	Roller Bearing	Ball-Bearing	3/4 Extension	Full Extension	1" Over Travel	No Disconnect	Friction Release	Lever Release	Lift Out	Quick Disconnect	Hold In Anti-Rebound	Hold-Out / Open	Lock Open	Lock Closed	Soft-Close
6500	Side	125		•		•				•			•				
6505	Side	125		•			•			•			•				
8500	Side	150		•		•						•	•				
8505	Side	150		•			•					•	•				
8520	Side	175		•		•						•	•				
8525	Side	175		•			•					•	•				
8600	Side	150		•		•				•							
8605	Side	140		•			•			•							
8620	Side	150		•		•				•			•				
8625	Side	140		•			•			•			•				
8650FM	Side	150		•		•				•							•
8655FM	Side	140		•			•			•							•
8810	Side	200		•		•				•			•				
8815	Side	190		•			•			•			•				
8820	Side	200		•		•				•			•				
8825	Side	190		•			•			•			•				
8900	Side	150-500		•		•		•									
8908	Side	150-500		•		•		•							•	•	

6500, 6505 Box or File Drawer Slide



Features

- Lever disconnect for easy drawer removal
- Closed position hold-in detent
- Non-handed design
- Recommended maximum drawer width 30"

Extension: 6500: Full Extension

6505: 1" Over Travel

Mounting: Side

Action: Telescopic movement on ball-bearings

Load Rating: 6500: 125 lb. class


6505: 120 lb. class 1.95" [49.4mm]

Clearance: .50" + .03" - 0" on each side

Finish: Zinc (ZC)

Profile:

Height:



Configurations



Bulk (B)	5 pairs per carton without screws
6500 Zinc (ZC	r) Finish
Size	Bulk (B)
12"	6500B 12
14"	6500B 14
16"	6500B 16
18"	6500B 18
20"	6500B 20
22"	6500B 22
24"	6500B 24
26"	6500B 26
28"	6500B 28

6505 Zinc (Z	C) Finish	
Size	Bulk (B)	
12"	6505B 12	
14"	6505B 14	
16"	6505B 16	
18"	6505B 18	
20"	6505B 20	
22"	6505B 22	
24"	6505B 24	
26"	6505B 26	
28"	6505B 28	

Recommended Fasteners	
#7 x 1/2" Wood Screws	

8500, 8505 Heavy-Duty File or Lateral Drawer Slides



Features

• 32mm hole pattern

• Non-handed quick disconnect drawer members

Hold-in feature to prevent bounce back

· Recommended maximum drawer width

8500: 36" 8505: 30"

Extension: 8500: Full extension

8505: 1.25" over travel

Mounting: Side

Action: Progressive movement on ball-bearings


Load Rating: 150 lb. class

Height: 3.79" [96.3mm] (includes quick disconnect rail)

Clearance: .50" + .03" - 0" on each side

Finish: Anochrome (ANO)

Profile:



Configurations



Bulk (B)	5 pairs per carton without screws			
Poly (P)	1 pair per bag with screws; 5 pairs per carton			
Quantity (Q)	10 pairs without screws; multiple cartons			
8500 Anochrome (AN	0) Finish			
Size	Bulk (B)	Poly (P)	Quantity (Q)	
12"	8500B 12	8500P 12	8500Q 12	
14"	8500B 14	8500P 14	8500Q 14	
16"	8500B 16	8500P 16	8500Q 16	
18"	8500B 18	8500P 18	8500Q 18	
20"	8500B 20	8500P 20	8500Q 20	
22"	8500B 22	8500P 22	8500Q 22	
24"	8500B 24	8500P 24	8500Q 24	
26"	8500B 26	8500P 26	8500Q 26	
28"	8500B 28	8500P 28	8500Q 28	
30"	8500B 30	8500P 30	8500Q 30	
8505 Anochrome (AN	0) Finish			
12"	8505B 12	8505P 12	8505Q 12	
14"	8505B 14	8505P 14	8505Q 14	
16"	8505B 16	8505P 16	8505Q 16	
18"	8505B 18	8505P 18	8505Q 18	
20"	8505B 20	8505P 20	8505Q 20	
22"	8505B 22	8505P 22	8505Q 22	
24"	8505B 24	8505P 24	8505Q 24	
26"	8505B 26	8505P 26	8505Q 26	
28"	8505B 28	8505P 28	8505Q 28	
30"	8505B 30	8505P 30	8505Q 30	

Recommended Fasteners	KV Part	Finish	Qty
#7 x 1/2" Phillips Pan Head Screws	8500-93	Zinc (ZC)	1000

Non-stock item – minimum order quantities and additional lead time may apply.

8520, 8525 Extra Heavy-Duty File or Lateral Drawer Slides



Features

- · 32mm hole pattern
- Non-handed quick disconnect drawer members
- Hold-in feature to prevent bounce back
- Recommended maximum drawer width

8520: 42" 8525: 36"

Extension: 8520: Full extension

8525: 1.25" over travel

Mounting: Side

Action: Progressive movement on ball-bearings


Load Rating: 175 lb. class

Height: 3.79" [96.3mm] (includes quick disconnect rail)

Clearance: .50" + .03" - 0" on each side

Finish: Anochrome (ANO)

Profile:



Configurations

Poly (P)	1 pair per bag with screws; 5 pairs per carton			
8520 Anochrome (ANO) Finish				
Size	Poly (P)			
16"	8520P 16			
18"	8520P 18			
20"	8520P 20			
8525 Anochrome (ANO) Finish				
16"	8525P 16			
18"	8525P 18			
20"	8525P 20			

Recommended Fasteners	KV Part	Finish	Qty
#7 x 1/2" Phillips Pan Head Screws	8500-93	Zinc (ZC)	1000

Non-stock item – minimum order quantities and additional lead time may apply.

8600, 8605 Heavy-Duty Drawer Slide



Features

- Butterfly lever disconnect
- Non-handed design
- Recommended maximum drawer width 36"

Extension: 8600: Full Extension

8605: 1" Over Travel

Mounting: Side

Action: Telescopic movement on ball-bearings

Load Rating (based on application): Load: 8600: 150 lb. class

> 8605: 140 lb. class Max. Drawer Width: 36"

Slides: 18"

Drawer Width: 36"

Cycles: 50,000 (center pull)

Load: 8600: 200 lb.

8605: 190 lb.

Max. Drawer Width: 18"

Slides: 18" Drawer Width: 18"


Cycles: 25,000 (center pull)

Height: 1.98" [50.4mm]

Clearance: .51" + .01" - 0" on each side

Finish: Zinc (ZC)

Profile:



Configurations

24"

26"

28"

8605B 24

8605B 26

8605B 28



Bulk (B)	5 pairs per carton without screws
8600 Zinc (ZC	c) Finish
Size	Bulk (B)
12"	8600B 12
14"	8600B 14
16"	8600B 16
18"	8600B 18
20"	8600B 20
22"	8600B 22
24"	8600B 24
26"	8600B 26
28"	8600B 28
8605 Zinc (ZC	c) Finish
Size	Bulk (B)
12"	8605B 12
14"	8605B 14
16"	8605B 16
18"	8605B 18
20"	8605B 20
22"	8605B 22

Recommended Fasteners #7 x 1/2" Truss Head Screws

8620, 8625 Metal Cabinet and Drawer Slide





Features

- Bayonet and Belt Loop Mount
- Lever disconnect for easy drawer removal
- Recommended maximum drawer width 36"

Extension: 8620: Full Extension

8625: 1" Over Travel

Mounting: Side (Bayonet and Belt Loop)
Action: Telescopic action on ball-bearings

Load Rating: 8620: 150 lb. class


8625: 140 lb. class

Height: 1.98" [50.4mm]

Clearance: .51" + .01" - 0" on each side

Finish: Zinc (ZC)

Profile:



Configurations

Quantity (Q)	10 pairs; multiple cartons
8620 Zinc (ZC) Fi	nish
Size	Quantity (Q)
14"	8620Q 14
16"	8620Q 16
18"	8620Q 18
20"	8620Q 20
22"	8620Q 22
24"	8620Q 24
26"	8620Q 26
28"	8620Q 28
8625 Zinc (ZC) Fi	nish
Size	Quantity (Q)
14"	8625Q 14
16"	8625Q 16
18"	8625Q 18
20"	8625Q 20
22"	8625Q 22
24"	8625Q 24
26"	8625Q 26
28"	8625Q 28

Non-stock item – minimum order quantities and additional lead time may apply.

8650FM, 8655FM Heavy-Duty Soft-Close Drawer Slide





Features

• Patented Force Management (FM) Soft-Close Technology

• Butterfly lever disconnect

• Non-handed design

· Recommended maximum drawer width 36"

Extension: 8650FM: Full Extension

8655FM: 1" Over Travel

Mounting: Side

Action: Telescopic movement on ball-bearings

Load Rating: 8650FM: 150 lb. class

8655FM: 140 lb. class Max. Drawer Width: 36"

Slides: 18" Drawer Width: 36"


Cycles: 50,000 (center pull)

Height: 1.98" [50.4mm]

Clearance: .51" + .01" - 0" on each side

Finish: Zinc (ZC)

Profile:



Configurations

Bulk (B)	5 pairs per carton without screws
8650 Zinc (Z0) Finish
Size	Bulk (B)
14"	8650FMB 14
16"	8650FMB 16
18"	8650FMB 18
20"	8650FMB 20
22"	8650FMB 22
24"	8650FMB 24
26"	8650FMB 26
28"	8650FMB 28
8655 Zinc (Z0) Finish
Size	Bulk (B)
18"	8655FMB 18
20"	8655FMB 20
22"	8655FMB 22
24"	8655FMB 24
26"	8655FMB 26

Recommended Fasteners	
#7 x 1/2" Truss Head Screws	

14" and 16" less than full extension 14" extension = 11"; 16" extension = 15"

8655FMB 28

28"

8810, 8815 Heavy-Duty Drawer Slide



Features

• Non-handed design for easy installation

• Closed-position hold-in detent

· Butterfly lever release

• Recommended maximum drawer width 42"

Extension: 8810: Full Extension

8815: 1" Over Travel

Mounting: Side

Action: Telescopic movement on ball-bearings

Load Rating: 8810: 200 lb. class

8815: 190 lb. class


• 100 lb. flat mount rating

Height: 2.09" [53mm]

Clearance: .765" + .02" - .01" on each side

Finish: Zinc (ZC)

Profile:



Configurations

Bulk (B)	4 pairs per carton without screws					
8810 Zinc (ZC)	Finish					
Size	Bulk (B)					
10"	8810B 10					
12"	8810B 12					
14"	8810B 14					
16"	8810B 16					
18"	8810B 18					
20"	8810B 20					
22"	8810B 22					
24"	8810B 24					
26"	8810B 26					
28"	8810B 28					
8815 Zinc (ZC)	Finish					
Size	Bulk (B)					
12"	8815B 12					
14"	8815B 14					
16"	8815B 16					
18"	8815B 18					
20"	8815B 20					
22"	8815B 22					
24"	8815B 24					
26"	8815B 26					
28"	8815B 28					

Recommended Fasteners	
#8 or #10 x 5/8" Phillips Flathead Screws	

8820, 8825 Heavy-Duty Metal Cabinet and Drawer Slide





Features

- · Bayonet and Belt Loop Mount
- Lever disconnect for easy drawer removal
- Recommended maximum drawer width 42"

Extension: 8820: Full Extension

8825: 1" Over Travel

Mounting: Side (Bayonet and Belt Loop)

Action: Telescopic action on ball-bearings

Load Rating: 8820: 200 lb. class


8825: 190 lb. clas

Height: 2.09" [53mm]

Clearance: .765" + .02" - .01" on each side

Finish: Zinc (ZC)

Profile:



Configurations

28"

Quantity (Q)	5 pairs; multiple cartons
8820 Zinc (ZC) F	inish
Size	Quantity (Q)
14"	8820Q 14
16"	8820Q 16
18"	8820Q 18
20"	8820Q 20
22"	8820Q 22
24"	8820Q 24
26"	8820Q 26
28"	8820Q 28
8825 Zinc (ZC) F	inish
Size	Quantity (Q)
14"	8825Q 14
16"	8825Q 16
18"	8825Q 18
20"	8825Q 20
22"	8825Q 22
24"	8825Q 24
26"	8825Q 26

Non-stock item – minimum order quantities and additional lead time may apply.

8825Q 28

8900 Extra Heavy-Duty Full Extension Drawer Slide



Features

- Heavy-Duty stops are designed to withstand rough use
- Non-handed design for easy installation
- · Full extension travel
- Non-disconnect

Mounting: Side


Action: Telescopic movement on ball-bearings Load Rating: 100–500 lb. class depending on application

• 100 lb. flat mount rating

Height: 3" [76.2mm]

Clearance: .75" + .03" - 0" on each side

Finish: Zinc (ZC)



Configurations



Bulk (B)		10" – 20": 4 pairs per carton; 22" – 28": 3 pairs per carton 30" – 36": 2 pairs per carton; 40" – 60": 1 pair per carton							
Poly (P)		10" – 20": 4 pairs per carton; 22" – 28": 3 pairs per carton 30" – 36": 2 pairs per carton							
8900 Zinc (ZC) Fin	ish								
Size	Bulk (B)	Poly (P)							
10"	8900B 10	8900P 10							
12"	8900B 12	8900P 12							
14"	8900B 14	8900P 14							
16"	8900B 16	8900P 16							
18"	8900B 18	8900P 18							
20"	8900B 20	8900P 20							
22"	8900B 22	8900P 22							
24"	8900B 24	8900P 24							
26"	8900B 26	8900P 26							
28"	8900B 28	8900P 28							
30"	8900B 30	8900P 30							
32"	8900B 32	8900P 32							
34"	8900B 34	8900P 34							
36"	8900B 36	8900P 36							
40"	8900B 40	_							
42"	8900B 42	_							
44"	8900B 44	_							
48"	8900B 48	_							
60"	8900B 60	_							

Recommended Fasteners
1/4" [M6 Euro] flat, hex or pan head screw for 0.26" [6.6mm] cabinet member hole
1/4" [M6 Euro] hex or pan head screw for 0.26" [6.6mm] drawer member hole
#10 [M5 Euro] flat, hex or pan head screw for 0.20" [5.2mm] cabinet member hole
#10 [M5 Euro] hex or pan head screw for 0.20" [5.2mm] drawer member hole

Load Rating Chart								
Load Rating	Test Condition	Open/Close Cycle Tested						
500 lb.	18" slide in 18" width drawer	10,000						
400 lb.	18" slide in 42" width drawer	30,000						
300 lb.	18" slide in 36" width drawer	75,000						
100 lb. flat load	18" slide in 32" width drawer	10,000						

Note: This slide must never be used as a pull-out step, platform, or any other application supporting human weight as injury may result.

8908 Extra Heavy-Duty Full Extension Locking Drawer Slides



Features

- · Automatic lock-in/lock-out feature
- Intuitive uni-directional release/closure
- · Removable, ergonomic handle
- Spring-activated latches for vertical and horizontal mounting
- Non-disconnect

Extension: Extra Heavy-Duty full extension lock-in/lock-out slide

Mounting: Side or flat mount


Action: Telescopic movement on ball-bearings Load Rating: 100–500 lb. class depending on application

• 100 lb. flat mount rating

Height: 3" [76.2mm]

Clearance: .75" + .03" - 0" on each side

Finish: Zinc (ZC)



Configurations

	10" – 20": 8 slides per carton without screws 22" – 28": 6 slides per carton without screws
Bulk (B)	30" – 36": 4 slides per carton without screws
	40", 42", 44", 48", 60": 2 slides per carton without screws
	Each slide is poly-bagged with instructions included
	Sold per slide, not pair

8908 Zinc (ZC) Finish						
Size	8908 Lock-in/Lock-out					
10"	-					
12"	8908B 12					
14"	8908B 14					
16"	8908B 16					
18"	8908B 18					
20"	8908B 20					
22"	8908B 22					
24"	8908B 24					
26"	8908B 26					
28"	8908B 28					
30"	8908B 30					
32"	8908B 32					
34"	8908B 34					
36"	8908B 36					
40"	8908B 40					
42"	8908B 42					
44"	8908B 44					
48"	8908B 48					
60"	8908B 60					

Note: This slide must never be used as a pull-out step, platform, or any other application supporting human weight as injury may result.

Note: The 8908 slide is designed for applications in the 100 $-\,500$ lb. class based on

application: modest use 500 lbs.; normal use 400 lbs.; vehicular use 300 lbs.; flat mount 100 lbs..



Specialty Drawer Slides

6300 Corrosion Resistant Finish Drawer Slide	48
6400 Stainless Steel Drawer Slide	49
8000 Over Travel Undermount Pantry Drawer Slide	50
8500T Lateral File Drawer Systems	51

			Ту	Type Extension		ion	Disconnect Type				Open/Close Features							
	Mounting Style	Load Class	Roller Bearing	Ball-Bearing	3/4 Extension	Full Extension	1" Over Travel	No Disconnect	Friction Release	Lever Release	Lift Out	Quick Disconnect	Hold In Anti-Rebound	Hold-Out / Open	Lock Open	Self-Close	Push-to-Open	Soft-Close
6300	Side	100		•		•				•			•					
6400	Side	100		•		•				•			•					
8000	Under	130		•			•				•		•					
8500T	Side	150		•		•						•	•					

6300 Corrosion Resistant Finish Drawer Slide



Features

- Corrosion Resistant Finish passes 100 hour salt spray test
- USDA H-1 approved grease
- 32mm hole pattern
- · Lever disconnect for easy drawer removal
- · Hold-in detent
- Non-handed design
- Recommended maximum drawer width 24"

Stainless Steel Componenets

- Ball-Bearing Retainer
- Ball-Bearings
- Release Lever Rivets
- · Fasteners (included)


Mounting: Side

Action: Telescopic movement on ball-bearings

Load Rating: 100 lb. class Height: 1.79" [45.5mm]

Clearance: .50" + .03" - 0" on each side Finish: Corrosion Resistant (CR)

Profile:



Configurations



Poly (P)	1 pair per bag with screws; 10 pair per carton					
6300 Corrosion Resistant (CR) Finish						
Size	Poly (P)					
250mm	6300P CR 10					
300mm	6300P CR 12					
350mm	6300P CR 14					
400mm	6300P CR 16					
450mm	6300P CR 18					
500mm	6300P CR 20					
550mm	6300P CR 22					
600mm	6300P CR 24					
650mm	6300P CR 26					
700mm	6300P CR 28					

Recommended Fasteners
#7 x 1/2" Stainless Steel Phillips Pan Head Screws

Mounting Brackets



Product	Front or Rear	Finish	Pack
6340 RB	Rear	Corrosion Resistant (CR)	10 pair/carton

6400 Stainless Steel Drawer Slide





Features

- 304-Grade stainless steel
- Ideal for use in wet or corrosive environments
- USDA H-1 approved grease
- Lever disconnect
- Recommended drawer width 24"

Mounting: Side


Action: Telescopic movement on ball-bearings

Load Rating: 100 lb. class **Height**: 1.78" [45.2mm]

Clearance: .50" + .03" - 0" on each side

Finish: Stainless Steel (SS)

Profile:



Configurations



Poly (P)	1 pair per bag with screws; 10 pairs per carton
6400 Stainless	s Steel (SS) Finish
Size	Poly (P)
10"	6400P SS 10
12"	6400P SS 12
14"	6400P SS 14
16"	6400P SS 16
18"	6400P SS 18
20"	6400P SS 20
22"	6400P SS 22
24"	6400P SS 24
26"	6400P SS 26
28"	6400P SS 28

Recommended Fasteners	
#8 x 1/2" Stainless Steel Pan Head Screws	

Mounting Brackets



Product	Front or Rear	Finish	Pack			
6340 RB	Rear	Corrosion Resistant (CR)	10 pair/carton			

8000 Over Travel Undermount Pantry Drawer Slide





Features

- Removable mounting brackets
- Hold-in detent
- Key-hole style mounting holes
- 1" over travel

Mounting: Bottom mount


Action: Telescopic movement on ball-bearings

Load Rating: 130 lb. class Height: 1.54" [39mm]

2.25" [57mm] (includes brackets)

Clearance: 3/4" (slide only); 2-1/4" (with brackets)

Finish: Anochrome (ANO)



Configurations

Poly (P)	1 pair per bag with screws; 5 pairs per carton								
8000 Anochro	8000 Anochrome (ANO) Finish								
Size	Poly (P)								
12"	8000P 12								
14"	8000P 14								
16"	8000P 16								
18"	8000P 18								
20"	8000P 20								
22"	8000P 22								
24"	8000P 24								
26"	8000P 26								
28"	8000P 28								

Recommended Fasteners	KV Part	Finish	Qty
#8 x 5/8" Phillips Pan Head Screws	200114-6	Zinc (ZC)	1000

8500T Lateral File Drawer Systems



Features

- · Patented integrated anti-tilt mechanism
- Uses high-strength cable that laces through the drawer slides and snaps into place, allowing only one drawer to open at a time
- Accommodates drawers on 12" (±1/2") vertical centers
- · Non-handed quick disconnect rail
- Designed for use on lateral file applications where a drawer anti-tilt feature is needed
- Full extension slide with maximum 36" drawer width

Mounting: Side


Action: Progressive movement on ball-bearings

Load Rating: 150 lb. class Height: 5.15" [131mm]

Clearance: .50" + .03" - 0" on each side

Finish: Anochrome (ANO)

Profile:



Configurations

Quantity (Q) 20 pairs without screws; multiple cartons										
8500T Anochrome (A	8500T Anochrome (ANO) Finish									
Size Quantity (Q)										
16"	8500TQ 16									
18"	8500TQ 18									
20"	8500TQ 20									
Special Order Only										
8520T	Special Order									
8525T	Special Order									

Recommended Fasteners	KV Part	Finish	Qty
#7 x 1/2" Phillips Pin Head Screws	8500-93	Zinc (ZC)	1000

8500 Interlok™ Cable Accessory

Required for 8500T Interlok anti-tilt systems.

Product	Size	Packed			
8500T-11B 482	For 2-high lateral files	40 per carton			
8500T-11B 789	For 3-high lateral files	40 per carton			
8500T-11B 1095	For 4-high lateral files	40 per carton			

Note: Custom length cables are available as special order. Consult Customer Service for information and availability.



Overhead Door and Desk Slides

4461D 5/8 Extension Variable Height Keyboard Slide	53
8150, 8157 3/4 Extension Variable Height Keyboard Slides	54
8250 3/4 Extension Variable Height Pencil or Center Drawer Slide	55
8050 Hinged Door Slide	56

			Туре	Extension		D	Disconnect Type				Open/Close Features								
	Mounting Style	Load Class	Ball-Bearing	5/8 Extension	3/4 Extension	Full Extension	1" Over Travel	No Disconnect	Friction Release	Lever Release	Lift Out	Quick Disconnect	Hold In Anti-Rebound	Hold-Out / Open	Lock Open	Self-Close	Push-to-Open	Soft-Close	Shelf Tabs
4461D	Under	75	•	•				•					•	•					•
8150	Under	75	•		•					•			•	•					
8157	Under	75	•		•					•			•	•					•
8250	Under	75	•		•					•			•						

4461D 5/8 Extension Variable Height Keyboard Slide





Features

- Mounting brackets adjust to three heights and can be reversed for in-board and out-board mounting
- Anti-rebound stay-close design holds pencil drawer in closed position yet allows for easy opening
- Integrated shelf tabs

Mounting: Under surface


Action: Ball-bearing movement

Load Rating: 75 lb. class

Height: Overall drop height 3.75"

to 4.25" in 1/2" increments

Finish: Black (BLK)



Configurations

Poly (P) 1 pair per bag with screws; 5 pairs per carton				
4461D Black (BLK) Finish				
Size	Poly (P)			
15"	4461D			



8150, 8157 3/4 Extension Variable Height Keyboard Slide



Features

- Mounting brackets adjust to seven different heights and can be reversed for in-board/out-board mounting
- Track member quickly disconnects using positive lever release, easing installation
- Hold-out feature keeps drawer securely in the open position
- · Hold-in feature prevents keyboard tray bounce back

Extension: 8150: 3/4 extension keyboard slide

8157: 3/4 extension keyboard slide with shelf tabs

Mounting: Under surface
Action: Ball-bearing movement

Load Rating: 75 lb. class

Height: Overall drop height adjusts from 2.34" [59.4mm]


to 3.68" [93.5mm] in 7/32" increments


Clearance: 1.62" [41mm] per side out-board

.62" [15.7mm] per side in-board

Finish: Anochrome (ANO), Ebony Black (EB)

Profile:





Configurations



Poly (P)	1 pair per bag with screws; 10 pairs per carton				
8150 Anochrome (ANO) Finish					
Size	Poly (P)				
12"	8150P 12				
14"	8150P 14				
16"	8150P 16				
18"	8150P 18				
20"	8150P 20				
8150 Ebony Black	(EB) Finish				
12"	8150P EB 12				
14"	8150P EB 14				
16"	8150P EB 16				
18"	8150P EB 18				
20"	8150P EB 20				
8157 Anochrome (ANO) Finish				
14"	8157P 14				
16"	8157P 16				
18"	8157P 18				
20"	8157P 20				
8157 Ebony Black	(EB) Finish				
14"	8157P EB 14				
16"	8157P EB 16				
18"	8157P EB 18				
20"	8157P EB 20				

Recommended Fasteners	KV Part	Finish	Qty
#7 x 1/2" Phillips Pan Head Screws	8500-93	Zinc (ZC)	1000

Non-stock item – minimum order quantities and additional lead time may apply.

8250 3/4 Extension Variable Height Pencil or Center Drawer Slide



Features

- Mounting brackets adjust to seven heights and can be reversed for in-board and out-board mounting
- Anti-rebound stay-close design holds pencil drawer in closed position yet allows for easy opening
- Track member quickly disconnects using positive lever releases

Mounting: Under surface

Action: Ball-bearing movement

Load Rating: 75 lb. class


Height: Overall drop height 2.34" [59.4mm]

to 3.68" [93.5mm] in 7/32" increments

Clearance: 1.62" [41mm] per side out-board

.53" [13.5mm] per side in-board

Finish: Anochrome (ANO)



Configurations




Poly (P)	1 pair per bag with s	1 pair per bag with screws; 10 pairs per carton			
Quantity (Q)	20 pairs without scre	20 pairs without screws; multiple cartons			
8250 Anochrome (Al	NO) Finish	nish			
Size	Poly (P)	Quantity (Q)			
10"	8250P 10	8250Q 10			
12"	8250P 12	8250Q 12			
14"	8250P 14	8250Q 14			
16"	8250P 16	8250Q 16			
18"	8250P 18	8250Q 18			
20"	8250P 20	8250Q 20			
22"	8250P 22	8250Q 22			

Recommended Fasteners	KV Part	Finish	Qty
#7 x 1/2" Phillips Pan Head Screws	8500-93	Zinc (ZC)	1000

Non-stock item – minimum order quantities and additional lead time may apply.

8050 Hinged Door Slide



Features

- One-piece, non-marring roller
- Permanently staked hinge pin


Mounting: Under surface

Action: Ball-bearing movement

Load Rating: 20 lb. class

Clearance: 1.31" [33.3mm] minimum

Finish: Anochrome (ANO)



Configurations

Poly (P) 1 pair per bag with screws; 10 pairs per carton			
8050 Anochrome (ANO) Finish			
Size	Poly (P)		
12"	8050PEZ 12		
14"	8050PEZ 14		
16"	8050PEZ 16		
18"	8050PEZ 18		
20"	8050PEZ 20		
22"	8050PEZ 22		
24"	8050PEZ 24		

Recommended Fasteners	KV Part	Finish	Qty
#7 x 1/2" Phillips Pan Head Screws	8500-93	Zinc (ZC)	1000

Non-stock item – minimum order quantities and additional lead time may apply.




Up and under application



Door Slides and Hinge Kits

8070, 8071, 8072 Pivot Door Slides	58
8080, 8081, 8082 Pivot Door Slides	59
8091, 8092 Pivot Door Slides	60
4x4 Pocket Door Full Overlay Kit	61
KV Hinge Kits.	62

8070, 8071, 8072 Pivot Door Slides



Features

- · Cabinet acts as installation jig
- · Cushioned stops and door hold-out
- Three-way adjustable door hinge

Extension: 8070: 3/4 extension slide with self-close 35mm hinge

8071: 3/4 extension slide without hinge and base **8072:** 3/4 extension slide with included hinge base

Mounting: Side

Action: Ball-bearing movement

Load Rating: 30 lb. class

Maximum

Dimensions: Vertical doors: 42" high x 24" wide


Horizontal pivot doors: 24" high x 48" wide

Clearance:

Maximum Slide Width Including Hinges				
Туре	Standard	KV		
Self-close hinge	1-23/32"	1-21/32"		
Free-swing hinge	1-23/32"	1-21/32"		
Overlay hinge	1-23/32"	1-7/8"		
Thick door hinge	2-3/32"	_		
Extra-thick door hinge	2-13/32"	2-5/16"		

Finish: Ebony Black (EB)

Profile:



8090P CR Raised Panel Cassette Roller



Additional protection for raised panel doors

Product	Pack
8090P CR	1 per poly pack with screws; 20 per carton

Configurations

Poly (P)	1 pair per bag with screws; 10 pairs per carton				
8070EZ E	Ebony Black (EB)	8071EZ E	8071EZ Ebony Black (EB)		bony Black (EB)
			Hinges and baseplates are not included		included; Must es separately
Size	Poly (P)	Size	Poly (P)	Size	Poly (P)
12"	8070PEZ EB 12	12"	8071PEZ EB 12	12"	8072PEZ EB 12
14"	8070PEZ EB 14	14"	8071PEZ EB 14	14"	8072PEZ EB 14
16"	8070PEZ EB 16	16"	8071PEZ EB 16	16"	8072PEZ EB 16
18"	8070PEZ EB 18	18"	8071PEZ EB 18	18"	8072PEZ EB 18
20"	8070PEZ EB 20	20"	8071PEZ EB 20	20"	8072PEZ EB 20
22"	8070PEZ EB 22	22"	8071PEZ EB 22	22"	8072PEZ EB 22
24"	8070PEZ EB 24	24"	8071PEZ EB 24	24"	8072PEZ EB 24

Recommended Fasteners		KV Part	Finish	Qty
#	6 x 13/32" Phillips Pan Head Screws	1300-83	Zinc (ZC)	1000

Hinge Kit Options

8086 HKEZXEB

40 mm



Inset - Extra Thick Door

Hinge Kit (K)	2 hinges per kit; 10	2 hinges per kit; 10 kits per carton			
Mepla Nickel Hinges (For Use with 8072)					
Kit (K)	Hinge Cup Size	Door Thickness	Application		
8080 HKEZS	35 mm	3/4"	Inset		
8080 HKEZL	40 mm	3/4"	Partial Overlay		
8080 HKEZF	35 mm	3/4"	Inset - Free Swing		
8085 HKEZT	40 mm	1"	Inset - Thick Door		
8086 HKEZX	40 mm	1-1/4"	Inset - Extra Thick Door		
Mepla Ebony Black	k (EB) Hinges (For Use	with 8072)			
Kit (K)	Hinge Cup Size	Door Thickness	Application		
8080 HKEZSEB	35 mm	3/4"	Inset		
8080 HKEZLEB	40 mm	3/4"	Partial Overlay		
8085 HKEZTEB	40 mm	1"	Inset - Thick Door		

KV Hinges (For Use with 8071) Nickel Finish (hinge base included)					
Kit (K)	Hinge Cup Size	Door Thickness	Application		
8080 HKS SAL	35 mm	3/4"	Inset		
8080 HKF SAL	35 mm	3/4"	Inset - Free Swing		
8080 HKL SAL	40 mm	3/4"	Partial Overlay		
8086 HKX SAL	40 mm	1-1/4"	Inset - Thick Door		
KV Hinges (For Use	with 8071) Ebony Bla	ack (EB) Finish (hing	e base included)		
Kit (K)	Hinge Cup Size	Door Thickness	Application		
8080 HKS SAL EB	35 mm	3/4"	Inset		
8080 HKL SAL EB	40 mm	3/4"	Partial Overlay		
8086 HKX SAL FB	40 mm	1-1/4"	Inset - Thick Door		

1-1/4"

For additional information on our KV hinge offerings please see page 62.

8080, 8081, 8082 Pivot Door Slides



Features

Cushioned stops and door hold-out

• Three-way adjustable door hinge

Extension: 8080: 3/4 extension slide with self-close 35mm hinge

8081: 3/4 extension slide without hinge and base **8082:** 3/4 extension slide with attached hinge base

Mounting: Side

Action: Ball-bearing movement

Load Rating: 30 lb. class

Maximum

Dimensions: Vertical doors: 42" high x 24" wide


Horizontal pivot doors: 24" high x 48" wide

Clearance:

Maximum Slide Width Including Hinges			
Туре	Standard	KV	
Self-close hinge	1-23/32"	1-21/32"	
Free-swing hinge	1-23/32"	1-21/32"	
Overlay hinge	1-23/32"	1-7/8"	
Thick door hinge	2-3/32"	_	
Extra-thick door hinge	2-13/32"	2-5/16"	

Finish: Anochrome (ANO) Ebony Black (EB)

Profile:



8090P CR Raised Panel Cassette Roller



Additional protection for raised panel doors

Product	Pack
8090P CR	1 per poly pack with screws; 20 per carton

Configurations



Poly (P)	1 pair per bag with	1 pair per bag with screws; 10 pairs per carton				
8080EZ Anochrome (ANO)		8081EZ A	8081EZ Anochrome (ANO)		8082EZ Anochrome (ANO)	
Includes	hinges and bases	No hinges	or bases	Hinge ba	se only	
Size	Poly (P)	Size	Poly (P)	Size	Poly (P)	
12"	8080PEZ 12	12"	8081PEZ 12	12"	8082PEZ 12	
14"	8080PEZ 14	14"	8081PEZ 14	14"	8082PEZ 14	
16"	8080PEZ 16	16"	8081PEZ 16	16"	8082PEZ 16	
18"	8080PEZ 18	18"	8081PEZ 18	18"	8082PEZ 18	
20"	8080PEZ 20	20"	8081PEZ 20	20"	8082PEZ 20	
22"	8080PEZ 22	22"	8081PEZ 22	22"	8082PEZ 22	
24"	8080PEZ 24	24"	8081PEZ 24	24"	8082PEZ 24	
8080EZ	Ebony Black (EB)			8082EZ	Ebony Black (EB)	
12"	8080PEZ EB 12	_	_	12"	8082PEZ EB 12	
14"	8080PEZ EB 14	_	-	14"	8082PEZ EB 14	
16"	8080PEZ EB 16	_	-	16"	8082PEZ EB 16	
18"	8080PEZ EB 18	_	_	18"	8082PEZ EB 18	
20"	8080PEZ EB 20	_	_	20"	8082PEZ EB 20	
22"	8080PEZ EB 22	_	_	22"	8082PEZ EB 22	
24"	8080PEZ EB 24	_	_	24"	8082PEZ EB 24	
		-				

Recommended Fasteners	KV Part	Finish	Qty
#6 x 13/32" Phillips Pan Head Screws	1300-83	Zinc (ZC)	1000

Hinge Kit Options




Hinge Kit (K)	2 hinges per kit; 10 kits per carton				
Mepla Nickel Hinge	s (For Use with 8082)	For Use with 8082P and 8082Q)			
Kit (K)	Hinge Cup Size	Door Thickness	Application		
8080 HKEZS	35 mm	3/4"	Inset		
8080 HKEZL	40 mm	3/4"	Partial Overlay		
8080 HKEZF	35 mm	3/4"	Inset - Free Swing		
8085 HKEZT	40 mm	1"	Inset - Thick Door		
8086 HKEZX	40 mm	1-1/4"	Inset - Extra Thick Door		
Mepla Ebony Black	(EB) Hinges (For Use	with 8082P and 80	82Q)		
Kit (K)	Hinge Cup Size	Door Thickness	Application		
8080 HKEZSEB	35 mm	3/4"	Inset		
8080 HKEZLEB	40 mm	3/4"	Partial Overlay		
8085 HKEZTEB	40 mm	1"	Inset - Thick Door		
8086 HKEZXEB	40 mm	1-1/4"	Inset - Extra Thick Door		

KV Hinges (For Use with 8081P) Nickel Finish (hinge base included)				
Kit (K)	Hinge Cup Size	Door Thickness	Application	
8080 HKS SAL	35 mm	3/4"	Inset	
8080 HKF SAL	35 mm	3/4"	Inset - Free Swing	
8080 HKL SAL	40 mm	3/4"	Partial Overlay	
8086 HKX SAL	40 mm	1-1/4"	Inset - Thick Door	
KV Hinges (For Use with 8081P) Ebony Black (EB) Finish (hinge base included)			nge base included)	
Kit (K)	Hinge Cup Size	Door Thickness	Application	
8080 HKS SAL EB	35 mm	3/4"	Inset	
8080 HKL SAL EB	40 mm	3/4"	Partial Overlay	
8086 HKX SAL EB	40 mm	1-1/4"	Inset - Thick Door	

For additional information on our KV hinge offerings please see page 62.

8091, 8092 Pivot Door Slides



Features

- · Rack and pinion design
- Multiple hinge options
- · Greatly reduces door sag

NOTE: 3/4 Full Overlay applications require 8091 slides. Full Overlay Kit and 8091 slides much be attached to a partition wall.

8091: Hinge and baseplate not included

8092: Baseplate attached; hinge must be ordered separately

Mounting: Side

Action: Ball-bearing movement


Load Rating: 75 lb. class

Maximum

Dimensions: Vertical doors: 72" high x 26" wide

Clearance:

Maximum Slide Width Including Hinges		
Туре	Standard	KV
Self-close hinge	1-23/32"	1-21/32"
Free-swing hinge	1-23/32"	1-21/32"
Overlay hinge	1-23/32"	1-7/8"
Thick door hinge	2-3/32"	-
Extra-thick door hinge	2-13/32"	2-5/16"



8090P CR Raised Panel Cassette Roller



Additional protection for raised panel doors

Product	Pack
8090P CR	1 per poly pack with screws; 20 per carton

Configurations

Poly (P)	1 pair per bag with s	1 pair per bag with screws; 1 pair per carton		
8091 Ebony Black (EB)		8092 Ebony B	Black (EB)	
Size	Poly (P)	Size	Poly (P)	
12"	8091SP EB 12	12"	8092SP EB 12	
13"	8091SP EB 13	13"	8092SP EB 13	
14"	8091SP EB 14	14"	8092SP EB 14	
15"	8091SP EB 15	15"	8092SP EB 15	
16"	8091SP EB 16	16"	8092SP EB 16	
18"	8091SP EB 18	18"	8092SP EB 18	
20"	8091SP EB 20	20"	8092SP EB 20	
22"	8091SP EB 22	22"	8092SP EB 22	
24"	8091SP EB 24	24"	8092SP EB 24	
26"	8091SP EB 26	26"	8092SP EB 26	
28"	8091SP EB 28	28"	8092SP EB 28	
30"	8091SP EB 30	30"	8092SP EB 30	

Recommended Fasteners	KV Part	Finish	Qty
#6 x 13/32" Phillips Pan Head Screws	1300-83	Zinc (ZC)	1000

Hinge Kit Options



Hinge Kit (K)	2 hinges per kit; 10 kits per carton												
Mepla Nickel Hinge	Mepla Nickel Hinges (For Use with 8092)												
Kit (K)	Hinge Cup Size	Door Thickness	Application										
8080 HKEZS	35 mm	3/4"	Inset										
8080 HKEZL	40 mm	3/4"	Partial Overlay										
8080 HKEZF	35 mm	3/4"	Inset - Free Swing										
8085 HKEZT	40 mm	1"	Inset - Thick Door										
8086 HKEZX	40 mm	1-1/4"	Inset - Extra Thick Door										
Mepla Ebony Black	(EB) Hinges (For Use	with 8092)											
Kit (K)	Hinge Cup Size	Door Thickness	Application										
8080 HKEZSEB	35 mm	3/4"	Inset										
8080 HKEZLEB	40 mm	3/4"	Partial Overlay										
8085 HKEZTEB	40 mm	1"	Inset - Thick Door										
8086 HKEZXEB	40 mm	1-1/4"	Inset - Extra Thick Door										


KV Hinges (For Use with 8091) Nickel Finish (hinge base included)											
Kit (K)	Hinge Cup Size	Door Thickness	Application								
8080 HKS SAL	35 mm	3/4"	Inset								
8080 HKF SAL	35 mm	3/4"	Inset - Free Swing								
8080 HKL SAL	40 mm	3/4"	Partial Overlay								
8086 HKX SAL	40 mm	1-1/4"	Inset - Thick Door								
KV Hinges (For Use	with 8091) Ebony Bla	ıck (EB) Finish (hin	ge base included)								
Kit (K)	Hinge Cup Size	Door Thickness	Application								
8080 HKS SAL EB	35 mm	3/4"	Inset								
8080 HKL SAL EB	40 mm	3/4"	Partial Overlay								
8086 HKX SAL EB	40 mm	1-1/4"	Inset - Thick Door								


For additional information on our KV hinge offerings please see page 62.

8090B Pinion Shafts for 4x4 Pocket Door Slides


SB Pack (SB) - 1 pair of shafts	Bulk Pack (B) - 10 each								
8090B Pinion Shaft Ebony Black (EB) Finish										
Size	Bulk (B)	Quantity								
36"	8090B EB 36	10								
48"	8090B EB 48	10								
72"	8090B EB 72	10								
8092SB Pin	ion Shaft Ebony Black	(EB) Finish								
36"	8092SB EB 36	2								
48"	8092SB EB 48	2								
72"	8092SB EB 72	2								

4x4 Pocket Door Full Overlay Kit





Bracket diagram for Mepla hinge



NOTE: 3/4 Full Overlay applications require 8091 slides. Full Overlay Kit and 8091 slides much be attached to a partition wall.

Features

- Provides a full door overlay on doors up to .75" thick
- Does not compromise key performance features of 4x4 pocket door system
- Systems for both Mepla and KV hinges
- Requires 8091 slide
- Must attach to a partition wall

Mounting: Mounts directly to KV 8091 Series slide

Load Rating: 75 lb. class **Finish**: Black

Configurations

		Brackets	Overlay Hinges	Hinge Bases	Hinge Cover Base	Protective Felt Pads	Packed		
	Poly (P)	Qty: 2	Qty: 4	Qty: 4	Qty: 4	Qty: 4	1 kit/ carton		
2004 Full Quarkey Peaket Dear Vit Block (BLV) Finish									


8091 Full Overlay Pocket Door Kit Black (BLK) Finish								
Poly (P)	Hinge							
8091SFULL34M	Mepla							
8091SFULL34S	KV							

8091 Full Overlay Pocket Door Kit Black (BLK) Finish									
Door Thickness	Amount of Overlay	Pocket Width							
3/4"	3/4"	1-3/4"							
13/16"	11/16"	1-13/16"							
7/8"	5/8"	1-7/8"							
15/16"	9/16"	1-15/16"							
1"	1/2"	2"							
1-1/16"	7/16"	2-1/16"							
1-1/8"	3/8"	2-1/8"							
1-3/16"	5/16"	2-3/16"							
1-1/4"	1/4"	2-1/4"							

Full Overlay Kit Installation Requirements

- Overlay kits require the use of a KV 8091 series slide
- Overlay kits require the use of a pinion shaft
- Overlay kits require the use of a partition wall within the cabinet

KV Hinge Kits



1. Depth Adjustment Cam

The horizontal (lateral) adjustment range is 6mm. The depth adjustment range is 3.1 mm (-0.5mm to +2.8mm) for all hinge bases.

2. Horizontal (Lateral) Adjustment Cam

The horizontal (lateral) adjustment range is 6mm (-1.5mm to +4.5mm for 35mm cup hinges; -0.5mm to +5.5mm for 40mm cup hinges), while maintaining a constant gap behind the door.

3. Vertical (Height) Adjustment Cam

The vertical (height) adjustment range is 4mm (-2mm to +2mm).

Features

- · Three-way cam hinges for easy adjustment
- Horizontal, vertical and depth changes can be made without loosening any screws
- Four types of hinges for a variety of application

Clearance: 8080 HKS standard hinge: 1-21/32"

8080 HKF free swing hinge: 1-21/32" 8080 HKL partial overlay hinge: 1-37/64" 8080 HKX extra thick door hinge: 1-37/64"

Finish: Black (BLK), Nickel (NP)

Configurations

Pack C	onfigurations	Hinge Base	Hinges	Screws	Cover Caps				
Kit (K)	2 per bag; 10 bags per carton	Yes	Yes	Yes	Yes				
Nickel	(NP) Finish KV I	linges for Use v	with 8071, 80	081, 8091 Pocket [Ooor Slides				
Kit (K)		Hinge Cup Siz	ze	Door Thickness	Application				
8080 HKS SAL		35 mm		3/4"	Inset				
8080 H	KF SAL	35 mm		3/4"	Inset - Free Swing				
8080 H	KL SAL	40 mm		3/4"	Partial Overlay				
8086 H	KX SAL	40 mm		1-1/4"	Inset - Thick Door				
Black (EB) Finish KV H	inges for Use w	ith 8071, 80	81, 8091 Pocket D	oor Slides				
Kit (K)		Hinge Cup Siz	ze	Door Thickness	Application				
8080 HKS SAL EB		35 mm		3/4"	Inset				
8080 HKL SAL EB		40 mm		3/4"	Partial Overlay				
8086 HKX SAL EB		40 mm		1-1/4"	Inset - Thick Door				



Shelving

Adjustable Wall Shelving Quick Reference Guide
Pilaster Shelving Systems65255/256 Series Mortise-Mount Pilaster Shelving Systems65233/237 Series Surface-Mount Pilaster Shelving System67
Regular-Duty Adjustable Shelving Systems6871/170 Regular-Duty Narrow Standard and Bracket System6880/180 Regular-Duty Standard and Bracket System69160LL/179/181 Series Specialty Brackets71
Heavy-Duty Adjustable Shelving Systems7382/182 Series Heavy-Duty Standard and Bracket System7383/183 Series Heavy-Duty Standard and Bracket System75161LL Heavy-Duty Lock Lever Bracket76
Extra-Duty Adjustable Shelving System
Super-Duty Adjustable Steel Shelving System791987 Series Galvanized Steel Shelving7987/186/187 Series Super-Duty Standard and Bracket System791987 Series Stainless Steel Shelving8187/186/187 Super-Duty Stainless Steel Standard and Bracket System81

Built-In Shelving and Shelf Supports83
5mm Series Shelf Supports
5mm Series Vinyl Coated Shelf Supports
1/4" Series Shelf Supports
5mm Series Grommets
1/4" Series Grommets
7/32" Series Shelf Supports
Utility Shelving Brackets
206 Series Extra-Duty Folding L-Bracket
208 Series Ultimate L-Bracket
221 Series Utility L-Bracket
Decorative Shelving Brackets
0035 & 0036 Designer Shelf Bracket
0117 & 0118 Designer Shelf Bracket
215 Series Slim-Line $^{\text{\tiny M}}$ Shelf Bracket
217 Series Silhouette™ Shelf Bracket
200 Series Designer Decorative Shelf Brackets
201 Series Premium Decorative Shelf Brackets
Shelf Board91
1980 Series All-Purpose Shelf Board

Adjustable Wall Shelving Quick Reference Guide

Knape and Vogt pioneered the development of the modern standards and bracket system of adjustable wall shelving, and we're still the leader in selection, quality and innovation. With one of the industry's widest selection of systems and component accessories, chances are we make a shelving system just right for you. To aid your selection process, we've created a comparison chart that lists the vital characteristics of our standards and bracket systems, as well as available finishes and accessories. If you still have questions or need more details, please contact KV Customer Service.

				Feat	ures							Fin	ish Op	otions					F	Pack (Option	s
Part	Description	1" Center Adjustment	1-1/4" Center Adjustment	2" Center Adjustment	Single Track	Double Track	Lock Lever	Anochrome (ANO)	Black (BLK)	Brass-look (BR)	Brown (BRN)	Clear (CL)	Stainless Steel (SS)	Galvanized Steel (GALV)	Titanium (TI)	White (WH)	Zinc (ZC)	Economy Zinc (E)	Standard Pack	Builders Pack (BP)	Display Pack (DP)	Hefty Pack (HP)
71/170 Regular-Duty	Narrow Adjustable Standa	rd a	nd B	racke	et Sy	sten	ı															
71	Narrow Faced Standard	•			•			•											•			
170	Bracket	•			•			•											•			
80/180 Regular-Duty	Adjustable Standard and B	rack	ket Sy	/sten	n																	
80	Standard	•			•			•	•	•	•				•	•			•	•		
180	Bracket	•			•			•	•	•	•				•	•			•	•		•
181	Lipless Bracket	•			•			•											•			
160LL	Lock Lever Bracket	•			•		•	•											•			
179	Adjustable Angle Bracket	•			•			•											•			
82/182 Heavy-Duty Ad	djustable Standard and Bra	cke	t Sys	tem																		
82	Standard		•			•			•						•	•			•	•		
182	Bracket		•			•			•						•	•			•	•		
182BE	Bookend		•			•										•			•			
82DP Screw	Screws/Anchors																•				•	
182DP LCTR/JNR	Shelf Locater/Joiner											•									•	
182DP LOCK	Bracket Lock Tab		•			•			•												•	
83/183 Oversized Hea	vy-Duty Adjustable Standa	ırd a	nd B	rack	et Sy	sten	n															
83	Oversized Standard	•			•			•											•			
183	Flange Bracket	•			•			•											•			
161LL	Lock Lever Bracket	•			•		•	•											•			
85/185 Extra-Duty Adj	justable Standard and Brad	cket	Syste	em																		
85	Standard	•				•		•								•			•			
185	Bracket	•				•		•								•			•			
106 ANO	Shelf Rest							•											•			
107 ANO	Hang Rod Clamp							•											•			
87/187 Super-Duty Ac	djustable Standard and Bra	icke	t Sys	tem																		
87	Standard			•	•			•					•			•			•			
186LL	Lock Lever Bracket			•	•		•	•					•			•			•			
187LL	Lock Lever Bracket			•	•		•	•					•			•			•			
1987	Steel Shelves												•	•					•			

255™/256™ Series Mortise-Mount Pilaster Shelving System

- Holds up to 500 lbs. per shelf*
- 1/2" vertical slot adjustment

- · Wide selection of finishes and sizes
- Limited lifetime warranty

255 Series Steel Standards

Dimensions: 5/8" width x 3/16" deep x selected length

Material: 23 gauge high strength steel

20 gauge galvanized steel: Economy Zinc (E) products only

Almond (ALM), Brass-look (BR), Brown (BRN), White (WH), Finish:

Zinc (ZC), Economy Zinc (E)

Origin: Made in the USA

Features: Numbered slots for fast, accurate clip insertion; countersunk

nail and screw holes; full finish coverage to deter corrosion;

precision cut lengths; BHMA Grade 1 Compliant*

Pack Configurations

Standard	b	12"-60", packed 100 standards per carton; 72"-96", packed 50 standards per carton									
Retail (P	K)	20 standards per	carton								
255 Ste	el Standards Standa	ard Pack									
Size	Almond (ALM)	Brass-look (BR)	Brown (BRN)	Economy Zinc (E)	White (WH)	Zinc (ZC)					
12"	255 ALM 12	255 BR 12	255 BRN 12	255 E 12	255 WH 12	255 ZC 12					
18"	255 ALM 18	255 BR 18	255 BRN 18	_	255 WH 18	255 ZC 18					
24"	255 ALM 24	255 BR 24	255 BRN 24	255 E 24	255 WH 24	255 ZC 24					
30"	255 ALM 30	-	255 BRN 30	-	255 WH 30	255 ZC 30					
36"	255 ALM 36	255 BR 36	255 BRN 36	255 E 36	255 WH 36	255 ZC 36					
42"	_	_	_	_	_	255 ZC 42					
48"	255 ALM 48	255 BR 48	255 BRN 48	255 E 48	255 WH 48	255 ZC 48					
60"	255 ALM 60	255 BR 60	255 BRN 60	255 E 60	255 WH 60	255 ZC 60					
72"	255 ALM 72	255 BR 72	255 BRN 72	255 E 72	255 WH 72	255 ZC 72					
84"	255 ALM 84	255 BR 84	255 BRN 84	255 E 84	255 WH 84	255 ZC 84					
96"	255 ALM 96	255 BR 96	255 BRN 96	255 E 96	255 WH 96	255 ZC 96					
255 Ste	el Standards Retail	Pack (PK)									
24"	_	_	_	_	_	PK255 ZC 24					
36"	_	PK255 BR 36	_	_	PK255 WH 36	PK255 ZC 36					
48"	-	PK255 BR 48	_	-	PK255 WH 48	PK255 ZC 48					
60"	_	PK255 BR 60	_	-	PK255 WH 60	PK255 ZC 60					
72"	_	PK255 BR 72	_	_	PK255 WH 72	PK255 ZC 72					



255 Series Aluminum Standards

Dimensions: 5/8" width x 3/16" deep x selected length

Material: 17 gauge aluminum

Finish: Natural (AL), Brass-look (BR), Brown (BRN), Walnut (WAL) Origin: Made in the USA

Features: Numbered slots for fast, accurate clip insertion; countersunk

> nail and screw holes; made of rust resistant aluminum; precision cut lengths; BHMA Grade 3 Compliant*

Pack Configurations



Non-stock item – minimum order quantities and additional lead time may apply.



Plated finish products only

65

^{*}Standards and brackets meet or exceed ANSI performance standards as established by BHMA testing requirements.

255™/256™ Series Mortise-Mount Pilaster Shelving System

256 Series Pilaster Shelf Support

Material: High-strength steel, Aluminum (AL)

Finish: Almond (ALM), Brass-look (BR), Walnut (WAL), White (WH),

Zinc (ZC), Natural Aluminum (AL NAT)

Origin: Made in the USA

Features: Patented design; full coverage finish to resist corrosion;

strength increasing dimple

Pack Configurations



256WP ZC

Standard Pack		100 pieces per carton							
Bulk (B)		1000 pieces per carton							
Barrel (BBL)		9000 pieces per b	oarrel						
Poly (P)		12 supports and 2	28 nails per bag; 10	bags per carton					
Warehouse (WF)	12 supports and 2	28 nails per bag; 50	bags per carton					
256 Shelf Supp	Supports Almond (ALM) Finish								
Standard	Bulk (B)	Barrel (BBL)	Poly (P)	Warehouse (WP)					
256S ALM	_	_	_	_					
256 Shelf Sup	oorts Brass-look (B	R) Finish							
256 BR	256B BR	256BBL BR	256P BR	_					
256 Shelf Sup	oorts Walnut (WAL)	Finish							
256 WAL	256B WAL	256BBL WAL	256BBL WAL –						
256 Shelf Sup	oorts White (WH) Fi	inish							
256S WH	_	_	256S P WH 256S WP WH						













NOTE: Use 256 WAL with 255 BRN and 255AL WAL

Specialty Pilaster Shelf Supports

256 Shelf Supports Natural Aluminum (AL NAT) Finish

256 Shelf Supports Zinc (ZC) Finish

256B ZC

256 ZC

256 AL NAT

Part #: 256R ZC: Support with Rubber Cushion

239 ZC*: Shelf Support

24276 ZC: Shelf Support with Mounting Hole 243 ZC: 3" Shelf Bracket (non-handed) 244 ANO: Wire Shelf Support

256BBL ZC

256P ZC

757 ANO: Flange for 1-1/16" OD closet rod

Material: High-strength steel, cold rolled steel

Finish: Anochrome (ANO), Zinc (ZC)

Origin: Made in the USA Packed: 100 per carton









229 Series Support Bracket

Finish: Anochrome (ANO)
Packed: 25 per carton

229 Bracket	
Size	Anochrome (ANO)
4"	229 ANO 4
6"	229 ANO 6
8"	229 ANO 8
10"	229 ANO 10





Non-stock item – minimum order quantities and additional lead time may apply.

233™/237™ Series Surface-Mount Pilaster Shelving System

- Holds up to 500 lbs. per shelf*
- 1/2" vertical slot adjustability

- BHMA Grade 1 Compliant*
- · Limited lifetime warranty

233 Surface Mount Steel Pilaster Standards

Dimensions: 13/16" width x 3/16" deep x selected height

Material: 23 gauge high-strength steel

Finish: Brass-look (BR), Steel (STL), Zinc (ZC)

Origin: Made in the USA

Features: Numbered slots for quick, accurate clip insertion; countersunk

nail, screw and staple holes; full finish coverage to deter

corrosion; precision cut lengths

Pack Configurations

Standard	12"-60" packed 100 standards per carton; 72"-96" packed 50 standards per carton		
233 Serie	s Steel Standards S	Standard Pack	
Size	Brass-look (BR)	Steel (STL)	Zinc (ZC)
12"	233 BR 12	233 STL 12	233 ZC 12
18"	_	_	233 ZC 18
24"	_	233 STL 24	233 ZC 24
36"	233 BR 36	233 STL 36	233 ZC 36
48"	233 BR 48	233 STL 48	233 ZC 48
60"	233 BR 60	233 STL 60	233 ZC 60
72"	233 BR 72	233 STL 72	233 ZC 72
96"	233 BR 96	233 STL 96	233 ZC 96





Pilaster Shelf Supports

Finish:

Part #: 237 ZC: Shelf support for 233 pilaster

238 ANO: Shelf support with locator tab

242 ANO: Wire shelf support Anochrome (ANO), Zinc (ZC)

Featured: Made in the USA
Packed: 100 pieces per carton

Features: Full finish coverage to deter corrosion



237





242

Nails for 255 and 233 Series Standards

Pack Configurations

Standard	Approximately 650 nails per bag; 5 bags per carton		
255 and 233 Na	ils		
Part	Finish	Use with:	
255-81N ALM	Almond (ALM)	255 ALM	
255-81N BR	Brass-look (BR)	255 BR, 233 BR, 255AL BR	
255-81N STB	Bronzed (STB)	255 BRN, 255 AL BRN, 255AL WAL	
255-81N WH	White (WH)	255 WH	
255-81N ZC	Zinc (ZC)	255 ZC, 233 ZC, 255E, 255AL	



^{*}Standards and brackets meet or exceed ANSI performance standards as established by BHMA testing requirements.

71™/170™ Regular-Duty Standard and Bracket System

71 Series Narrow Standards

Dimensions: 5/16" wide x 13/32" deep x selected height

Material: 13 gauge steel
Finish: Anochrome (ANO)
Origin: Made in the USA

Features: Narrow design to fit between prefabricated wall panels for

flush wall mount; countersunk screw holes; center aligned

slots and screw holes; precision cut lengths

170 ANO Series Brackets

Material: 14 gauge steel
Finish: Anochrome (ANO)
Origin: Made in the USA

Features: Holds up to 210 lbs. per pair; two locking teeth;

shelf retaining lip; stamped wing stablizer

Pack Configurations

Standard	10 per carton
71 Series Standards	
Size	Anochrome (ANO)
48"	71 ANO 48
60"	71 ANO 60
72"	71 ANO 72
96"	71 ANO 96

Pack Configurations

Standard	10 per carton
170 ANO Series Brackets	
Size	Anochrome (ANO)
10"	170 ANO 10
12"	170 ANO 12
14"	170 ANO 14





Non-stock item – minimum order quantities and additional lead time may apply.

80™/180™ Regular-Duty Standard and Bracket System

· Single slot design

• 1" vertical slot adjustability

• BHMA Grade 2 Compliant*

· Limited lifetime warranty

80 Series Standards

Dimensions: 5/8" wide x 13/32" deep x selected length

Material: 16 gauge steel

Finish: Anochrome (ANO), Black (BLK), Brass-look (BR),

Brown (BN), Titanium (TI), White (WH)

Origin: Made in the USA

Features: Countersunk screw holes; safety lead-in at top of standards;

embossed "up" and arrow to show correct orientation; center aligned slots and screw holes; precision cut lengths

Pack Configurations



Standar	d	10 standards per carton, with UPC labels					
Builders	Pack (BP)	25 standards p	25 standards per carton, no UPC labels				
80 Seri	es Standards Sta	ndard Pack					
Size	Anochrome (ANO)	Black (BLK)	Brown (BN)	Brass-look (BR)	Titanium (TI)	White (WH)	
12"	80 ANO 12	80 BLK 12	80 BN 12	80 BR 12	80 TI 12	80 WH 12	
18"	80 ANO 18	-	_	-	-	_	
24"	80 ANO 24	80 BLK 24	80 BN 24	80 BR 24	80 TI 24	80 WH 24	
36"	80 ANO 36	80 BLK 36	80 BN 36	80 BR 36	80 TI 36	80 WH 36	
48"	80 ANO 48	80 BLK 48	80 BN 48	80 BR 48	80 TI 48	80 WH 48	
60"	80 ANO 60	80 BLK 60	80 BN 60	80 BR 60	80 TI 60	80 WH 60	
72"	80 ANO 72	80 BLK 72	80 BN 72	80 BR 72	80 TI 72	80 WH 72	
84"	80 ANO 84	_	_	_	_	_	
96"	80 ANO 96	80 BLK 96	_	_	_	80 WH 96	

80 Series Standards Builder Pack (BP)			
Size Anochrome (ANO)			
24"	80BP ANO 24		
36"	80BP ANO 36		
48"	80BP ANO 48		
60"	80BP ANO 60		
72"	80BP ANO 72		
84"	80BP ANO 84		
96"	80BP ANO 96		



^{*}Standards and brackets meet or exceed ANSI performance standards as established by BHMA testing requirements.

80™/180™ Regular-Duty Standard and Bracket System

180 Series Brackets

Material: 14 and 16 gauge steel

Finish: Anochrome (ANO), Black (BLK), Brass-look (BR), Brown (BN),

10 brackets per carton with UPC labels attached

Titanium (TI), White (WH)

Origin: Made in the USA

Features: Holds up to 320 lbs. per pair*; two complete locking teeth; spring steel clip for stability

and friction lock; shelf retaining lip

Pack Configurations

Standard



ANO ROHS

BLK ROHS

BR ROHS

WH -ROHS

Hefty F	Pack (HP)	40 brackets per display carton, with UPC labels					
Builde	rs Pack (BP)	100 brackets per carton, no UPC labels					
180 S	180 Series Brackets Standard Pack						
Size	Anochrome (ANO)	Black (BLK)	Brown (BN)	Brass-look (BR)	Titanium (TI)	White (WH)	
4"	180 ANO 4	180 BLK 4	-	-	-	180 WH 4	
6"	180 ANO 6	180 BLK 6	180 BN 6	180 BR 6	180 TI 6	180 WH 6	
8"	180 ANO 8	180 BLK 8	180 BN 8	180 BR 8	180 TI 8	180 WH 8	
10"	180 ANO 10	180 BLK 10	180 BN 10	180 BR 10	180 TI 10	180 WH 10	
12"	180 ANO 12	180 BLK 12	180 BN 12	180 BR 12	180 TI 12	180 WH 12	
14"	180 ANO 14	180 BLK 14	_	180 BR 14	_	180 WH 14	
16"	180 ANO 16	180 BLK 16	180 BN 16	180 BR 16	180 TI 16	180 WH 16	
18"	180 ANO 18	_	_	_	_	180 WH 18	
20"	180 ANO 20	_	_	_	_	180 WH 20	
180 S	180 Series Brackets Hefty Pack (HP)						
6"	_	_	_	_	180HP TI 6	180HP WH 6	
8"	180HP ANO 8	180HP BLK 8	_	_	180HP TI 8	180HP WH 8	
10"	180HP ANO 10	180HP BLK 10	-	_	180HP TI 10	180HP WH 10	
12"	180HP ANO 12	180HP BLK 12	_	_	180HP TI 12	180HP WH 12	
16"	180HP ANO 16	180HP BLK 16	_	_	180HP TI 16	180HP WH 16	

180 Series Brackets Bu					
6"	180BP ANO 6				
8"	180BP ANO 8				
10"	180BP ANO 10				
12"	180BP ANO 12				
14"	180BP ANO 14				
16"	180BP ANO 16				
18"	180BP ANO 18				



Locking Teeth Side View

Dimensions: #6 head, #8 body, 1-1/2" length

Finish: Anochrome (ANO), Black (BLK), Brown (BN), Brass-look (BR),

Titanium (TI), White (WH), Zinc (ZC)

Features: For proper installation of 80 series standards

Pack Configurations

Screws and Anchors

Display Pack ([OP)	20 poly bags per carton; each poly bag contains 6 screws and 6 screw anchors			rew anchors	
Standard Pack		50 screws per p	50 screws per pack, no anchors			
80 Series Scr	ew Packs					
Pack Type	Anochrome (ANO)	Black (BLK)	Brass-look (BR)	Titanium (TI)	White (WH)	Zinc (ZC)
Display Pack	80-88DP ANO	80-88DP BLK	80-88DP BR	80-88DP TI	80-88DP WH	-
Standard Pack	-	80-80 BLK	80-80 BR	-	80-80 WH	80-80 ZC

80™/180™ Series Regular-Duty Standard and Bracket System

160LL™ Series Lock Lever Bracket

Material: 14 gauge steel Finish: Anochrome (ANO) Origin: Made in the USA

Features: For use with 1" adjustable standards; two locking teeth;

lever lock for extra secure mounting and stability;

shelf retaining lip

Pack Configurations

Standard	10 per carton, no UPC labels		
160 Series Brackets			
Size	Anochrome (ANO)		
6"	160LL ANO 6		
8"	160LL ANO 8		
10"	160LL ANO 10		
12"	160LL ANO 12		
14"	160LL ANO 14		
16"	160LL ANO 16		
18"	160LL ANO 18		

179™ Series Adjustable Angle Brackets

Material: 14 and 16 gauge steel Finish: Anochrome (ANO) Origin: Made in the USA

Features: For use with 1" adjustment standards; two complete locking

teeth; shelf retaining lip; spring clip for stability and friction

locking; adjust to 15°, 30°, 45° and level

Pack Configurations

Standard	10 per carton, no UPC labels			
179 Series Brackets				
Size	Anochrome (ANO)			
10"	179 ANO 10			
12"	179 ANO 12			
14"	179 ANO 14			





181™ Series Lipless Brackets

Material: 14 and 16 gauge steel Finish: Anochrome (ANO) Origin: Made in the USA

Features: For use with 1" adjustment standards; two complete locking

teeth; spring clip provides stability and a friction lock; lipless version of the 180 series bracket to allow for easy concealing

of the bracket

Pack Configurations

Standard	10 per carton, no UPC labels
181 Series Brackets	
Size	Anochrome (ANO)
8"	181 ANO 8
10"	181 ANO 10
12"	181 ANO 12
14"	181 ANO 14
16"	181 ANO 16



Non-stock item – minimum order quantities and additional lead time may apply.

80™/180™ Series Regular-Duty Standard and Bracket System

Accessories		101 PLAS	102 PLAS	103 PLAS
Packed:	100 per carton			11-11-1
101 PLAS:	Clear plastic back rest with divider		404	4-
102 PLAS:	Clear plastic front rest with divider	103-1/2	104 ANO	104 PLAS
103 PLAS:	Clear plastic front rest	The state of the s		The state of the s
103-1/2L PLAS:	Clear plastic front rest left	A Walley St. All		W. W.
103-1/2R PLAS:	Clear plastic front rest right			
104 ANO:	Anochrome (ANO) steel back rest	104 1/0 DLAC	110 DUD	100 DUD
104 PLAS:	Clear plastic back rest	104-1/2 PLAS	119 RUB	129 RUB
104-1/2 PLAS:	Clear plastic back rest	The state of the s		
119 RUB:	Gray rubber cushion use with metal rests			
129 RUB:	Gray rubber cushion use with plastic rests	40		
136 ANO:	Socket-#80 standard bottom socket	136	137	154
137 ANO:	Socket-#80 standard top socket	100	107	104
154 ANO:	Shelf-fastener (fastens shelf to bracket)			

82™/182™ Series Heavy-Duty Standard and Bracket System

· Double slot design

• 1-1/4" vertical slot adjustability

• BHMA Grade 2 Compliant*

Limited lifetime warranty

82 Series Standards

Dimensions: 1-1/16" wide x 11/16" deep x selected length

Material: 14 gauge steel

Finish: Black (BLK), Titanium (TI), White (WH)

Pack Configurations



		10 standards per carton with UPC labels		
		10 standards per carton, no UPC labels		
82 Series S	Standards Standard Pac	ck	k	
Size	Black (BLK)	Titanium (TI)	White (WH)	
16.5"	82 BLK 16.5	82 TI 16.5	82 WH 16.5	
28"	82 BLK 28	82 TI 28	82 WH 28	
39"	82 BLK 39	82 TI 39	82 WH 39	
48"	82 BLK 48	82 TI 48	82 WH 48	
63"	82 BLK 63	82 TI 63	82 WH 63	
78"	82 BLK 78	82 TI 78	82 WH 78	
94"	82 BLK 94	82 TI 94	82 WH 94	
82 Series Standards Builders Pack (BP)				
16.5"	82BP BLK 16.5	_	82BP WH 16.5	
28"	82BP BLK 28	_	82BP WH 28	
39"	82BP BLK 39	_	82BP WH 39	
48"	82BP BLK 48	_	82BP WH 48	
63"	82BP BLK 63	_	82BP WH 63	
78"	82BP BLK 78	_	82BP WH 78	
94"	82BP BLK 94	_	82BP WH 94	

Origin: Made in the USA

Features: Strength enhancing ribs; countersunk screw holes; embossed

"up" and arrow to show correct orientation; center aligned

slots and screw holes; precision cut lengths



Accessories

182BE Bookend

Finish: White (WH)
Packed: 10 pairs per carton
Origin: Made in the USA

	82 Series Bookend Standard Pack	
	Size White (WH)	
7" 182BE WH 7		182BE WH 7
	9"	182BE WH 9
	10.5"	182BE WH 10.5

82DP SCREW ZC

Finish: Zinc (ZC)

Packed: 20 bags per carton (6 screws + 6 anchors per bag)

182DP LCTR/JNR Shelf Locator Joiner

Finish: Clear plastic (CL)

Packed: 20 bags per carton (4 joiners + 8 screws per bag)

182DP LOCK Bracket Lock

Finish: Black rubber (BLK)

Packed: 20 bags per carton (6 locks per bag)













182DP LOCK



Non-stock item – minimum order quantities and additional lead time may apply.

^{*}Standards and brackets meet or exceed ANSI performance standards as established by BHMA testing requirements.

82™/182™ Series Heavy-Duty Standard and Bracket System

182 Series Brackets

Material: 16 gauge steel

Finish: Black (BLK), Titanium (TI), White (WH)

Features: Holds up to 450 lbs. per pair of brackets*; four complete

locking teeth; countersunk screw holes to fasten shelves

Pack Configurations



Standard Builders Pack (BP)		10 brackets per carton with UPC labels	
		10 brackets per carton, no UPC labels	
182 Series Brack	kets Standard Pacl	k	
Size	Black (BLK)	Titanium (TI)	White (WH)
5"	_	_	182 WH 5
7"	182 BLK 7	182 TI 7	182 WH 7
9"	182 BLK 9	182 TI 9	182 WH 9
10.5"	182 BLK 10.5	182 TI 10.5	182 WH 10.5
12.5"	182 BLK 12.5	182 TI 12.5	182 WH 12.5
14.5"	182 BLK 14.5	182 TI 14.5	182 WH 14.5
18.5"	182 BLK 18.5	182 TI 18.5	182 WH 18.5
24"	182 BLK 24	182 TI 24	182 WH 24
182 Series Brackets Builders Pack		(BP)	
5"	182BP BLK 5	_	182BP WH 5
7"	182BP BLK 7	_	182BP WH 7
9"	182BP BLK 9	182BP TI 9	182BP WH 9
10.5"	182BP BLK 10.5	182BP TI 10.5	182BP WH 10.5
12.5"	182BP BLK 12.5	182BP TI 12.5	182BP WH 12.5
14.5"	182BP BLK 14.5	182BP TI 14.5	182BP WH 14.5
18.5"	182BP BLK 18.5	182BP TI 18.5	182BP WH 18.5
24"	182BP BLK 24	182BP TI 24	182BP WH 24



75

83™/183™ Series Heavy-Duty Standard and Bracket System

- · Single slot design
- 1" vertical slot adjustability

- BHMA Grade 2 Compliant*
- Limited lifetime warranty

83 Series Oversized Standards

Dimensions: 3/4" wide x 1/2" deep x selected length

Material: 16 gauge steel Finish: Anochrome (ANO) Origin: Made in the USA

Features: Safety lead-in at top of standard; embossed logo to show

correct orientation; countersunk screw holes; center aligned

slots and screw holes; precision cut lengths

Pack Configurations

Standard		10 standards per carton, no UPC labels
83 Series St	andards Standard Pack	
Size	Anochrome (ANO)	
24"	83 ANO 24	
36"	83 ANO 36	
48"	83 ANO 48	
60"	83 ANO 60	
72"	83 ANO 72	
84"	83 ANO 84	
96"	83 ANO 96	



Accessories

113L ANO Left-Hand Anochrome (ANO) Panel Clip 113R ANO Right-Hand Anochrome (ANO) Panel Clip

Finish: Anochrome (ANO) Origin: Made in the USA

50 per carton; Left and right clips packed separately Packed: Application: Used to attach display and wall panels into vertical position



Packed: 100 per carton



134 ANO Socket-#83 Standard Bottom Socket 135 ANO Socket-#83 Standard Top Socket

Origin: Made in the USA Packed: 100 per carton





159LL ANO Lock Lever Heavy-Duty Support Bracket

Finish: Anochrome (ANO) Origin: Made in the USA Packed: 100 per carton



Provides extra support for shelves with heavy loads; Benefit:

lever lock for extra secure mounting and stability

191 ANO Hang Rod Saddle 192 ANO Hang Rod Saddle

Finish: Anochrome (ANO) Made in the USA Origin: Packed: 10 per carton



191 bolts to 183L & 183R or 185 brackets to hold 1-1/16" O.D. tubing Features:

192 bolts to 183L & 183R or 185 brackets to hold 1-5/16" O.D. tubing

^{*}Standards and brackets meet or exceed ANSI performance standards as established by BHMA testing requirements.

83™/183™ Series Heavy-Duty Standard and Bracket System

183 Series Brackets

Part #: 183R: Right Flange Bracket

183L: Left Flange Bracket 183C: Center Flange Bracket

Material: 16 gauge steel
Finish: Anochrome (ANO)
Origin: Made in the USA

Features: Holds up to 460 lbs. per pair of brackets*; bracket flanges

allow for simple attachment to wooden shelves; brackets may also be used with 85 Series Standards for added support on

long shelves

Pack Configurations

Standard		10 brackets per carton, no UPC labels	
183 Series Brackets Standard Pack - Anochrome (ANO) Finish			
Size	Right	Left	Center
8"	183R ANO 8	183L ANO 8	183C ANO 8
10"	183R ANO 10	183L ANO 10	183C ANO 10
12"	183R ANO 12	183L ANO 12	183C ANO 12
14"	183R ANO 14	183L ANO 14	183C ANO 14
16"	183R ANO 16	183L ANO 16	183C ANO 16
18"	183R ANO 18	183L ANO 18	183C ANO 18
20"	183R ANO 20	183L ANO 20	183C ANO 20



161LL Lock Lever Bracket

Material: 14 gauge steel
Finish: Anochrome (ANO)
Origin: Made in the USA

Features: Three locking teeth; lever lock for extra secure mounting

and stability; for use with 1" adjustable shelving; shelf retaining lip

Pack Configurations

Standard 10 brackets per carton, no UPC labe			
161LL Brackets Size Anochrome 14" 161LL ANO 14 16" 161LL ANO 16			
		18" 161LL ANO 18 20" 161LL ANO 20 24" 161LL ANO 24	



85™/185™ Series Extra-Duty Standard and Bracket System

- · Single slot design
- 1" vertical slot adjustability

- BHMA Grade 2 Compliant*
- Limited lifetime warranty

85 Series Standards

Dimensions: 1-1/4" wide x 1/2" deep x selected length

Material: 16 gauge steel

Finish: Anochrome (ANO), White (WH)

Origin: Made in the USA

Features: Safety lead-in at top of standard; embossed logo to show

correct orientation; countersunk screw holes; center aligned

slots and screw holes; precision cut lengths

Pack Configurations



Standard	10 standards per carton, no UPC labels		
85 Series Sta	85 Series Standards Standard Pack		
Size Anochrome (ANO)		White (WH)	
24"	85 ANO 24	85 WH 24	
36"	85 ANO 36	85 WH 36	
48"	85 ANO 48	85 WH 48	
60"	85 ANO 60	85 WH 60	
72"	85 ANO 72	85 WH 72	
84"	85 ANO 84	85 WH 84	
96"	85 ANO 96	85 WH 96	







Accessories

106 ANO: Shelf Rest

Finish: Anochrome (ANO)
Packed: 100 per carton

Origin: Made in the USA

Application: Used to join two shelves at one bracket

107 ANO: Hang Rod Clamp
Finish: Anochrome (ANO)
Packed: 20 per carton
Origin: Made in the USA

Application: Bolts to 183 and 185 Brackets to hold rods securely

113L ANO: Left-Hand Anochrome (ANO) Panel Clip 113R ANO: Right-Hand Anochrome (ANO) Panel Clip

Finish: Anochrome (ANO)

Packed: 50 per carton; Left and right clips packed separately

Origin: Made in the USA

Application: Used to attach display and wall panels into vertical position

129 RUB: Gray rubber cushion for use

with metal and plastic rests

Packed: 100 per carton

159LL ANO: Lock Lever Heavy-Duty Support Bracket

Finish: Anochrome (ANO)
Packed: 100 per carton
Origin: Made in the USA

Benefit: Provides extra support for shelves with heavy loads;

lock lever for extra secure mounting and stability

191 ANO: Hang Rod Saddle 192 ANO: Hang Rod Saddle Finish: Anochrome (ANO)


Packed: 10 per carton
Origin: Made in the USA

Features: 191 bolts to 183L & 183R or 185 brackets

to hold 1-1/16" O.D. tubing

192 bolts to 183L & 183R or 185 brackets

to hold 1-5/16" O.D. tubing



85™/185™ Series Extra-Duty Standard and Bracket System

185 Series Brackets

Material: 14 and 16 gauge steel
Finish: Anochrome (ANO), White (WH)

Origin: Made in the USA

Features: Holds up to 680 lbs. per pair of brackets*; shelf retaining


lip on brackets; four locking teeth and two lugs for safety

and stability; shelf fastening screw holes

Pack Configurations



Standard 10 brackets per carton, no UPC labels		Clabels		
185 Series Brackets Standard Pack				
Size	Anochrome (ANO)	White (WH)		
8"	185 ANO 8	185 WH 8		
10"	185 ANO 10	185 WH 10		
12"	185 ANO 12	185 WH 12		
14"	185 ANO 14	185 WH 14		
16"	185 ANO 16	185 WH 16		
18"	185 ANO 18	185 WH 18		
20"	185 ANO 20	185 WH 20		
22"	185 ANO 22	185 WH 22		
24"	185 ANO 24	185 WH 24		





87™/186™/187™ Series Super-Duty Standard and Bracket System

· Single slot design

· 2" vertical slot adjustability

· Limited lifetime warranty

• BHMA Grade 2 Compliant*

87 Series Standards

Dimensions: 7/8" wide x 11/16" deep x selected height

Material: 12 gauge steel

Finish: Anochrome (ANO), White (WH)

Origin: Made in the USA

Features: Countersunk screw holes; embossed logo to show

correct orientation; center aligned slots and screw holes;

precision cut lengths

Pack Configurations



Standard	5 per carton, no UPC lab	5 per carton, no UPC labels		
87 Series Standards Standard Pack				
Size	Anochrome (ANO)	White (WH)		
24"	87 ANO 24	87 WH 24		
36"	87 ANO 36	87 WH 36		
48"	87 ANO 48	87 WH 48		
60"	87 ANO 60	87 WH 60		
72"	87 ANO 72	87 WH 72		
84"	87 ANO 84	87 WH 84		
96"	87 ANO 96	87 WH 96		





1987 Series Galvanized Steel Shelving

Material:Galvanized steelFinish:Galvanized Steel (GALV)Origin:Made in the USA

Features: Predrilled mounting holes to fasten to brackets

Pack Configurations

Standard	5 per carton; except 20" x 32": 3 per carton		
1987 Series Shelving Sta	1987 Series Shelving Standard Pack		
Size	Galvanized (GALV)		
8" x 32"	1987 GALV 8X32		
10" x 32"	1987 GALV 10X32		
12" x 32"	1987 GALV 12X32		
16" x 32"	1987 GALV 16X32		
20" x 32"	1987 GALV 20X32		



^{*}Standards and brackets meet or exceed ANSI performance standards as established by BHMA testing requirements.

87™/186™/187™ Series Super-Duty Standard and Bracket System

186LL and 187LL Series Lock Lever Brackets

Material: 12 gauge steel

Finish: Anochrome (ANO), White (WH)

Origin: Made in the USA

Features: Holds up to 1,060 lbs. per pair of brackets*; utilizes an

easy-to-install unique cam lock that secures brackets to the standard; two or three complete locking teeth; predrilled holes for mounting 1987 Series shelves or attaching shelf rests

Pack Configurations



Standard	10 per carton, no UPC la	10 per carton, no UPC labels		
186 Series Brackets Standard Pack				
Size	Anochrome (ANO)	White (WH)		
8"	186LL ANO 8	186LL WH 8		
10"	186LL ANO 10	186LL WH 10		
187 Series Brackets Standard Pack				
12"	187LL ANO 12	187LL WH 12		
14"	187LL ANO 14	187LL WH 14		
16"	187LL ANO 16	187LL WH 16		
18"	187LL ANO 18	187LL WH 18		
20"	187LL ANO 20	187LL WH 20		
22"	187LL ANO 22	187LL WH 22		
24"	187LL ANO 24	187LL WH 24		



Accessories

87-10 WH 100

Sizes: #10 x 2-3/4" screw Finish: White (WH)

Packed: 100 per bag

119 RUB: Gray rubber cushion for use with metal rests

Packed: 100 per carton

Recommended for use when supporting glass shelves

129 RUB: Gray rubber cushion for use with metal and plastic rests

Packed: 100 per carton

Recommended for use when supporting glass shelves

0

210 ANO: Anochrome (ANO) End Rest with screw 210 WH: White (WH) End Rest with screw 211 ANO: Anochrome (ANO) Center Rest with screw 211 WH: White (WH) Center Rest with screw Anochrome (ANO) Front Rest with screw 212 ANO: 212 WH: White (WH) Front Rest with screw 213C ZC: Zinc (ZC) Snap-In Center Rest Finish: Anochrome (ANO), White (WH), Zinc (ZC)

Packed: 100 per carton

shelf to brackets to shelves



87[™]/186[™]/187[™] Super-Duty Stainless Steel Standard and Bracket System

· Single slot design

Standard

Size

24"

36"

48"

72"

• 2" vertical slot adjustability

Limited lifetime warranty

BHMA Grade 2 Compliant*

87 Series Standards


Dimensions: 7/8" wide x 11/16" deep

14 gauge, 304 grade stainless steel Material:

Finish: Stainless Steel (SS) Origin: Made in the USA

Features: Countersunk screw holes; center aligned slots and screw

holes; precision cut lengths





1987 Series Stainless Steel Shelving

Material: 14 gauge, 304 grade stainless steel Finish: Stainless Steel (SS) with brushed finish

Origin: Made in the USA

Features: Predrilled mounting holes to fasten to brackets;

87 SS 60

87 SS 72

shelves are shipped with protective vinyl wrap

Pack Configurations

Standard	5 per carton; except 20" x 32": 3 per carton	
1987 Series Stainless Steel Shelving Standard Pack		
Size	Stainless Steel (SS)	
8" x 32"	1987 SS 8X32	
10" x 32"	1987 SS 10X32	
12" x 32"	1987 SS 12X32	
16" x 32"	1987 SS 16X32	
20" x 32"	1987 SS 20X32	



^{*}Standards and brackets meet or exceed ANSI performance standards as established by BHMA testing requirements.

87[™]/186[™]/187[™] Super-Duty Stainless Steel Standard and Bracket System

186LL and 187LL Series Stainless Steel Lock Lever Brackets

Material: 14 gauge 304 grade stainless steel Finish: Brushed Stainless Steel (SS)

Origin: Made in the USA

Features: Holds up to 560 lbs. per pair of brackets*; lever lock for

easy installation, stability and safety; predrilled holes for mounting 1987 Series shelves or attaching shelf rests;

two or three complete locking teeth

Pack Configurations



Standard	10 per carton, no UPC labels		
186 Series Brackets Standar	rd Pack		
Size	Stainless Steel (SS)		
8"	186LL SS 8		
10"	186LL SS 10		
187 Series Brackets Standar	187 Series Brackets Standard Pack		
12"	187LL SS 12		
14"	187LL SS 14		
16"	187LL SS 16		
18"	187LL SS 18		
20"	187LL SS 20		
24"	187LL SS 24		

NOTE: Stainless Steel brackets do not work with 87 steel standards. Must be used with Stainless Steel Standards







Non-stock item — minimum order quantities and additional lead time may apply. *Standards and brackets meet or exceed ANSI performance standards as established by BHMA testing requirements.

5mm Shelf Supports for Built-In Shelving

326 ANO and 326 BR Grommets

Grommet Diameter: For 7/32" (5.556mm) holes
Pin Diameter: Designed for 5mm pin diameters
Finish: Anochrome (ANO), Brass-look (BR)
Packed: 1000 per bag, 4 bags per carton



330 ANO Shelf Supports

Pin Diameter: Designed for 5mm holes Finish: Anochrome (ANO)

Packed: 2000 per bag, 4 bags per carton



332 ANO and 332 BR Shelf Supports

Pin Diameter: Designed for 5mm holes

Pin Length: 5/16" (8mm)

Shelf Rest: 5/16" (8mm) wide x 7/16" (11mm) long Finish: Anochrome (ANO), Brass-look (BR) Packed: 1000 per bag, 4 bags per carton



338 Series Plastic Shelf Support Pins

Pin Diameter: Designed for 5mm holes

Pin Length: 5/16" (8mm)

Shelf Rest: 7/16" (11mm) wide x 13/32" (10mm) long

100 pieces per carton

Finish: Almond (ALM), Brown (BRN), Clear Plastic (CL), White (WH)



Pack Configurations

Standard

Poly (P)	12 supports per bag; 10 bags per carton	
338 Series Shelf Support		
Pack Configuration	Clear Plastic (CL)	White (WH)
Standard Pack	338 CL	338 WH
Poly (P) Pack	338P CL	-

339 WH Plastic Locking Shelf Support for 3/4" Shelves

Pin Diameter: Designed for 5mm holes

Pin Length: 1/4"
Finish: White (WH)

Packed: 100 per bag, 25 bags per carton



340 WH Plastic Locking Shelf Supports for 1" Shelves

Pin Diameter: Designed for 5mm holes

Pin Length: 1/4"
Finish: White (WH)

Packed: 100 per bag, 5 bags per carton



345 Series Metal Shelf Pins*

Pin Diameter: Designed for 5mm holes

Pin Length: 5/16" (8mm)

Shelf Rest: 1/2" (13mm) wide x 11/16" (17mm) long
Finish: Nickel Plated (NP), Brass-Look (BR), Walnut (WAL)



Pack Configurations

Standard	100 pieces per carton		
Poly (P)	12 supports per bag; 10 bags per carton		
345 Series Shelf Support			
Pack Configuration	Nickel Plated (NP)	Brass-Look (BR)	Walnut (WAL)
Standard Pack	345 NP	345 BR	345 WAL
Poly (P) Pack	345P NP	-	-

348 ALM, 348 BRN and 348 WH Vinyl Coated Shelf Supports

Pin Diameter: Designed for 5mm holes;

use 13/64" diameter drill bit

Pin Length: 5/16" (8mm)

Shelf Rest: 1/2" (13mm) wide x 11/16" (17mm) long Finish: Almond (ALM), Brown (BRN), White (WH)

Packed: 1000 pieces per carton





1/4" and 7/32" Shelf Supports and Grommets

325 ANO and 325 BR Grommets

Grommet Diameter: For 9/32" (7.143mm) holes

Pin Diameter: Designed for 1/4" pin diameters

Finish: Anochrome (ANO), Brass-look (BR)

Packed: 1000 per bag, 4 bags per carton



331 ANO and 331 BR Shelf Supports

Pin Diameter: Designed for 1/4" holes

Pin Length: 3/8" (9mm)

Shelf Rests:3/8" (9mm) wide x 1/2" (13mm) longFinish:Anochrome (ANO), Brass-look (BR)Packed:1000 per bag, 4 bags per carton



335 Series Plastic Shelf Support Pins

Pin Diameter: Designed for 1/4" holes

Pin Length: 7/16" (11mm)

Shelf Rest: 1/2" (13mm) wide x 17/32" (14mm) long
Finish: Clear Plastic (CL), Plastic (PLAS), White (WH)



Pack Configurations

Standard	10 pieces per carton		
Poly (P)	12 supports per bag; 10 bags per carton		
335 Series Shelf Support			
Pack Configuration Clear Plastic (CL) Plastic (PLAS) White (WH)		White (WH)	
Standard Pack	335 CL	335 PLAS	335 WH
Poly (P) Pack	335P CL	335P PLAS	335P WH

346 Series Metal Shelf Pins*

Pin Diameter: Designed for 1/4" holes

Pin Length: 3/8" (9mm)

Shelf Rest: 1/2" (13mm) wide x 11/16" (17mm) long
Finish: Anochrome (ANO), Brass-Look (BR), Walnut (WAL)



Standard	100 pieces per carton		
Poly (P)	12 supports per bag; 10 bags per carton		
346 Series Shelf Sup	346 Series Shelf Support		
Pack Configuration	Anochrome (ANO)	Brass-Look (BR)	Walnut (WAL)
Standard Pack	346 ANO	346 BR	346 WAL
Poly (P) Pack	346P ANO	346P BR	346P WAL

333 ZC Shelf Supports

Pin Diameter: Designed for 7/32" holes;

use 15/64" diameter drill

Pin Length: 1/2" (13mm)

Shelf Rest: 9/16" (14mm) wide x 7/16" (11mm) long

Finish: Zinc (ZC)
Packed: 1000 per carton



Utility Shelving Brackets

206 Series Extra-Duty Folding L-Bracket

Finish: Zinc (ZC), White (WH)

Features: Holds up to 750 lbs. per pair*; 4 adjustable positions: 90°,

> 80°, 70°, and 0° (closed position)**; all steel construction with spring-loaded release lever; predrilled screw holes in top of bracket for easy fastening to wood shelves;

BHMA Grade 2 Compliant*

Pack Configurations

Standard	10 per display carton with UPC labels attached	
206 Series Folding L-Brackets		
Size	Zinc (ZC)	White (WH)
12"	206 ZC 12	206 WH 12
16"	206 ZC 16	206 WH 16

^{**}Angle has a tolerance of +1°. May need to shim for level installations.







208 Series Ultimate L-Bracket


Finish: Black (BLK), Titanium (TI), White (WH)

Features: Holds up to 1,200 lbs. per pair*; super-duty bracket;

> corrosion resistant Epoxy-Coated finish; 5mm steel bar and 3/4" steel strut; BHMA Grade 2 Compliant*

Pack Configurations

3			
Standard	10 per display carton with UPC labels		
208 Series Bracket			
Size	Black (BLK)	Titanium (TI)	White (WH)
300mm	208 BLK 300	208 TI 300	208 WH 300
400mm	208 BLK 400	208 TI 400	208 WH 400
500mm	208 BLK 500	208 TI 500	208 WH 500
550mm	208 BLk 550	208 TI 550	208 WH 550



221 Series Utility L-Bracket

Finish: Gray (GRY), White (WH)

Features: Holds up to 120 lbs. per pair*; regular-duty bracket;

durable powder coat finish

Pack Configurations

Standard	20 per carton with UPC	20 per carton with UPC labels	
221 Series Bracket	221 Series Bracket		
Size	Gray (GRY)	White (WH)	
5" x 6"	221 GRY 5X6	221 WH 5X6	
6" x 8"	221 GRY 6X8	221 WH 6X8	
8" x 10"	221 GRY 8X10	221 WH 8X10	
10" x 12"	221 GRY 10X12	221 WH 10X12	
12" x 14"	221 GRY 12X14	221 WH 12X14	





^{*}Standards and brackets meet or exceed ANSI performance standards as established by BHMA testing requirements.

Decorative Shelf Brackets

0117 & 0118 Designer Shelf Bracket

Finish: White (WH)

Features: Metal brackets with color covers

215 Series Slim-Line™ Shelf Bracket

Finish: Black (BLK), White (WH)

Features: BHMA Grade 2 Compliant*; accented with decorative plastic

trim that hides mounting hardware

Pack Configurations

Standard	5 per display carton with UPC labels	
0117 Designe	r Shelf Bracket	
Size	White (WT)	
24"	0117-24WT	
36"	0117-36WT	
48"	0117-48WT	
0118 Designer Shelf Bracket		
24"	0118-24WT	



Pack Configurations

Special Pack	10 per carton (all sizes)		
215 Series Bracket S	pecial Pack (SP)		
8"	215SP BLK 8	215SP WH 8	
10"	215SP BLK 10	215SP WH 10	
12"	215SP BLK 12	215SP WH 12	



0035 & 0036 Designer Shelf Bracket

Finish: Black (BLK), White (WH)

Features: BHMA Grade 2 Compliant*; heavy-duty steel; accented with

decorative plastic trim that hides mounting hardware. Metal

brackets with color covers

Pack Configurations

Standard	10 per display carton v	10 per display carton with UPC labels	
0035 & 0036 Designer Shelf Bracket			
Size	Black (BLK)	Black (BLK) White (WT)	
6"	BK-0035-BK	BK-0035-WT	
8"	BK-0036-BK	BK-0036-BK BK-0036-WT	



217 Series Silhouette™ Shelf Bracket

Finish: Black (BLK), White (WH)

Features: BHMA Grade 2 Compliant*; heavy-duty steel; center rib

for superior strength; countersunk screw holes

Pack Configurations

Special Pack	10 per carton (all sizes)		
217 Series Bracket S	217 Series Bracket Special Pack (SP)		
8"	217SP BLK 8	217SP WH 8	
10"	217SP BLK 10	217SP WH 10	
12"	217SP BLK 12	217SP WH 12	



^{*}Standards and brackets meet or exceed ANSI performance standards as established by BHMA testing requirements.

200 Series Designer Decorative Shelf Brackets

Concord 200C Series Decorative Brackets


Finish: Antique Bronze (AB), Black (BLK), Satin Nickel (SN), White (WH)
Features: Holds up to 50 lbs. per pair*; BHMA Grade 1 Compliant*;

distinct traditional styles fit any decor; screw holes for easy mounting; 6" size for 6"–8" deep shelves; 8" size

for 8"-12" shelves

Pack Configurations

Standard	10 carded pieces per carton			
200C Series Concord Decorative Shelf Bracket				
Size	Antique Bronze (AB)	Black (BLK)	Satin Nickel (SN)	White (WH)
6"	200C AB 6	200C BLK 6	200C SN 6	200C WH 6
8"	200C AB 8	200C BLK 8	200C SN 8	200C WH 8



Manchester 200M Series Decorative Brackets

Finish: Antique Bronze (AB), Black (BLK), Satin Nickel (SN), White (WH)


Features: Holds up to 50 lbs. per pair*: BHMA Grade 1 Compliant*:

Holds up to 50 lbs. per pair*; BHMA Grade 1 Compliant*; distinct traditional styles fit any decor; screw holes for easy mounting; 6" size for 6"-8" deep shelves; 8" size

for 8"-12" shelves

Pack Configurations

Standard	Standard 10 carded pieces per carton				
200M Sei	200M Series Manchester Decorative Shelf Bracket				
Size	Antique Bronze (AB)	Black (BLK)	Satin Nickel (SN)	White (WH)	
6"	200M AB 6	200M BLK 6	200M SN 6	200M WH 6	
8"	200M AB 8	200M BLK 8	200M SN 8	200M WH 8	



Oak Park 2000P Series Decorative Brackets


Finish: Antique Bronze (AB), Black (BLK), Satin Nickel (SN)

Features: Holds up to 100 lbs. per pair*; BHMA Grade 1 Compliant*;

distinct contemporary styles fit any decor; screw holes for easy mounting; 8" size for 8"–12" shelves; cast zinc insets

Pack Configurations

Standard	ard 10 carded pieces per carton		
2000P Series	2000P Series Oak Park Decorative Shelf Bracket		
Size	Antique Bronze (AB)	Black (BLK)	Satin Nickel (SN)
8"	2000P AB 8	2000P BLK 8	2000P SN 8



Stockton 200S Series Decorative Brackets


Finish: Black (BLK), Satin Nickel (SN)

Features: Holds up to 100 lbs. per pair*; BHMA Grade 1 Compliant*;

distinct contemporary styles fit any decor; screw holes for easy mounting; 8" size for 8"-12" shelves; cast zinc insets

Pack Configurations

	_		
Standard	10 carded pieces per carton		
200S Series Stockton Decorative Shelf Bracket			
Size	Black (BLK)	Satin Nickel (SN)	
8"	200S BLK 8	200S SN 8	



Finish:



87

200 Series Designer Decorative Shelf Brackets

Baton Rouge 200BR Series Decorative Brackets

Finish: Antique Bronze (AB), Black (BLK), Satin Nickel (SN)

Features: Holds up to 200 lbs. per pair*; BHMA Grade 2 Compliant*;

> distinct elegant styles fit any decor; screw holes for easy mounting; 8" size for 8"-12" shelves; cast zinc insets

Pack Configurations

Standard 10 carded pieces per carton			
200BR Series Baton Rouge Decorative Shelf Bracket			
Size	Antique Bronze (AB)	Black (BLK)	Satin Nickel (SN)
8"	200BR AB 8	200BR BLK 8	200BR SN 8



Charleston 200CH Series Decorative Brackets


Finish: Black (BLK), Satin Nickel (SN)

Features: Holds up to 200 lbs. per pair*; BHMA Grade 2 Compliant*;

> distinct elegant styles fit any decor; screw holes for easy mounting; 8" size for 8"-12" shelves; cast zinc insets

Pack Configurations

	_	
Standard 10 carded pieces per carton		
200CH Series Charleston Decorative Shelf Bracket		
Size	Black (BLK)	Satin Nickel (SN)
8"	200CH BLK 8	200CH SN 8



Finish:



Antique Bronze (AB)



(BLK)

Satin Nickel

(SN)

201 Series Premium Decorative Shelf Brackets

Richland 201RC Series Decorative Brackets

Finish: Black (BK), Bronze (BRZ)

Features: Holds up to 500 lbs. per pair*; BHMA Grade 1 Compliant*;

distinct styles fit any decor; screw holes for easy mounting;

8" size for 8"-12" deep shelves; 12" size for

12"-16" deep shelves

Pack Configurations

Standard	8 brackets with screws		
201RC Series Richland Decorative Shelf Bracket			
Size	Black (BK) Bronze (BRZ)		
8"	RP-201RC-8BK	RP-201RC-8BRZ	
12"	RP-201RC-12BK RP-201RC-12BRZ		



Manhattan 201MN Series Decorative Brackets

Finish: Black (BK), Bronze (BRZ), Satin Nickel (SN)

Features: Holds up to 500 lbs. per pair*; BHMA Grade 1 Compliant*;

distinct styles fit any decor; screw holes for easy mounting;

8" size for 8"-12" deep shelves; 12" size for

12"-16" deep shelves

Pack Configurations

Standard	8 brackets with screws		
201MN Se	201MN Series Manhattan Decorative Shelf Bracket		
Size	Black (BK)	Bronze (BRZ)	Satin Nickel (SN)
8"	RP-201MN-8BK	RP-201MN-8BRZ	RP-201MN-8BSN
12"	RP-201MN-12BK	RP-201MN-12BRZ	RP-201MN-12SN



Heartland 201HR Series Decorative Brackets

Finish: Anthracite (ANT), Black (BK), Bronze (BRZ)

Features: Holds up to 50 lbs. per pair*; BHMA Grade 1 Compliant*;

distinct styles fit any decor; screw holes for easy mounting; $6" \times 8"$ size for 6"-12" deep shelves; $8" \times 10"$ size for

8"-14" deep shelves

Pack Configurations

Standard	8 brackets with screws		
201HR Series Heartland Decorative Shelf Bracket			
Size	Black (BK)	Bronze (BRZ)	Anthracite (ANT)
6" x 8"	RP-201HR-68BK	RP-201HR-68BRZ	RP-201HR-68BANT
8" x 10"	RP-201HR-810BK	RP-201HR-810BRZ	RP-201HR-810ANT



Silverston 201SL Series Decorative Brackets

Finish: Black (BK)

Features: Holds up to 75 lbs. per pair*; BHMA Grade 1 Compliant*;

distinct styles fit any decor; screw holes for easy mounting;

10" size for 9.75" deep shelves; 12" size for


11.75" deep shelves

Pack Configurations

	J	
Standard	8 brackets with screws	
201SL Series Manhattan Decorative Shelf Bracket		
Size	Black (BK)	
10"	RP-201SL-10BK	
12"	RP-201SL-12BK	



Finish:



201 Series Premium Decorative Shelf Brackets

Lewiston 201LW Series Decorative Brackets

Finish: Black (BK), Satin Gold (SG), Satin Nickel (SN)

Features: Holds up to 100 lbs. per pair*; BHMA Grade 1 Compliant*;

distinct styles fit any decor; screw holes for easy mounting;

8" size for 8"-12" deep shelves; 12" size for

12"-16" deep shelves

Pack Configurations

Standard	8 brackets with screws		
201LW Series Lewiston Decorative Shelf Bracket			
Size	Black (BK)	Satin Gold (SG)	Satin Nickel (SN)
8"	RP-201LW-8BK	RP-201LW-8SG	RP-201LW-8SN
12"	RP-201LW-12BK	RP-201LW-12SG	RP-201LW-12SN



Pittsburgh 201MN Series Decorative Brackets

Finish: Black (BK), Bronze (BRZ), Satin Nickel (SN)

Features: Holds up to 200 lbs. per pair*; BHMA Grade 1 Compliant*;

distinct styles fit any decor; screw holes for easy mounting; 8" size for 0.625" thick x 7.95" deep shelves; 12" size for 0.625" thick by 11.95" deep shelves; sold in pairs

Pack Configurations

Standard	10 pairs of brackets with screws		
201MN Series Pittsburgh Decorative Shelf Bracket			
Size	Black (BK)	Bronze (BRZ)	Satin Nickel (SN)
8"	RP-201PT-8BK	RP-201PT-8BRZ	RP-201PT-8SN
12"	RP-201PT-12BK	RP-201PT-12BRZ	RP-201PT-12SN



Finish:









Satin Gold (SG)

Shelf Board

1980 Series All-Purpose Shelf Board

Finish: Diamond Ash (DA), Espresso (ESP), Maple (MPL), Oak (OK),

Walnut (W), White (WH)

Origin: Made in China

Features: Holds up to 200 lbs. when properly installed; 5/8" thick with

square corners; scratch and stain resistant for long life; easy

to clean surface



Pack Configurations

Standard 5 per carton, with the exception: 12" x 72" packed 3 per carton						
1980 Series Shelving Standard Pack						
Size	Diamond Ash (DA)	Espresso (ESP)	Maple (MPL)	0ak (0K)	Walnut (W)	White (WH)
8" x 24"	1980 DA 8X24	1980 ESP 8X24	1980 MPL 8X24	1980 OK 8X24	1980 W 8X24	1980 WH 8X24
8" x 36"	1980 DA 8X36	1980 ESP 8X36	1980 MPL 8X36	1980 OK 8X36	1980 W 8X36	1980 WH 8X36
8" x 48"	1980 DA 8X48	1980 ESP 8X48	1980 MPL 8X48	1980 OK 8X48	1980 W 8X48	1980 WH 8X48
10" x 24"	1980 DA 10X24	1980 ESP 10X24	1980 MPL 10X24	1980 OK 10X24	1980 W 10X24	1980 WH 10X24
10" x 36"	1980 DA 10X36	1980 ESP 10X36	1980 MPL 10X36	1980 OK 10X36	1980 W 10X36	1980 WH 10X36
10" x 48"	1980 DA 10X48	1980 ESP 10X48	1980 MPL 10X48	1980 OK 10X48	1980 W 10X48	1980 WH 10X48
12" x 24"	1980 DA 12X24	1980 ESP 12X24	1980 MPL 12X24	1980 OK 12X24	1980 W 12X24	1980 WH 12X24
12" x 36"	1980 DA 12X36	1980 ESP 12X36	1980 MPL 12X36	1980 OK 12X36	1980 W 12X36	1980 WH 12X36
12" x 48"	1980 DA 12X48	1980 ESP 12X48	1980 MPL 12X48	1980 OK 12X48	1980 W 12X48	1980 WH 12X48
12" x 72"	_	_	_	_	_	1980 WH 12X72



Closet and Specialty Hardware

Door & Mirror Hardware	93
Magnetic and Bullet Catches	93
Sliding Door Pulls	
Mirror Clips/Glass Clips, Fittings and Latches	
Drawer Accessories	95
Index Followers	95
Label Holders	95
Locks	95
Pulls	
Cabinet Hardware	96
Fasteners	96
Hinges	96
Sliding Door Hardware	97
Glass Door Locks	97
Door Rollers	97
Sheaves	98
Plastic Tracks and Guides	99
Plastic Door Track Packaged Assemblies	99
Steel Tracks and Guides	100
Roll-Ezy Ball-Bearing Track Systems	101
Roll-Ezy Aluminum Track Systems	

Closet Rods
60 Series Heavy-Duty Round Closet Rods
50 Series Heavy-Duty Round Closet Rods
70 Series Extra-Duty Round Closet Rods
ound Closet Rod Mounting Flanges and Accessories
80 Series Extra-Duty Oval Closet Rods
djustable Closet Rods
Closet Brackets
loset Shelf Brackets
loset Rods and Shelf Brackets
Closet Storage Aids110
tility Hooks
oat and Hat Hook
ang Rod
lothing Carrier
owel Bar

Magnetic and Bullet Catches Sliding Door Pulls

Magnetic Catches

918 ALUM Heavy-Duty Aluminum Magnetic Catch

2-1/16" width x 1" depth x 3/4" tall

Aluminum (ALUM) Finish:

Packed: 10 per carton, packed in a clear

envelope with screws

Pull Strength: 7 lbs.



Bullet Catches

903 BR DIP Adjustable Brass Catch

3/8" diameter; 5/8" long; Size:

9/16" x 1-1/16" diameter strike

Finish: Brass-look (BR) Packed: 100 per carton



905 BR DIP Adjustable Brass-look Catch

1/2" diameter; 1-1/32" long; Size:

5/8" x 1-1/4" diameter strike

Finish: Brass-look (BR)

Packed: 50 per carton with screws





Knob Pulls

813 ANO Oval Flush Finger Pull*

Over-flange 3/16" x 2-7/8"

Bore 51/64" x 2-1/2" x 25/64" deep

Finish: Anochrome (ANO) Origin: Made in the USA Packed: 100 per carton



1088 ANOD Knob Pull

Finish: Zinc plated steel (ANOD) Packed: Sets of: 2 knobs, screws,

and rubber bumpers per envelope

50 sets per carton

Features: Mounts to 1095 shoe (1092 assembly)

Finger Pulls

801X NP and 803X NP Flush Finger Pull

801X: 31/32" outside diameter.

Bore 25/36" hole diameter, 1/4" depth 803X: 31/32" outside diameter, Bore 25/36" hole diameter, 3/8" depth

Finish: Nickel Plate (NP) Origin: Made in the USA Packed: 100 per carton



836 ANO Threaded Finger Pull

Size: 1-1/16" outside diameter, cut a 13/16" diameter hole

for installation

Finish: Anochrome (ANO) Origin: Made in the USA Packed: 50 per carton

Features: Two-piece screw-together pull for glass 3/16'

to 5/16" thick; with beveled edges



Mirror Clips/Glass Clips, Fittings and Latches

Mirror Clips/Glass Clips

6092 PLAS Plastic Mirror Clips

Size: For 1/4" thick glass/mirror Finish: Clear Plastic (PLAS) Packed: 100 per carton with screws



6094 PLAS Plastic Mirror Clip

Size: For 1/8" thick glass/mirror Finish: Clear Plastic (PLAS) Packed: 100 per carton with screws



266 CHR Cast Mirror Clip

Size: 1-1/16" long x 3/4" wide, for 1/4" thick glass/mirror

Finish: Chrome (CHR)

Packed: 12 per carton with screws



268 CHR Heavy-Duty Cast Mirror Clip

Size: 1-1/4" long x 11/16" wide, for 1/4" thick glass/mirror

Finish: Chrome (CHR)

Packed: 12 per carton with screws



277 ANO Bottom-Mount Steel Mirror Clip

Size: 1-1/2" wide x 1" high, for 1/4" thick glass/mirror

Anochrome (ANO) Finish: Origin: Made in the USA Packed: 10 per carton

Features: Screw attached bottom flange for snug mounting



278 ANO Top-Mount Steel Mirror Clip

1-1/2" wide x 1-1/8" high, for 1/4" thick glass/mirror Size:

Finish: Anochrome (ANO) Origin: Made in the USA Packed: 10 per carton



Features: Screw attached upper flange for snug mounting



288 ANO Steel Mirror Clip

Size: 1/2" wide, for 1/4" thick glass/mirror

Finish: Anochrome (ANO) Made in the USA Origin: Packed: 100 per carton



309 ANO Steel Mirror Clip

Size: 9/16" wide x 1-1/4" long, for 5/16" thick glass/mirror

Finish: Anochrome (ANO) Origin: Made in the USA Packed: 100 per carton

Features: Countersunk for #4 screws



318 ANO Steel Mirror Clip

Size: 9/16" wide x 1-1/4" long, for 5/16" thick glass/mirror

Finish: Anochrome (ANO) Origin: Made in the USA Packed: 100 per carton

Features: Countersunk elongated slot for #5 flat head screws;

elongated mounting hole for adjustable installation



Fittings

306 ANO Glass Fitting

Size: 9/16" wide x 1-1/4" long Finish: Anochrome (ANO) Packed: 100 per carton Origin: Made in the USA

Features: Countersunk for #4 screws



Latches

989 Series Secret Gate Latch

Size: 2" x 2-3/8" Finish: Aluminum Packed: 12 per carton

Features: Interchangeable left or right hand mounting



Non-stock item – minimum order quantities and additional lead time may apply

Index Followers, Label Holders, Locks and Pulls

Index Followers and Track



475F ZC Card Sized Index Follower

Size: Mounted plate is 2-11/16" from track and 4-3/4" wide

Finish: Anochrome (ANO)
Origin: Made in the USA
Packed: 10 per carton



476F ZC Letter Sized Index Follower

Size: Mounted plate is 7-5/8" from track and 10-3/4" wide

Finish: Anochrome (ANO)
Origin: Made in the USA
Packed: 10 per carton



476T ZC 26 Index Follower Track

Size: 26" long; may be recessed in a 2-1/4" x 1/4" slot

Finish: Anochrome (ANO)
Origin: Made in the USA

Packed: 10 per carton with screws



Label Holders

701 ANO Label Holder

Size: 2-5/8" x 1-7/16" for card dimension of 2" x 1"

Finish: Anochrome (ANO)
Origin: Made in the USA
Packed: 100 per carton



704 ANO Label Holder

Size: 3-1/2" x 1-3/4" for card dimension

of 2-15/16" x 1-1/2"

Finish: Anochrome (ANO)
Origin: Made in the USA
Packed: 100 per carton



Drawer Locks

986 Series Drawer Lock

Size: Mounting flange: 1-1/2" x 2" wide

with screw holes on 1-7/16" centers;

barrel OD: 7/8"; bolt travel: 3/8"

Finish: Polished Nickel (NP)
Origin: Made in the USA
Packed: 12 per carton

Features: Available keyed alike; mounts to material

up to 7/8" thick

986 Series Drawer Locks				
Product Finish Keyed				
986KA 70 NP	Nickel (NP)	Alike		

Drawer Pulls

819X ANO

819X BR

819X Flush Drawer Pull

Size: 1-3/4" x 3-1/4" x 9/16" deep with beveled edges

Finish: Anochrome (ANO), Dull Brass (BR)
Packed: 12 per carton with screws

Anochrome (ANO)

Dull Brass (BR)

819X Flush Drawer Pull
Product Finish



Fasteners and Hinges

Surface Fasteners

320 STL Table Top Fastener, 1" width 323 STL Table Top Fastener, 5/8" width 324 STL Table Top Fastener, 3/4" width

Finish: Steel (STL)
Origin: Made in the USA
Packed: 100 per carton



341 ZC and 342 ZC Corner Brace

Size: 341: 1" x 1" installed

342: 2" x 2" installed

Finish: Zinc (ZC)
Origin: Made in the USA
Packed: 100 per carton



1547 STL Desk Top Fastener

Finish: Steel (STL)
Origin: Made in the USA
Packed: 100 per carton



1548 ZC Desk Top Fastener

Finish: Zinc (ZC)
Origin: Made in the USA
Packed: 500 per carton



521 ZC Hanger Plate (1/16" steel)

Size: 13/16" x 2"
Finish: Zinc (ZC)
Origin: Made in the USA
Packed: 100 per carton




Features: Use with 3/4" #10 flathead wood screws

Bolt Style Fastener

510 ZC Joint Fastener

Size: 4" bolt with plate 5/16" x 5/8" x 1-1/2"

Finish: Zinc (ZC)
Packed: 100 per carton





Size: 4" bolt with flat bar plate

7/16" x 3/16" x 1-1/4"

Finish: Zinc (ZC)
Packed: 100 per carton



517 ZC Joint Fastener

Size: 3-1/2" bolt with flat bar plate 7/16" x 3/16" x 1-1/4"

Finish: Zinc (ZC)
Packed: 100 per carton



Tite-Joint® Fastener

516 ZC designed for 3/4" wood

Size: Center-to-center 2" to 3-1/2"

Finish: Zinc (ZC)
Origin: Made in the USA

Features: Applies an even, controlled pressure between joint members

to eliminate twisting and buckling

25 per carton			
100 per carton			
Zinc (ZC)	516 Joint Fast	ener Accessory Parts	
Builders (BP)	Product	Description	Packed
516/100 ZC	516-1	Draw Bolt	1 per carton
	516-60	Locking Sleeve	1 per carton
	516-62	Tightening Rod	1 per carton
	516-63	Drill Guide	1 per carton
arrie ar	516-64	Drill	1 per carton
122	516-80 100	Tightening Assembly	1 per carton
	100 per carton Zinc (ZC) Builders (BP)	100 per carton Zinc (ZC) 516 Joint Fast Builders (BP) 516/100 ZC 516-60 516-62 516-63 516-64	100 per carton Zinc (ZC) 516 Joint Fastener Accessory Parts Builders (BP) Product Description 516/100 ZC 516-1 Draw Bolt 516-60 Locking Sleeve 516-62 Tightening Rod 516-63 Drill Guide 516-64 Drill









Hinges

472 ANO Steel Support Hinge

Size: 6" or 10"
Finish: Anochrome (ANO)
Origin: Made in the USA



Pack Configurations						
Standard	12 pair (left and right handed) per carton with screws					
Optional	Left or right hand packaged separately in cartons of 24					
472 Support Hinges Standard Pack 472 Support Hinges Optional Pack						
Standard	Finish	Product	Finish	Handed		
472 ANO 6	Anochrome (ANO)	472L ANO 10	Anochrome (ANO)	Left		
472 ANO 10	Anochrome (ANO)	, , , , , , , , , , , , , , , , , , , ,				

Locks and Door Rollers

Sliding Glass Door Locks

962KA 440 CHR Adjustable Ratchet Lock for 3/4" glass 963KA 440 CHR Adjustable Ratchet Lock for 1/4" glass*

Size: Adjustable 3/4" to 3-3/8"

Finish: Chrome (CHR)
Packed: 12 per carton

Features: 962 fits any door to 3/4" with thumbscrew adjustment

963 fits 1/4" sliding glass doors, keyed alike

965 Ratchet Locks

Size: Adjustable from 1" to 3-3/8"
Finish: Polished Nickel (NP)
Packed: 12 per carton

Features: Adjustable lock for 1/4" sliding glass doors

965 Ratchet Locks				
Product	Finish	Keyed		
965KA 50 NP	Polished Nickel	Alike		

984KA 90 NP Plunger Lock

Size: Mounting flange: 7/8" x 2" with screw holes on

1-1/2" centers; Barrel: 7/8" outside diameter;

Plunger travel: 15/32";

Plunger receptacle: 1/2" (outside diameter) x 7/16"

Finish: Polished Nickel (NP)
Packed: 12 per carton
Features: Keyed alike only

Door Rollers

420 STL Door Roller

Size: Frame: 7/16" x 1-7/8";

Nylon roller: 9/16" diameter; 5/16" wide 🗸

Finish: Steel (STL)
Packed: 100 per carton

422 STL Door Roller

Size: Frame: 5/8" x 1-13/16";

Nylon roller: 9/16" diameter; 1/2" wide

Finish: Steel (STL)
Packed: 100 per carton

423 STL Door Roller

Size: Frame: 5/8" x 1-13/16";

Steel roller: 5/8" diameter; 1/2" wide

Finish: Steel (STL)
Packed: 100 per carton

424 STL Door Roller

Size: Frame: 1" x 2";

Steel roller: 5/8" diameter; 7/8" wide

Finish: Steel (STL)
Packed: 50 per carton



Sheaves

427 STL Steel Sheave

Frame: 2-15/16" x 1/2"; Wheel: 1-3/16" diameter Size:

Finish: Steel (STL) Packed: 50 per carton

Ball-bearing round groove sheave; Features:

for use with KV tracks 455, 467, and 469

429 STL Steel Sheave

Frame: 2-1/4" x 3/8"; Wheel: 1" diameter Size:

Finish: Steel (STL) Packed: 100 per carton Features: Round groove sheave;

for use with KV tracks 455, 467, and 469



Frame: 2-3/4" x 1/2"; Wheel: 1-3/8" diameter Size:

Origin: Made in the USA Finish: Steel (STL) Packed: 50 per carton

Ball-bearing round groove sheave; Features:

for use with KV tracks 455, 467, and 469

430 N STL Neoprene Treaded Steel Sheave

Size: Frame: 2-3/4" x 1/2"; Wheel: 1-3/8" diameter

Finish: Steel (STL) Packed: 50 per carton

Features: Flat neoprene tire, ball-bearing sheave;

used without track

592 STL Convex Nylon Sheave

Frame: 9/32" x 2-1/4"; Wheel: 1-3/16" diameter Size:

Finish: Steel (STL) Packed: 100 per carton

Features: Convex nylon wheel for thin doors;

for use with inverted KV track 455

594 NYLON Concave Nylon Sheave

Size: Frame: 2-15/16" x 1/2"; Wheel: 1-3/16" diameter

Finish: Steel (STL) Packed: 50 per carton

For doors to 1-1/8" thick; nylon round groove Features:

wheel; for use with all KV tracks

607 ZC Side Mount Steel Sheave

Size: Frame: 2-5/16" x 1-5/16"; Wheel: 1-3/8" diameter

Finish: Steel (STL) Packed: 50 per carton

Features: Heavy-duty ball-bearing sheave with side fastening

plate; for use with KV tracks 455, 467, and 469

620 STL Steel Sheave

Frame: 7/16" x 1-7/8"; Wheel: 11/16" x 9/32' Size:

Finish: Steel (STL) Packed: 100 per carton

Features: Axle bearing grooved steel roller;

for use with KV tracks 455, 467, and 469

400A STL Concealed Steel Sheave

Size: Case: 1-1/4" x 5/16"; Flange: 1-3/4" x 9/16"

Finish: Steel (STL) Packed: 100 per carton

Features: Ball-bearing sheave drive type;

for use with KV tracks 455, 467, and 469

402 STL Concealed Steel Sheave

Size: Frame: 1-1/4" x 5/16"; Flange: 2-1/4" x 5/16"

Finish: Steel (STL) Packed: 100 per carton Features: Ball-bearing sheave;

for use with KV tracks 455, 467, and 469

580 STL Concealed Steel Sheave

Size: Case: 1-1/4" x 5/16"; Flange: 1-3/4" x 9/16"

Finish: Steel (STL) Packed: 100 per carton

Features: Nylon round groove sheave for light doors;

for use with KV tracks 455, 467, and 469

582 STL Concealed Steel Sheave

Size: Case: 1-1/4" x 5/16"; Flange: 2-1/4" x 5/16

Finish: Steel (STL) Packed: 100 per carton

Features: Nylon round groove sheave;

for use with KV tracks 455, 467, and 469





















Plastic Door Track Assemblies for Sliding Doors

P2413 1/8" Door Assembly Kits

Size: 48", 72" lengths
Finish: Tan (TAN)
Packed: 10 kits per carton

P2413 1/8" Door Assembly Kits					
Product	Finish	Length	Door Size		
P2413 TAN 48	Tan (TAN)	48"	1/8"		
P2413 TAN 72	Tan (TAN)	72"	1/8"		



P2417 1/4" Door Assembly Kits

Size: 48", 72" lengths
Finish: Tan (TAN), White (WH)
Packed: 10 kits per carton

P2417 1/4" Door Assembly Kits				
Product	Finish	Length	Door Size	
P2417 TAN 48	Tan (TAN)	48"	1/4"	
P2417 TAN 72	Tan (TAN)	72"	1/4"	
P2417 WH 48	White (WH)	48"	1/4"	
P2417 WH 72	White (WH)	72"	1/4"	



P2421 1/2" Door Assembly Kits

Size: 48", 72" lengths
Finish: Tan (TAN)
Packed: 10 kits per carton

P2421 1/2" Door Assembly Kits					
Product	Finish	Length	Door Size		
P2421 TAN 48	Tan (TAN)	48"	1/2"		
P2421 TAN 72	Tan (TAN)	72"	1/2"		






P2419 3/4" Door Assembly Kits

Size: 48", 72" lengths Finish: Tan (TAN) Packed: 10 kits per carton

P2419 3/4" Door Assembly Kits				
Product	Finish	Length	Door Size	
P2419 TAN 48	Tan (TAN)	48"	3/4"	
P2419 TAN 72	Tan (TAN)	72"	3/4"	





Finish:





Tan White (TAN) (WH)

99

Non-stock item – minimum order quantities and additional lead time may apply.

Steel Tracks and Guides for Sliding Doors

455 STL 144 Lower Track

Size: 19/64" height x 21/32" width x 144" length

Finish: Wrought Steel (STL)
Origin: Made in the USA

Packed: 1 each

455 SS 144 Lower Track

Size: 19/64" height x 21/32" width x 144" length

Finish: Stainless Steel (SS)
Origin: Made in the USA

Packed: 1 each

467 STL 144 Lower Track

Size: 19/64" height x 7/16" width x 144" length

Finish: Steel (STL)
Origin: Made in the USA

Packed: 1 each

469 ZC 144 Double Lower Track

Size: 1/4" height x 1" width x 144" length

Finish: Zinc (ZC)
Origin: Made in the USA

Packed: 1 each

953 ZC 144 Top Door Divider

Size: 5/8" height x 5/8" width x 144" length

Finish: Pre-coated Steel (ZC)
Origin: Made in the USA

Packed: 1 each

Features: Upper T-guide separates the sliding door at the top



Roll-Ezy Ball-Bearing Track Systems

Complete Assembly



P992 Large Glass Door Track Assembly Kit

Includes: (1) 993 Upper Channel, (2) 995 Shoe, (2) 997 Carrier,

(1) 999 Lower Track

Origin: Made in the USA Packed: 1 set per carton

Features: For large glass door applications, for 1/4" thick glass installations

Complete Assemblies	
Product	Installation Opening Width
P992 ZC 36	36"
P992 ZC 48	48"
P992 ZC 60	60"
P992 ZC 72	72"

Installation Notes & Recommendations: Knape & Vogt does not recommend butt-joints and/or openings longer than 12 feet. We recommend that the height to width ratio for glass doors should not exceed 2:1.



953 ZC 144 Top Door Divider

Size: 5/8" width x 5/8" height x 144" length

Finish: Zinc (ZC)
Origin: Made in the USA

Packed: 1 each

Features: Pre-coated steel upper T-guide for wood framed installations;

for use with 1/4" glass doors only; for large glass door applications

993 ZC 144 Upper Channel

Size: 15/16" wide x 5/8" height x 144" length

Finish: Zinc (ZC)
Origin: Made in the USA

Packed: 1 each

Features: Upper channel for top and ends of opening; wide divider

maintains door position; for large glass door applications

995 ZC 144 Door Shoe

Size: 21/64" wide x 7/16" height x 144" length

Finish: Zinc (ZC)
Origin: Made in the USA

Packed: 1 each

Features: Lightly curved bottom for free rolling position on ball-bearings;

for 1/4" glass, scant or full; for large glass door applications

997 ZC 144 Ball Carrier

Size: 3/8" wide x 17/32 height x 144" length

Finish: Zinc (ZC)
Origin: Made in the USA

Packed: 1 each

Features: Ball-bearing carrier has free rolling balls on 3" centers;

unique design creates two point suspension between shoe

and lower rack; for large glass door applications

999 ZC 144 Lower Track

Size: 1" wide x 1" high x 144" length

Finish: Zinc (ZC)
Origin: Made in the USA
Packed: 1 each

Packed: 1 each
Features: Balls ride freely on curved anvil with no contact against

aidea of lawer treels for large gloss door applications

sides of lower track; for large glass door applications











NOTE: For each foot of opening use 1' of upper channel and lower track and shoe (plus 1" per door for overlap), with 1-1/2' of carrier (1-1/2 times door width for each door). Glass is cut 1-1/4" lower than height of opening.

Roll-Ezy Aluminum Track Systems

Complete Assembly



P1092 Small to Medium Glass Door Track Assembly Kit

(1) 1093 Upper Channel, (4) 1097 Rollers,

(4) 1085 Vinyl Guides, (2) 1095 Shoe, (1) 1099 Lower Track

Packed: 1 set per carton

Features: For small to medium size glass door installations;

for 1/4" thick glass

Complete Assemblies	
Product	Length
P1092 ANOD 36	36"
P1092 ANOD 48	48"
P1092 ANOD 60	60"
P1092 ANOD 72	72"

Installation Notes & Recommendations: Knape & Vogt does not recommend butt-joints and/or openings longer than 12 feet. We recommend that the height to width ratio for glass doors should not exceed 2:1.



1093 144 Upper Channel

1-3/16" width x 9/16" height x 144" length Size:

Finish: Aluminum (AL) Origin: Made in the USA 1 each

Packed:

Features: Double channel for tops, bottoms, and ends; for small to

medium size glass door installations; for 1/4" thick glass

1095 144 Door Shoe

Size: 27/64" width x 1" height x 144" length

Finish: Aluminum (AL) Origin: Made in the USA

Packed: 1 each

Features: Rollers to be inserted in the bottom: for small to medium

size glass door installations; for 1/4" thick glass

1096 144 Single Lower Track

31/64" width x 15/32" height x 144" length Size:

Finish: Aluminum (AL) Origin: Made in the USA

Packed: 1 each

Features: For single doors, or may be used with 1093 double channel

for covered installation; for small to medium size glass door

installations; for 1/4" thick glass

NOTE: Cut glass 1-1/2" lower than opening when using 1096/1093 tracks

1099 144 Double Lower Track

1-1/16" width x 1/4" height x 144" length Size:


Finish: Aluminum (AL) Origin: Made in the USA

Packed: 1 each

For small to medium size glass door installations; Features:

for 1/4" thick glass

NOTE: Cut glass 1-3/16" lower than opening when using 1099 track



1085 VINYL Guide

Size: 7/8" length Vinyl (VINYL) Finish: Origin: Made in the USA Packed: 100 per carton

Features: Vinyl guide fits over the top of glass for noiseless operation

in upper channel; for small to medium size glass door

installations; for 1/4" thick glass

1087 RUB Rubber Bumper

Finish: Rubber (RUB) Packed: 100 per carton

Features: Rubber bumper installs in jambs to cushion glass





1097 NYLON Nylon Rollers

Finish: Nylon (NYLON) Origin: Made in the USA Packed: 100 per carton

Features: Rubber roller press fits into bottom of 1095 shoe

1098 ZC Steel Ball-bearing Roller

Finish: Zinc (ZC) Made in the USA Origin: Packed: 20 per carton

Features: Steel ball-bearing roller press fits into bottom

of 1095 shoe



Round Closet Rods

660 Series Heavy-Duty Round Closet Rods WOODWORK



660 Series Heavy-Duty Round Closet Rod

Diameter: Outside 1-1/16"; Inside 29/32"; Wall thickness 0.087"

Finish: Stainless Steel (SS) Origin: Made in the USA Packed: 6 per carton

Features: Steel core with solid stainless steel

660 Series Heavy-Duty Round Closet Rods	
Length	Stainless Steel (SS)
72"	660 SS 72
96"	660 SS 96
120"	660 SS 120
144"	660 SS 144



750 Series Heavy-Duty Round Closet Rods

750 1 Heavy-Duty Round Closet Rod

Diameter: Outside: 1-1/16"; Inside: 29/32"; Wall thickness: 0.075"

Finish: Chrome (CHR) Packed: 6 per carton



Diameter: Outside 1-5/16"; Inside 1-5/32"; Wall thickness 0.075"

Finish: Chrome (CHR) Packed: 6 per carton

750 Series Heavy-D		
Length	750 1 Series	750 5 Series
72"	750 1 72	750 5 72
96"	750 1 96	750 5 96
120"	750 1 120	750 5 120
144"	750 1 144	750 5 144



770 Series Extra-Duty Round Closet Rods



770 1 Extra-Duty Round Closet Rod

Diameter: Outside: 1-1/16"; Inside: 27/32"; Wall thickness: 0.106"

Finish: Chrome (CHR) Packed: 6 per carton



Outside: 1-5/16"; Inside: 61/64"; Wall thickness: 0.106" Diameter:

Finish: Chrome (CHR) 6 per carton Packed:

770 Series Extra-Duty Round Closet Rods		
Length	770 1 Series	770 5 Series
72"	770 1 72	770 5 72
96"	770 1 96	770 5 96
120"	770 1 120	770 5 120
144"	770 1 144	770 5 144



Round Closet Rod Mounting Flanges and Accessories

734 CHR Closed Wall-Mount Flange*

Finish: Chrome (CHR)

Packed: 50 per carton with screws Holes: 2 screw holes on 2" centers Features: For 660, 750 1 and 770 1

Series Closet Rods



735 CHR Open Wall-Mount Flange*

Finish: Chrome (CHR)

Packed: 50 per carton with screws Holes: 2 screw holes on 2" centers Features: For 660, 750 1 and 770 1

Series Closet Rods




764 CHR Closed Wall-Mount Flange*

Chrome (CHR) Finish:

Packed:

Holes: Features:



766 CHR Open Wall-Mount Flange*

Finish: Chrome (CHR)

12 per carton with screws Packed:

Holes: 2 holes on 2-1/4" centers, one at 90° Features: For 750 5 and 770 5 Series Closet Rods



730 ANO End Cap

Finish: Anochrome (ANO) Packed: 50 per carton

For use with 660 Series Closet Rods Features:



731 ANO End Cap

Finish: Anochrome (ANO) Packed: 50 per carton

Features: For 750 1 and 770 1 Series Closet Rods NOTE: May need to modify prongs for 750 1 installation



732 ANO End Cap

Finish: Anochrome (ANO) Packed: 50 per carton

For 750 5 and 770 5 Series Closet Rods Features: NOTE: May need to modify prongs for 750 5 installation



757 ANO Pilaster Flange*

Finish: Anochrome (ANO) Origin: Made in the USA Packed: 100 per carton

Features: Fits 255 or 233 series pilaster; for 660,

750 1 and 770 1 Series Closet Rods

632 CHR Line Bore Flange

Finish: Chrome (CHR) Packed: 100 per carton

Features: Screw hole for extra mounting strength;

two 5mm pins; for use with 750 1 and

770 1 Series Closet Rods



760 ANO 24 Center Closet Rod Support

Anochrome (ANO) Finish: Origin: Made in the USA

Packed: 12 per carton with screws

Features: Center support 24" can be cut to size;

for 660, 750 1 and 770 1 Series Closet Rods





880 Series Extra-Duty Oval Closet Rods

Oval Closet Rods

880 Series Oval Closet Rod

Size: 30mm high x 15mm wide; wall thickness 1.2mm

Finish: Chrome (CHR) 10 per carton lengths Packed:

Heavy gauge, invisible welded seam Features:

Length	Chrome (CHR)
96"	880 CHR 96
144"	880 CHR 144



Mounting Flanges

881 CHR Mounting Flange

Finish: Chrome (CHR) Packed: 50 per carton

Holes: Screw hole for extra mounting strength

Features: For use with 880 oval tubing; for line bore installation;

two 5mm pins



Front

Adjustable Closet Rods


KV2 Series Adjustable Closet Rods

Finish: White (WH), Zinc (ZC)

Features: Attached end flanges; hardware included;

2-1/2" hook drop depth

Pack Configuration				
Standard Pack	10 per carton up to	10 per carton up to 60"-96" size; 5 per carton for 72"-120" and above		
Builders Pack (BP)	20 per carton	20 per carton		
	KV2 Zinc (ZC)	KV2 Zinc (ZC) KV2 White (WH) KV2BP Zinc (ZC)		
Length	Standard Pack	Standard Pack	Builders Pack (BP)	
18"-30"	KV2 ZC 18	KV2 WH 18	KV2BP ZC 18	
30"- 48"	KV2 ZC 30	KV2 WH 30	KV2BP ZC 30	
48"-72"	KV2 ZC 48	KV2 WH 48	_	
60"-96"	KV2 ZC 60	KV2 WH 60	_	
72"-120"	KV2 ZC 72	KV2 WH 72	_	
96"-144"	KV2 ZC 96	_	_	



Finish: Anochrome (ANO)
Packed: 12 per carton

Features: Use with installations of 72" or more in width





RP0020 Series Heavy-Duty Adjustable Closet Rods

Diameter: 1-1/4" outside diameter

Finish: Brushed Nickel (BN), Bronze (BRZ), Chrome (CH), Warm White (WT)

Packed: 6 per carton

Features: Adjustable heavy-duty closet rods are quick and simple

to install and create a quality finished look; the rod quickly attaches to included flanges for easy installation, no cutting

necessary; hardware included

Heavy-D	avy-Duty Adjustable Closet Rods			
Length	Brushed Nickel (BN)	Bronze (BRZ)	Chrome (CH)	Warm White (WT)
30"-48"	RP0020-30/48BN	RP0020-30/48BRZ	RP0020-30/48CH	RP0020-30/48WT
48"-72"	RP0020-48/72BN	RP0020-48/72BRZ	RP0020-48/72CH	RP0020-48/72WT
72"–120"	RP0020-72/120BN	RP0020-72120BRZ	RP0020-72/120CH	RP0020-72/120WT



Closet Shelf Brackets

Regular-Duty Adjustable Shelf Bracket

Finish: Warm White (WT)
Packed: 20 per carton

Features: Holds up to 150 lbs. per pair; install with or without

wall cleat; 13 gauge steel platform; 16 gauge steel support strut; for 11" to 14" deep shelves; adjusts

from 10-1/4" to 10-3/4"

Size	Warm White (WT) Finish
12"	0040-WTS

Heavy-Duty Fixed Shelf Bracket

Size: 12", 16", 20"

Finish: Chrome (CH), Warm White (WT)

Packed: 20 per carton

Features: Holds up to 500 lbs. per pair;

14 gauge steel construction

Size Chrome (CH) Finish Warm White (V		Warm White (WT) Finish
12"	RP-0046-CH	RP-0046-WT
16"	_	RP-0046-15WT
20"	_	RP-0048-19WT

Heavy-Duty Fixed Shelf Bracket

Size: 16", 20"
Finish: Warm White (WT)
Packed: 20 per carton

Features: Holds up to 500 lbs. per pair; optional rod

hook (WS46-WT HOOK); 14 gauge

steel construction

Size	Warm White (WT) Finish
16"	WS46-12WT
20"	WS46-16WT

Closet Rods and Shelf Brackets

Adjustable Closet Rod and Shelf Brackets

Economy Rod and Shelf Bracket

Finish: Warm White (WT) 40 per carton Packed: Hook Depth: 2-1/2"

Features: Holds up to 150 lbs. per pair; use with

> up to 11"-14" deep shelves; must be installed with wall cleat; 12 gauge steel platform; KV2 compatible

Warm White (WT)

0041-B

Regular-Duty Adjustable Rod and Shelf Bracket

Finish: Warm White (WT) 20 per carton Packed: Hook Depth: 2-1/2"

Features: Holds up to 300 lbs. per pair; KV2

> compatible; use with up to 1-3/8" OD closet rods; for 11"-14" deep shelves; install with or without wall cleat; shelf platform is 10" without cleat;

14 gauge steel platform

Warm White (WT) RP-0042-BWT

Regular-Duty Adjustable Rod and Shelf Bracket

Finish: Warm White (WT) Packed: 20 per carton

Hook Depth: 3'

Holds up to 300 lbs. per pair; use with Features:

> up to 1-3/8" OD closet rods; for 11"-14" deep shelves; install with or without wall cleat; shelf platform adjusts from

10-1/4"-10-3/4"; 14 gauge steel construction

Warm White (WT)

RP-0043-WT

Heavy-Duty Adjustable Rod and Shelf Bracket

Cream White (CREAM), Finish:

Bright White (WH)

Packed: 10 per carton

Hook Depth: 3"

Holds up to 500 lbs. per pair; Features:

use with up to 1-3/8" OD

closet rods; for 11"-14" deep shelves; install with or without wall cleat; shelf platform adjusts from 10-1/4" - 10-3/4";

low profile design; 13 gauge steel construction

Cream White (CREAM) Bright White (WH) 1194 CREAM 1194 WH

Fixed Closet Rod and Shelf Brackets

Regular-Duty Fixed Rod and Shelf Bracket

Finish: Warm White (WT) Packed: 20 per carton Hook Depth: 2-1/2"

Features: Holds up to 400 lbs. per pair; KV2 compatible;

use with up to 1-3/8" OD closet rods; for 11"-14" deep shelves; 10-7/8" shelf platform; one-piece design provides superior

strength; 16 gauge steel construction

Warm White (WT) RP-0044-BWT

Heavy-Duty Fixed Rod and Shelf Bracket

Finish: Cream White (CREAM)

Bright White (WH)

Packed: 10 per carton

Hook Depth: 2-1/2"

Features: Holds up to 500 lbs. per pair; KV2 compatible;

> use with up to 1-3/8" OD closet rods; for 11"-14" deep shelves; 11" shelf platform; 12 gauge

steel construction

Cream White (CREAM) Bright White (WH) 1195 CREAM 1195 WH

Heavy-Duty Fixed Rod and Shelf Bracket

Finish: Chrome (CH), Warm White (WT)

Packed: 20 per carton

Hook Depth: 3"

Features: Holds up to 500 lbs. per pair; use with

> up to 1-3/8" OD closet rods; for 11"-14" deep shelves; 11" shelf platform; one-piece design provides superior strength; 14 gauge

steel construction

White (WT) Chrome (CH) RP-0045-CH RP-0045-WT

Heavy-Duty Fixed Rod and Shelf Bracket

Finish: Warm White (WT) Packed: 20 per carton

Hook Depth: 3"

Features: Holds up to 500 lbs. per pair;

use with up to 1-3/8" OD closet rods;

for 10-1/2" - 14" deep shelves; 10-5/16" shelf platform; patented Slide-Thru™ feature; 14 gauge

steel construction

Warm White (WT)

RP-0052-WT

WT

CH

Non-stock item – minimum order quantities and additional lead time may apply

Closet Rods and Shelf Brackets

Fixed Closet Rod and Shelf Brackets

Extra-Duty Fixed Rod and Shelf Bracket

Finish: Brushed Nickel (BN), Bronze (BRZ), Chrome (CH),

Warm White (WT)

Packed: 10 per carton – BN, CH, WT

6 per carton – BRZ


Hook Depth: 3"

Features: Holds up to 1,000 lbs. per pair; for 11-1/2" -14" deep shelves;

snap-in pole feature for 1-1/4" – 1-5/16" OD closet rods; 11"-1/4" shelf platform; patented Slide-Thru™ feature;

10 gauge steel construction

Brushed Nickel (BN)	Bronze (BRZ)	Chrome (CH)	White (WT)
RP-0495-BN	RP-0495-BR7	RP-0495-CH	RP-0495-WT



Heavy-Duty Fixed Rod and Shelf Bracket

Finish: Warm White (WT)
Packed: 5 per carton
Hook Depth: 3-3/4"

Features: Holds up to 500 lbs. per pair; for 14"–18" deep shelves;

snap-in pole feature for 1-1/4"-1-5/16" OD closet rods; 14" shelf platform; patented Slide-Thru™ feature; 13 gauge

steel construction

Warm White (WT)

RP-0496-WT




Utility and Coat Hooks

Utility Hooks

1132 ANO Single Prong Utility Hook

Size: 4", 6" and 10"
Finish: Anochrome (ANO)
Origin: Made in the USA



SKU Number	Length
1132 ANO 4	4"
1132 ANO 6	6"
1132 ANO 10	10"

PKV3 ANO Heavy-Duty Single Prong Utility Hook

Size: 5-1/2" or 10" lengths Finish: Anochrome (ANO) Origin: Made in the USA

Packed: 10 units per carton with screws
Features: Sturdy steel rod for extra hanging space

SKU Number	Length	
PKV3 ANO 5-1/2	5-1/2"	
PKV3 ANO 10	10"	

Garment Hook

2038 CHR Coat and Hat Hook

Finish: Chrome (CHR)

Packed: 12 units per carton with screws
Features: Classic institutional garment hook;

coat and hat hook



Non-stock item – minimum order quantities and additional lead time may apply.

Valet Rods, Clothing Carriers and Towel Bars

Hang Rod

753 ANO Telescopic Valet Rod

Size: 7/16" diameter rod, extends 5/8"-8-1/4"

Finish: Anochrome (ANO)
Origin: Made in the USA

Packed: 1 per carton with screws; 12 per carton

Features: Extends from 5/8"–8-1/4"; for convenient hanging storage;

retract to get it out of the way when not in use



KV1 ANO Clothing Carrier

Size: 10": fits 10" shelf only

12": fits 12"-16" depth shelves 16": fits 16"-20" depth shelves 20": fits 20"-24" depth shelves

Finish: Anochrome (ANO)
Origin: Made in the USA

Packed: 1 per bag with screws, 12 bags per carton

Features: Mounts under closet shelves, greatly increasing capacity,

and makes garments more accessible

SKU Number	Travel	
KV1 ANO 10	10"	
KV1 ANO 12	12"	
KV1 ANO 16	16"	
KV1 ANO 20	20"	

Heavy-Duty Slide-Out Towel Bar

P793 ANO Slide-Out Towel Bar

Size: 18" length x 5" width Finish: Anochrome (ANO) Packed: 10 units per carton

Features: Side mounts to either left or right hand side of the cabinet;

rack mounts with 4 screws; all steel construction; three bars

accommodate at least three towels or cloths







Non-stock item – minimum order quantities and additional lead time may apply.

Index

Index	212 80	516 96	1195 108	8500-93 11, 13, 19, RP-0496 109
4x4 Pocket Door Full	213C 80	517 96	1300 11	20, 21, 24, 25, 26, 27, KV Hinge Kits 62
Overlay Kit 61	215 86	521 96	1303 11	28, 29, 38, 39, 51, 54, TT100 28
0035 86	217 86	580 98	1547 96	55, 56 TT401 28, 29
0036 86	221 85	582 98	1548 96	8500T 51 TT401B 28, 29
0040 107	229 66	592 98	1805 12	8505 38 WS46 107
0041-B 108	233 67	594 98	1980 91	8520 39
71 68	237 67	607 98	1987 79	8525 39
80 69	238 67	620 98	1987 SS 81	8600 40
80-88DP 70	239 66	632 104	2038 110	8605 40
82 73	242 67	660 103	2070 31	8620 41
82DP 64, 73	243 66	701 95	4101B 14, 15	8625 41
83 75	244 66	704 95	4104B 14, 15	8650FM 42
85 77	255 65	730 104	4400 14	8655FM 42
87 79, 81	255-81N 67	731 104	4450 15	8810 43
87-10 80	256 66	732 104	4461D 53	8815 43
101 12, 72	266 94	734 104	4500 29	8820 44
102 72	268 94	735 104	6092 94	8825 44
103 72	277 94	750 103	6094 94	8900 45
103-1/2L 72	278 94	753 111	6300 48	8908 46
103-1/2R 72	288 94	757 66, 104	6340 RB 48, 49	24276 66
104 72	306 94	760 104	6400 49	29201 106
104-1/2 72	309 94	764 104	6500 37	GS2070 31
106 64, 77, 103	318 94	766 104	6505 37	GS4200 25
107 64, 77	320 96	770 103	6875 94	GS4205 25
113L 75, 77	323 96	801X 93	8000 50	GS4260 26
113R 75, 77	324 96	803X 93	8050 56	GS4270 27
0117 86	325 84	813 93	8070 58	GS4340 25, 26, 27
0118 86	326 83	819X 95	8071 58	KV1 111
119 72, 75, 80	330 83	836 93	8072 58	KV2 106
129 72, 77, 80	331 84	880 105 881 105	8080 59	MuV+ 32
134 75 135 75	332 83 333 84	901 93	8081 59 8082 59	MUV1D-RL 32, 33, 34, 35
136 72	335 84	903 93	8085 58, 59, 60	MUV2D-RL 32, 33,
137 72	338 83	905 93	8086 58, 59, 60, 62	34, 35
154 72	339 83	918 93	8090P 58, 59, 60	MUV3D-RL 32, 33,
159LL 75, 77	340 83	953 100, 101	8091 60	34, 35
160LL 71	341 96	962KA 97	8092 60	MuV+34 33
161LL 64, 76	342 96	963KA 97	8150 54	MuV+34HD 35
170 68	345 83	965 97	8157 54	MUV-124 32, 33, 34,
179 71	346 84	984KA 97	8250 55	35
180 70	348 83	986 95	8350 13	MuV+HD 34
181 71	400A 98	989 94	8400 17–18	MUV-RBM 32, 33
182 74	402 98	993 101	8400RV 22	MUV-RBP 32, 33
182BE 64, 73	420 97	995 101	8401 18, 19, 20, 21	P793 111
182DP 64, 73	422 97	997 101	8402 18, 19, 20, 21	P992 101
183 76	423 97	999 101	8403 18, 19, 20, 21,	P1092 102
185 78	424 97	1085 102	22, 24	P2413 99
186LL 80	427 98	1087 102	8404 18, 19, 20, 21,	P2417 99
186LL SS 82	429 98	1088 93	22, 24	P2419 99
187LL 80	430 98	1093 102	8405 19	P2421 99
187LL SS 82	455 100	1095 102	8407 20	PKV3 110
191 75, 77	467 100	1096 102	8414 21	RP0020 106
192 75, 77	469 100	1097 102	8417 22	RP-0042 108
200 87, 88	472 96	1098 102	8419 22	RP-0043 108
201 89, 90	475F 95	1099 102	8420 23	RP-0044 108
206 85	476F 95	1123 10, 11	8425 23	RP-0045 108
208 85	476T 95	1132 110	8450FM 24	RP-0046 107
210 80	510 96	1175 10	8455FM 24	RP-0052 108
211 80	513 96	1194 108	8500 38	RP-0495 109

Knape and Vogt Limited Warranty

Limited Lifetime Warranty for Commercial Business Products

15 Year Limited Warranty for Ergonomics Products

This warranty is given to the initial purchaser of new commercial and ergonomic products purchased from Knape & Vogt Manufacturing Company and its subsidiaries. The warranty covers defects in materials and workmanship. The warranty does not apply to defects resulting from misuse, damage or abuse, normal wear and tear, accident, modification, improper installation or maintenance, third party materials or damage during shipping. The warranty is not transferable and does not cover any subsequent purchasers of the products.

Definitions of the specific warranty time periods by product can be obtained from Customer Service at 1.800.253.1561. The warranty time period begins on the date of purchase for all products. Applicable warranty time periods are based on one 8-hour shift per day usage, and warranty time periods are adjusted and shortened proportionally for any multiple shift or excess usage.

During the warranty period, Knape & Vogt, will, at its option, repair or replace any defective product with a comparable product or component. This limited warranty is for repair or replacement of defective products only and does not cover any other costs such as removal, installation, or other related expenses.

For warranty service, please contact Knape & Vogt Manufacturing Company, 2700 Oak Industrial Drive, Grand Rapids, MI 49505, Attention: Customer Service. Information regarding the claimed defect and date of purchase of the product must be provided. Any defective product must be returned postage or freight prepaid to Knape & Vogt.

THIS LIMITED WARRANTY CONSTITUTES THE ONLY WARRANTY FOR THE PRODUCTS AND ALL OTHER WARRANTIES OR REPRESENTATIONS, EXPRESS OR IMPLIED, BY OPERATION OF LAW OR OTHERWISE, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY DISCLAIMED. (Some states do not allow limitations on how long an implied warranty lasts.)

THIS LIMITED WARRANTY CONSTITUTES THE SOLE REMEDY AVAILABLE WITH REGARD TO ANY DEFECTIVE PRODUCTS. KNAPE & VOGT SHALL NOT BE LIABLE FOR ANY INCIDENTAL, INDIRECT, CONSEQUENTIAL OR SPECIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOSS OF TIME, INCONVENIENCE, OR LOST REVENUES OR PROFITS. (Some states do not allow the exclusion or limitation of incidental or consequential damages.)

Copyright ©2021 Knape & Vogt Manufacturing Company, all rights reserved. Standard KV Commercial Warranty

Return Policy

Return Policy for special order or nonstock items:

We're sorry, we cannot accept returns on nonstock products or special order products unless there is a Knape & Vogt error — which we will be happy to correct. To return product(s), please follow these procedures:

Please contact Knape & Vogt Customer Service at 1.800.253.1561. A Customer Service Representative will assist you with getting a Return Goods Authorization (RMA) number. The original P.O. is required to receive a RMA number. Please return product within 30 days of issuance of the RMA number.

Restocking Fees:

- All resalable product returned in original resalable packaging will be assessed a 25% fee for restocking and handling.
- Minimum fee is \$25.
- All resalable products not returned in resalable original packaging will be assessed a 25% fee for repackaging in addition to the 25% restocking and handling fee.
- Above referenced fees will be waived on returns resulting from a Knape & Vogt error.

Shipping:

You are responsible for all return shipping charges to return the product unless we made an error in shipping your order, i.e., the product we shipped is not the one you ordered, or is defective.

In the US, please ship to: Knape & Vogt

Return Goods Department, 3800 Eastern Ave SE, Wyoming, MI 494509

In Canada, please ship to:

Knape and Vogt/ Vanguard, Attn: Return Goods Department, 265 Export Blvd, Mississauga, ON L5S 1Y4

- Ensure the product(s) are properly packaged to prevent shipping damage.
- Include RMA number with return.
- Ensure all products returned match quantities and products listed on the assigned RMA.

Credit:

- A credit memo will be issued upon inspection and approval of the returned product.
- Upon receipt and inspection Knape & Vogt will determine credit amount and notify you of any discrepancies.
- DO NOT make any financial adjustments to your account prior to Knape and Voqt issuing a credit memo for returned goods.
- Please allow a minimum of 15 days for us to receive and process your return.
- We will credit or refund the value of the product total and any taxes you were charged less applicable fees. (excluding delivery charges).
- · Refunds will be given in the same form of payment. Adjustments to credit cards should appear within two billing cycles.

Replacement Orders:

- · Any replacement orders will be charged to your account.
- A credit memo will be issued for returned products that have been approved.

RMA Status Information:

- Visit www.customercareconnection.com.
- Enter your account information.
- If you do not already have your account set up for this free service, please register at www.customercareconnection.com.
- Your satisfaction is our priority. We are happy to accept returns or exchanges for any resalable or defective products within 60 days of the shipping date.





TORONTO
Tel.: (416) 798-7198
Email: cnmdtor@canmade.com
www.canmade.com

MONTRÉAL Tél.: (514) 351-1460 Email: info@canmademtl.com www.canmademtl.com



2700 Oak Industrial Dr. NE Grand Rapids, MI 49505-6026 USA Tel: 1.800.253.1561 | 616.459.3311

Fax: 877.636.3290 www.kv.com

This and other KV literature is available for download at www.kv.com > Resource Library

Knape & Vogt reserves the right to change product specifications at any time without notice and without incurring responsibility for existing units.

 $\ensuremath{\texttt{@}}\xspace2021$ Knape & Vogt. KV and the KV logo are trademarks of Knape & Vogt.